3-1617543-5 - ACTIVE

CII

TE Internal #: 3-1617543-5 TO-5/.100 Grid Relays, Contact Arrangement 2 Form C, DPDT, 2 C /O, 20VDC Input Voltage, Without MOSFET Driver, Without Transistor Driver

View on TE.com >

Relays, Contactors & Switches > Relays > Mil-Aero Relays > TO-5/.100 Grid Relays



Contact Arrangement: 2 Form C, DPDT, 2 C/O

Input Voltage: 20 VDC

Coil Suppression Diode: Without

MOSFET Driver: Without

Transistor Driver: Without

Features

Product Type Features

 Enclosure Type
 Hermetically Sealed

 Relay Type
 Military/Aerospace High Performance



Coil Latching	Without
Product Type	Relay
MOSFET Driver	Without
Configuration Features	
Transistor Driver	Without
Electrical Characteristics	
Coil Magnetic System	Non-Polarized, Monostable
Vibration	30G's, 10 – 3000Hz
Actuating System	DC
Shock	75G's, 6ms
Coil Power Measurement	Milliwatts
Input Voltage	20 VDC
Coil Suppression Diode	Without
Coil Voltage	36 VDC
Coil Resistance	6500 Ω

3-1617543-5

TO-5/.100 Grid Relays, Contact Arrangement 2 Form C, DPDT, 2 C/O, 20VDC Input Voltage, Without MOSFET Driver, Without Transistor Driver



Coil Power Rating (DC)	199 mW
Coil Polarity Protection Diode	Without
Contact Switching Voltage (Max)	28
Contact Features	
Contact Current Class	Low Level – 1 A
Pin Configuration	.200" x .300" Spreader Pad
Contact Arrangement	2 Form C, DPDT, 2 C/O
Contact Current Rating	1 A
Termination Features	
Termination Type	PC Pins
Mechanical Attachment	
Mounting Type	Printed Circuit Board
Usage Conditions	
Operating Temperature Range	-65 – 125 °C

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUN 2020 (209) Candidate List Declared Against: JUL 2019 (201) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished

3-1617543-5

TO-5/.100 Grid Relays, Contact Arrangement 2 Form C, DPDT, 2 C/O, 20VDC Input Voltage, Without MOSFET Driver, Without Transistor Driver



product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



Customers Also Bought







Documents

CAD Files 3D PDF

L For support call+1 800 522 6752

3-1617543-5

TO-5/.100 Grid Relays, Contact Arrangement 2 Form C, DPDT, 2 C/O, 20VDC Input Voltage, Without MOSFET Driver, Without Transistor Driver



3D

Customer View Model ENG_CVM_CVM_3-1617543-5_O.2d_dxf.zip English Customer View Model ENG_CVM_CVM_3-1617543-5_O.3d_igs.zip English Customer View Model ENG_CVM_CVM_3-1617543-5_O.3d_stp.zip English

Datasheets & Catalog Pages 5-1773450-5_sec1_MS

English

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: JMSC-36XPS