




|   |               |                  |                    |
|---|---------------|------------------|--------------------|
| Connector: RP-SMA Jack (Male Pin)               |               |                  |                    |
| Termination: PCB Edge Multi-Mount, 0.062" Thick |               |                  |                    |
| Part Number                                     |               | CONREVSMA006.062 | CONREVSMA006.062-G |
| Connector Part                                  | Material      | Finish           | Finish             |
| Bodies  | Body: Brass   | Nickel           | Gold               |
|   | Nut: Brass    | Nickel           | Gold               |
|   | Washer: Brass | Nickel           | Gold               |
| Center Contact                                  | Pin: Brass    | Gold             | Gold               |
| Insulator                                       | PTFE          | -                | -                  |

| REVISIONS |  |           |      |
|-----------|--|-----------|------|
| REV       | DESCRIPTION                              | DATE      | APPV |
| A         | INITIAL RELEASE OF LINX INTERNAL DRAWING | 01/MAR/19 | CLL  |



# NOTES: (UNLESS OTHERWISE SPECIFIED)

1. ALL DIMENSIONS ARE IN mm [INCHES].
2. DIMENSIONS APPLY AFTER FINISHING.
3. MANUFACTURE TO BE COMPLIANT WITH EU RoHS DIRECTIVE, USE MATERIALS THAT DO NOT CONTAIN REACH SUBSTANCES OF VERY HIGH CONCERN >1000ppm, AND USE DRC CONFLICT-FREE SOURCED MATERIALS.
4. SAFETY BREAK ALL SHARP CORNERS AND EDGES 0.5 MAXIMUM.
5. SEE TABLE I FOR ELECTRICAL SPECIFICATIONS. (SHEET 2)
6. SEE TABLE II FOR ENVIRONMENTAL SPECIFICATIONS. (SHEET 2)
7. SEE TABLE III FOR MECHANICAL SPECIFICATIONS. (SHEET 2)
8. SEE PARTSLIST. "\*" INDICATES FINISH TYPE.



SCALE 1 : 1

NUT

WASHER

**WARNING:** THIS DRAWING CONTAINS PROPRIETARY INFORMATION THAT IS THE SOLE PROPERTY OF LINX TECHNOLOGIES, AND SHALL BE TREATED AS SUCH. NO DISCLOSURE OR REPRODUCTION OF THIS DOCUMENT IS PERMITTED, IN WHOLE OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF LINX TECHNOLOGIES OR ITS DESIGNATED AGENTS.

|           |   |                                    |                 |
|-----------|---|------------------------------------|-----------------|
| MATERIAL: | INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5. |                                    | PROJECTION:<br> |
|           | .X ±2.0<br>.XX ±1.00<br>.XXX ±.500                  | ANGLES: ±1°<br>SURFACE: $\sqrt{3}$ |                 |
| FINISH:   | DRAWN: M. SCHULTE                                   | DT: 21/JAN/19                      | SCALE: 3:1      |
|           | ENGR: DV  | DT: 08/MAR/19                      |                 |



159 ORT LANE  
MERLIN, OR 97532

TITLE:  
**RP-SMA FEMALE EDGE MULTI  
MOUNT FOR 0.062" THICK BOARD**

SIZE DWG. NO. REV  
**A** C-CONREVSMA006.062-p **A**

DO NOT SCALE DRAWING SHEET 1 OF 2

5 TABLE I

| Electrical Data       | Detail   |
|-----------------------|--|
| Impedance             | 50 $\Omega$  |
| Frequency Range       | 0 to 18 GHz  |
| Insulation Resistance | 5 000 M $\Omega$ min.                                      |
| Voltage Rating        | 500 V RMS  |
| Contact Resistance    | Center: $\leq 2.0$ m $\Omega$ Outer: $\leq 2.0$ m $\Omega$ |
| VSWR                  | $\leq 1.2 : 1$ @ 6 GHz                                     |


6 TABLE II

| Environmental Data       | Detail                                  |
|--------------------------|---|
| Corrosion (Salt spray)   | ASTM B-117                              |
| Thermal Shock            | MIL-STD-202 Method 107 test condition B |
| Vibration                | MIL-STD-202 Method 204 test condition D |
| Mechanical Shock         | MIL-STD-202 Method 213 test condition I |
| Temperature Range        | -65 °C to +165 °C                       |
| Environmental Compliance | RoHS                                    |


7 TABLE III

| Mechanical Data        | Detail                    |
|------------------------|---------------------------|
| Mounting Type          | PCB Edge Multi-Mount      |
| Fastening Type         | 1/4"-36 Threaded Coupling |
| Recommended Torque     | 0.57 N·m (5.0 in·lbs)     |
| Coupling Nut Retention | 60 lbs. min.              |
| Connector Durability   | 500 cycles min.           |
| Weight                 | 3.4 g (0.12 oz)           |




SEE SHEET 1 FOR REVISIONS



RECOMMENDED FOOTPRINT



RECOMMENDED MOUNTING HOLE



MOUNTING METHODS

| SIZE       | DWG. NO.             | REV          |
|------------|----------------------|--------------|
| <b>A</b>   | CONREVSMA006.062-*   | <b>A</b>     |
| SCALE: 3:1 | DO NOT SCALE DRAWING | SHEET 2 OF 2 |

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[CONREVSMA006.062-G](#)