

Product Facts

- Product available in temperature ranges of 500°F [260°C], 550°F [288°C], 650°F [343°C] and 1200°F [649°C]
- Product employs the famous "W" and "C" crimp
- Wide range of wire sizes
- Complete line of related application tooling
- Accommodates solid and/or stranded conductors



AMP Photo #103097

Heat...extreme heat...searing temperatures up to 1200°F [649°C]. This is one of the most challenging environments that electrical/electronic circuitry has ever entered.

If heat is an unavoidable dimension in your circuit design and production, this product is an important ally. In this AMP line of STRATO-THERM terminals and splices, you'll find high temperature circuit hardware. You'll also find solutions to other more familiar circuit problems such as vibration, corrosion and flash-over, when they occur at high temperatures.

Different types of high temperature terminals and splices found in this catalog are as follows:

PIDG Terminals and Splices, and Pre-Insulated Spare Wire Caps — 550°F [288°C] Range

PIDG Insulation Restriction Terminals — 550°F [288°C] Range

Post-Insulated Terminals and Splices — 550°F [288°C] Range

Uninsulated Terminals and Splices — 650°F [343°C] Range

Uninsulated Terminals and Splices — 1200°F [649°C] Range

Need more information?

Call the AMP Product Information Center:
1-800-522-6752

The Product Information Center is staffed with specialists well versed in all AMP products. The Center can provide you with:

- Technical Support
- Catalogs
- Technical Documents
- Product Samples
- AMP Authorized Distributor Locations

Specifications subject to change. Consult AMP Incorporated for latest design specifications.

© Copyright 1965, 1966, 1970, 1972, 1973, 1974, 1975, 1977, 1980, 1983, 1991 and 1998 by AMP Incorporated. All Rights Reserved.

AMP, STRATO-THERM, PIDG, DIAMOND GRIP, SOLISTRAND, CERTI-CRIMP, AMP-TAPETRONIC, DYNA-CRIMP are Trademarks.

TEFLON — Trademark of E.I. duPont, Inc.

Table of Contents

Introduction	3, 4
Insulated Terminals and Splices:	
PIDG (Pre-Insulated Diamond Grip)	
Ring Tongue Terminals—550°F [288°C] and 500°F [260°C]	5, 6
Insulation Restriction Ring Tongue Terminals—550°F [288°C]	6
Splices—500°F [260°C]	7
Spare Wire Caps—550°F [288°C]	7
Post Insulated	
Ring Tongue Terminals—500°F [260°C]	8
Splices—550°F [288°C] and 500°F [260°C]	8
Uninsulated Terminals and Splices:	
Non-Insulation Support	
Heat Resistant 650°F [343°C]—	
Ring Tongue Terminals	9, 10
Splices	10
High Temperature 1200°F [649°C]—	
Ring Tongue Terminals	11
Spade Tongue Terminals	12
Splices	12
Insulation Support	
Heat Resistant 650°F [343°C]—	
Ring Tongue Terminals	13
Splices	14
High Temperature 1200°F [649°C]—	
Ring Tongue Terminals	14, 15
Splices	16
Application Tooling	17-21
Numerical Index	22

Introduction

PIDG Terminals and Splices, and Pre-Insulated Spare Wire Caps 550°F [288°C] Range



Designed for reliable performance up to 550°F [288°C], this line of ring-tongue terminals, butt splices and spare wire caps features a pre-insulation sleeve of TEFLON TFE insulation material. A special funnel entry feature has been added to assure easy entry and proper seating of wire. The body is copper with a choice of gold over nickel plating or nickel plating. The terminal and splice barrel accommodates stranded wire conductors only. The spare wire caps are designed for unstripped wire.

PIDG Insulation Restriction Terminals 550°F [288°C] Range



These pre-insulated insulation restriction terminals prevent the insulation of thin-wall insulation wire from entering the terminal's wire crimp area during the crimping process.

Designed for reliable performance up to 550°F [288°C], these terminals feature a pre-insulation sleeve of TEFLON (TFE) insulation material.

Because of features such as a one-piece constructed inner sleeve and a wide funnel entry design which facilitates wire entry, standard STRATO-THERM PIDG tooling may be used to terminate this product.

Post-Insulated Terminals and Splices 550°F [288°C] Range



The temperature range of these terminals and splices is 550°F [288°C] for nickel plating and gold over nickel plated copper, and 500°F [260°C] for silver plating. These terminals and splices accommodate solid and/or stranded conductors.

Uninsulated Terminals and Splices 650°F [343°C] Range



These terminals and splices are available with and without wire insulation support. Both types are manufactured from electrolytic copper, plated with nickel. In the insulation support type, the support sleeve is fabricated from nickel-silver alloy. Both types accommodate solid or stranded conductors in various combinations. Wire size range is listed in the tabular data section.

Uninsulated Terminals and Splices 1200°F [649°C] Range



Nickel material is used for the body of both the terminal and splice. They are available with or without wire insulation support sleeve of nickel-silver alloy material. Accommodating either solid or stranded conductors in different combinations, these terminals and splices are made to cover a broad wire size range, listed in the tabular data section.

Terminals made of alumel and chromel material with nickel-silver alloy sleeves are available for thermocouple applications. When using either alumel or chromel conductors, a terminal of the same material should be selected.

Introduction (Continued)**Ordering Information**

All terminals and splices are listed according to wire size and type of terminal or splice. If the part number of the terminal or splice is known, refer to the Numerical Index, at the back of this catalog, for page location of tabular data.

In the Tabular Data Section, part numbers are available in either loose piece or tape mounted form.

When ordering tape mounted part numbers, specify the terminal or splice part number, the total quantity of parts desired (if applicable). The chart to the right lists by wire size the type of packaging available and the quantity per package.

Wire Range AWG	Standard Quantities	
	Loose Piece	Tape Mounted
26-14	1,000	5,000
26-22	—	2,500
12-10	500	2,500
8, 6, 4	100	—
2, 1/2	50	—

Note: Package quantities may vary with specific part numbers.

The Crimp

All five types of STRATO-THERM terminals and splices provide optimum corrosion and vibration resistance plus outstanding tensile characteristics.

All types, except the STRATO-THERM PIDG terminals, splices and pre-insulated spare wire caps, employ the famous "W" crimp which creates the precise electromechanical properties necessary for solid and/or stranded conductor combinations. A proper crimp will provide a uniform and permanent attachment. When mechanical pressure is applied to the terminal barrel, the wire inside is forced into the serrations or dimples of the barrel. Shown are four typical photomicrographs of the "W" crimp, illustrating the results of crimping various conductor combinations. In each case, the action of the crimp has compressed the conductors and the barrel into a homogenous mass.

"W" Crimp

One Solid

One Solid
Two Stranded

Two Solid




One Stranded

STRATO-THERM PIDG terminals and splices employ the equally reliable confined "C" crimp plus multiple position insulation support crimp for today's smaller insulated wires. This "C" crimp is especially suited to crimping the terminal barrel and insulation sleeve to stranded wire conductors. The photomicrograph shows the results of "C" crimping. Virtually the same electromechanical properties are obtained as in the "W" crimp. Pre-insulated spare wire caps and post-insulated splices are crimped with an "O" crimp configuration.

Confined C

Insulated Terminals and Splices

PIDG (Pre-Insulated Diamond Grip) Ring Tongue Terminals



Temperature Rating, Material and Finish

Insulation — TEFLON

Terminal Body — Copper per ASTM B152

Plating — Nickel per QQ-N-290, 550°F [288°C]. Gold per MIL-G-45204 over Nickel per QQ-N-290 500°F [260°C]

Metallic Sleeve — Copper per ASTM B152

Plating — Nickel per QQ-N-290, 550°F [288°C]

Related Product Data

Application Tooling — pages 17-21


Wire Size Circular Mils [mm ²]	Tongue Material Thickness Max.	Stud Size	Dimensions				Terminal Insulation Color	Wire Insulation Diameter Max.	Body Plating ¹	Part Numbers	
			W	C Min.	E Max.	L Max.				Loose Piece	Tape Mounted
26-24 238-475 [0.12-0.24]	.020 0.51	4	.203 5.16	.211 5.36	.542 13.77	.646 16.41	Black	.082 2.08	Nickel	50829	—
		6 M3.5	.250 6.35	.281 7.14	.612 15.54	.740 18.80	Black	.082 2.08	Nickel	50830	—
		4	.281 7.14	.250 6.35	.631 16.03	.774 19.66	Green	.100 2.54	Nickel	50831	—
		6 M3.5	.281 7.14	.250 6.35	.631 16.03	.774 19.66	Green	.100 2.54	Nickel	50831-1	—
22-20 509-1,290 [0.26-0.65]	.025 0.64	8 M4	.312 7.92	.281 7.14	.662 16.81	.821 20.85	Green	.100 2.54	Nickel	50832	50832-2
			.312 7.92	.281 7.14	.662 16.81	.821 20.85	Green	.100 2.54	Gold	332434	—
		10	.312 7.92	.281 7.14	.662 16.81	.821 20.85	Green	.100 2.54	Nickel	50832-1	50832-3
			.312 7.92	.281 7.14	.662 16.81	.821 20.85	Green	.100 2.54	Gold	1-332434-0	—
		4	.218 5.54	.156 3.96	.560 14.22	.672 17.07	Orange	.135 3.43	Nickel	50834	—
			.281 7.14	.250 6.35	.654 16.61	.797 20.24	Orange	.135 3.43	Nickel	50835	50835-1
			.281 7.14	.250 6.35	.654 16.61	.797 20.24	Orange	.135 3.43	Gold	332453	—
			.312 7.92	.281 7.14	.685 17.40	.844 21.44	Orange	.135 3.43	Nickel	50836	—
18-16 1,600-2,800 [0.81-1.42]	.033 0.84	8 M4	.312 7.92	.281 7.14	.685 17.40	.844 21.44	Orange	.135 3.43	Gold	332454	—
			.312 7.92	.281 7.14	.685 17.40	.844 21.44	Orange	.135 3.43	Nickel	50836-1	50836-3
		10	.312 7.92	.281 7.14	.685 17.40	.844 21.44	Orange	.135 3.43	Gold	1-332454-0	—
			.312 7.92	.281 7.14	.685 17.40	.844 21.44	Orange	.135 3.43	Nickel	50837	—
		1/4 M6	.468 11.89	.437 11.10	.841 21.36	1.078 27.38	Orange	.135 3.43	Nickel	50838	—
		3/8	.531 13.49	.531 13.49	.924 23.47	1.192 30.28	Orange	.135 3.43	Nickel	50839-1	—
		6 M3.5	.250 6.35	.171 4.34	.575 14.61	.703 17.86	White	.150 3.81	Nickel	50839-1	—
			.250 6.35	.171 4.34	.575 14.61	.703 17.86	White	.150 3.81	Gold	1-332438-0	—
		8 M4	.343 8.71	.281 7.14	.685 17.40	.859 21.82	White	.150 3.81	Nickel	50840	—
			.343 8.71	.281 7.14	.685 17.40	.859 21.82	White	.150 3.81	Nickel	50840-1	—
14 4,234 [2.15]	.033 0.84	10	.343 8.71	.281 7.14	.685 17.40	.859 21.82	White	.150 3.81	Gold	1-332439-0	—
			.343 8.71	.281 7.14	.685 17.40	.859 21.82	White	.150 3.81	Nickel	50841	—
		1/4 M6	.468 11.89	.437 11.10	.841 21.36	1.078 27.38	White	.150 3.81	Nickel	50841	—

¹Nickel plated parts are to be used with nickel plated wire. Gold plated parts are to be used with silver plated wire.

Note: "C" dimension applies from edge of metal wire barrel to center of stud hole.

Insulated Terminals and Splices (Continued)

PIDG (Pre-Insulated Diamond Grip) Ring Tongue Terminals (Continued)



Temperature Rating, Material and Finish

Insulation — TEFLON

Terminal Body — Copper per ASTM B152

Plating — Nickel per QQ-N-290, 550°F [288°C]. Gold per MIL-G-45204 over Nickel per QQ-N-290 500°F [260°C]

Metallic Sleeve — Copper per ASTM B152

Plating — Nickel per QQ-N-290, 550°F [288°C]


Related Product Data

Application Tooling — pages 17-21

Wire Size Circular Mils [mm ²]	Tongue Material Thickness Max.	Stud Size	Dimensions				Terminal Insulation Color	Wire Insulation Diameter Max.	Body Plating ¹	Part Numbers	
			W	C Min.	E Max.	L Max.				Loose Piece	Tape Mounted
12-10 5,180-13,100 [2.62-6.64]	.042 1.07	4	.281 7.14	.219 5.56	.794 20.17	.937 23.80	Black	.214 5.44	Nickel	50844	—
		6 M3.5	.375 9.53	.302 7.67	.893 22.68	1.083 27.51	Black	.214 5.44	Nickel	50845	—
		8 M4	.375 9.53	.302 7.67	.893 22.68	1.083 27.51	Black	.214 5.44	Nickel	50845-1	—
		10	.375 9.53	.302 7.67	.893 22.68	1.083 27.51	Black	.214 5.44	Nickel	50845-2	—
			.375 9.53	.302 7.67	.893 22.68	1.083 27.51	Black	.214 5.44	Gold	1-332446-1	—
		1/4 M6	.531 13.49	.437 11.10	1.012 25.70	1.280 32.51	Black	.214 5.44	Nickel	50846	—
		5/16 M8	.531 13.49	.468 11.89	1.059 26.90	1.327 33.71	Black	.214 5.44	Nickel	50847	—
		3/8	.593 15.06	.531 13.49	1.106 28.09	1.405 35.69	Black	.214 5.44	Nickel	50848	—

¹Nickel plated parts are to be used with nickel plated wire. Gold plated parts are to be used with silver plated wire.
Note: "C" dimension applies from edge of metal wire barrel to center of stud hole.

PIDG (Pre-Insulated Diamond Grip) Ring Tongue Terminals (Insulation Restricting)



Temperature Rating, Material and Finish

Insulation — TEFLON

Terminal Body and Metallic Sleeve — Copper per ASTM B152

Plating — Nickel per QQ-N-290, 550°F [288°C]

Related Product Data


Application Tooling — pages 17-21

Wire Size Circular Mils [mm ²]	Tongue Material Thickness Max.	Stud Size	Dimensions				Terminal Insulation Color	Wire Insulation Diameter Max.	Part Numbers	
			W	C Min.	E Max.	L Max.			Loose Piece	
24 475 [0.24]	.020 0.51	10	.300 7.62	.281 7.14	.652 16.56	.807 20.50	Blue	.055 1.40	55114-1	
22 754 [0.38]	.025 0.64	4	.281 7.14	.250 6.35	.666 16.92	.809 20.55	Green	.110 2.79	53572-1	
12 6,654 [3.37]	.042 1.07	10	.375 9.53	.302 7.67	.933 23.70	1.123 28.52	Yellow	.200 5.08	53587-1	

Note: "C" dimension applies from edge of metal wire barrel to center of stud hole.

Insulated Terminals and Splices (Continued)

Pre-Insulated Butt Splices



Temperature Rating, Material and Finish

Insulation — TEFLON

Splice Body — Copper per
ASTM B152

Plating — Gold per MIL-G-45204
over Nickel per QQ-N-290, 500°F
[260°C]

Metallic Sleeve — Copper per
ASTM B152

Plating — Nickel per QQ-N-290,
550°F [288°C]

Related Product Data

Application Tooling — pages 17-21

Wire Size Circular Mils [mm ²]	Dimension L Max.	Metallic Sleeve Color	Wire Insulation Diameter Max.	Part Numbers Loose Piece
22-20 509-1,290 [0.26-0.65]	1.156 29.36	Natural	.100 2.54	330377
18-16 1,600-2,800 [0.81-1.42]	1.531 38.89	Red	.140 3.56	330378
14-12 3,831-6,654 [1.94-3.37]	1.781 45.24	Blue	.170 4.32	330379

Pre-Insulated Spare Wire Caps (For Unstripped Wire)



Temperature Rating, Material and Finish

Insulation — TEFLON

Ring — Copper per ASTM B152

Plating — Nickel per QQ-N-290,
550°F [288°C]

Related Product Data

Application Tooling — shown this
page




Tool Part No.
69272-1

Wire Insulation Diameter Range	Dimension L Max.	Ring Color	Part Numbers	Tool Color Guide
.036 - .043 0.91-1.09	.500 12.70	Red and Green	328854	Green
.044 - .051 1.12-1.30	.500 12.70	Blue and Green	328855	Green
.052 - .056 1.32-1.42	.500 12.70	Yellow and Green	328856	Green
.056 - .064 1.42-1.63	.500 12.70	Brown and Green	328857	Green
.065 - .074 1.65-1.88	.500 12.70	Violet and Green	328858	Green
.075 - .087 1.91-2.21	.500 12.70	Black and Orange	328859	Orange
.088 - .110 2.24-2.79	.500 12.70	Gray and Orange	328860	Orange
.125 - .138 3.18-3.51	.500 12.70	Nickel and Nickel	328861	White

Insulated Terminals and Splices (Continued)

Post-Insulated Ring Tongue Terminals



Temperature Rating, Material and Finish

Insulation — TEFLON

Terminal Body — Copper per
ASTM B152

Plating — Silver per QQ-S-365,
500°F [260°C], Gold per MIL-G-
45204 over Nickel per QQ-N-290,
500°F [260°C]

Ring — Copper per ASTM B152,
Aluminum per QQ-A-250/1

Plating — Nickel per QQ-N-290,
550°F [288°C]

Related Product Data

Application Tooling — pages 17-21

Wire Size Circular Mils [mm ²]	Tongue Material Thickness Max.	Stud Size	Dimensions		Body Plating	Ring Material	Ring Plating	Ring Color Code	Wire Insulation Diameter Range	Part No. Loose Piece
			W	L Dim. Approx. (After Crimping)						
22-20 509-1,290 [0.26-0.65]	.025 0.64	8 M4	.312 7.92	.906 23.01	Silver	Copper	Nickel	Natural	.046-.063 1.17-1.60	326760
8 13,100-20,800 [6.64-10.5]	.051 1.30	10	.469 11.91	1.560 39.62	Gold	Aluminum	—	Red	.215-.255 5.46-6.48	329580
6 20,800-33,100 [10.5-16.8]	.060 1.52	10	.468 11.89	1.870 47.50	Gold	Aluminum	—	Blue	.270-.310 6.86-7.87	329583

Post-Insulated Splices



Temperature Rating, Material and Finish

Insulation — TEFLON

Bushing — TEFLON

Splice Body — Copper per
ASTM B152

Plating — Gold per MIL-G-45204
over Nickel per QQ-N-290, 500°F
[260°C], Nickel per QQ-N-290,
550°F [288°C], Silver per QQ-S-
365, 500°F [260°C]

Ring — Aluminum per QQ-A-250/1,
Copper per ASTM B152

Plating — Nickel per QQ-N-290,
550°F [288°C]

Related Product Data


Application Tooling — pages 17-21

Wire Size Circular Mils [mm ²]	Dimension		Splice Plating	Ring Material	Ring Plating	Ring Color Code	Wire Insulation Diameter Range	Part No. Loose Piece
	L Dim. Approx. (After Crimping)							
26-24 238-475 [0.12-0.24]	.937 23.80		Gold	Aluminum	—	Yellow	.040-.050 1.02-1.27	324370
22-20 509-1,290 [0.26-0.65]	1.062 26.97		Silver	Copper	Nickel	Natural	.080-.100 2.03-2.54	326835 ¹
	1.650 41.91		Nickel	Aluminum	—	Red	.050-.068 1.27-1.73	55235-1
18-16 1,600-2,800 [0.81-1.42]	1.312 33.32		Gold	Aluminum	—	Red	.064-.088 1.63-2.24	329647
8 13,100-20,800 [6.64-10.5]	1.921 48.79		Gold	Aluminum	—	Red	.215-.255 5.46-6.48	329716

¹No bushing

Uninsulated Terminals and Splices

Solistrand Heat Resistant Ring Tongue Terminals



Non-Insulation Support

Non-Insulation Support
(Wire Range 2 & 1/0)

Temperature Rating, Material and Finish

Terminal Body — Copper per
ASTM B152

Plating — Nickel per QQ-N-290,
650°F [343°C]

Related Product Data


Application Tooling — pages 17-21

Wire Size Circular Mils [mm²]	Tongue Material Thickness Max.	Stud Size	Style	Dimensions				Part Numbers	
				W	C	E Max.	L Max.	Loose Piece	Tape Mounted
22-16 509-3,260 [0.26-1.65]	.033 0.84	6 M3.5	A	.218 5.54	.156 3.96	.337 8.56	.449 11.40	322797	—
			A	.281 7.14	.250 6.35	.436 11.07	.574 14.58	323219	—
		8 M4	A	.281 7.14	.250 6.35	.436 11.07	.574 14.58	322798	—
		10	A	.281 7.14	.250 6.35	.436 11.07	.574 14.58	322799	—
16-14 2,050-5,180 [1.04-2.62]	.033 0.84	6 M3.5	A	.343 8.71	.281 7.14	.462 11.73	.636 16.15	322693	—
			A	.250 6.35	.171 4.34	.352 8.94	.480 12.19	322805	—
		8 M4	A	.343 8.71	.281 7.14	.462 11.73	.636 16.15	322694	—
		10	A	.343 8.71	.281 7.14	.462 11.73	.636 16.15	322695*	2-322695-2
12-10 5,180-13,100 [2.62-6.64]	.042 1.07	1/4 M6	A	.469 11.91	.437 11.10	.618 15.70	.855 21.72	322733	—
		6 M3.5	A	.375 9.53	.302 7.67	.575 14.61	.765 19.43	323060	—
		8 M4	A	.375 9.53	.302 7.67	.575 14.61	.765 19.43	323061	—
		10	A	.375 9.53	.302 7.67	.575 14.61	.765 19.43	323062	2-323062-2
		1/4 M6	A	.531 13.49	.468 11.89	.736 18.69	1.004 25.50	323063	—
		5/16 M8	A	.531 13.49	.468 11.89	.736 18.69	1.004 25.50	323064	—
8 13,100-20,800 [6.64-10.5]	.051 1.30	3/8	A	.593 15.06	.531 13.49	.799 20.29	1.098 27.89	323065	—
		8 M4	A	.406 10.31	.359 9.12	.743 18.87	.949 24.10	2-324061-5	—
		10	A	.406 10.31	.359 9.12	.743 18.87	.949 24.10	323165	—
		1/4 M6	A	.469 11.91	.359 9.12	.696 17.68	.933 23.70	323166	—
		5/16 M8	A	.562 14.27	.406 10.31	.790 20.07	1.074 27.28	323167	—
		3/8	A	.594 15.09	.531 13.49	.868 22.05	1.168 29.67	323168	—
6 20,800-33,100 [10.5-16.8]	.060 1.52	10	A	.468 11.89	.531 13.49	.931 23.65	1.168 29.67	323169	—
		1/4 M6	A	.468 11.89	.531 13.49	.931 23.65	1.168 29.67	323170	—
		5/16 M8	A	.625 15.88	.531 13.49	.931 23.65	1.246 31.65	323171	—
		3/8	A	.625 15.88	.531 13.49	.931 23.65	1.246 31.65	323172	—

*Available in small packaging quantities.

Uninsulated Terminals and Splices (Continued)

Solistrand Heat Resistant Ring Tongue Terminals (Continued)



Non-Insulation Support

Non-Insulation Support
(Wire Range 2 & 1/0)

Temperature Rating, Material and Finish

Terminal Body — Copper per
ASTM B152


Plating — Nickel per QQ-N-290,
650°F [343°C]

Related Product Data

Application Tooling — pages 17-21

Wire Size Circular Mils [mm ²]	Tongue Material Thickness Max.	Stud Size	Style	Dimensions				Part Numbers	
				W	C	E Max.	L Max.	Loose Piece	Tape Mounted
4 33,100-52,600 [16.8-26.7]	.073 1.85	1/4 M6	A	.500 12.70	.437 11.10	.946 24.03	1.199 30.45	323173	—
		5/16 M8	A	.625 15.88	.500 12.70	1.009 25.63	1.324 33.63	323174	—
		3/8	A	.625 15.88	.500 12.70	1.009 25.63	1.324 33.63	323175	—
2 52,600-83,700 [26.7-42.4]	.073 1.85	3/8	B	.625 15.88	.540 13.72	1.212 30.78	1.527 38.79	323177	—
1/0 83,700-119,500 [42.4-60.6]	.073 1.85	3/8	B	.807 20.50	.625 15.88	1.519 38.58	1.925 48.90	323180	—


Solistrand Heat Resistant Splices



Style-A
Non-Insulation
Support
Butt Splice



Style-B
Non-Insulation
Support
Parallel Splice



Style-C
Non-Insulation
Support
Butt Splice

Temperature Rating, Material and Finish

Splice Body — Copper per
ASTM B152

Plating — Nickel per QQ-N-290,
650°F [343°C]


Related Product Data

Application Tooling — pages 17-21

Wire Size Circular Mils [mm ²]	Material Thickness Max.	Style	Dimensions			Part Numbers
			L Max.	ID Min.	OD Max.	
22-16 509-3,260 [0.26-1.65]	.033 0.84	A	.578 14.68	.061 1.55	.141 3.58	323796
		B	.301 7.65	.061 1.55	.141 3.58	323030
		C	.591 15.01	.061 1.55	.141 3.58	322822
16-14 2,050-5,180 [1.04-2.62]	.033 0.84	A	.567 14.40	.085 2.16	.165 4.19	323795
		B	.301 7.65	.085 2.16	.165 4.19	323794
		C	.529 13.44	.085 2.16	.165 4.19	322824
12-10 5,180-13,100 [2.62-6.64]	.042 1.07	A	.565 14.35	.129 3.28	.226 5.74	323755
		B	.333 8.46	.129 3.28	.226 5.74	323754
		C	.703 17.86	.129 3.28	.226 5.74	323756
8 13,100-20,800 [6.64-10.5]	.051 1.30	B	.375 9.53	.172 4.37	.296 7.52	2-34318-1

Uninsulated Terminals and Splices (Continued)

Solistrand High Temperature Ring Tongue Terminals



Non-Insulation Support

Temperature Rating and Material

Terminal Body — Nickel per
ASTM B162, 1200°F [649°C]

Related Product Data


Application Tooling — pages 17-21

Wire Size Circular Mils [mm²]	Tongue Material Thickness Max.	Color Code	Stud Size	Dimensions				Part Numbers	
				W	C Min.	E Max.	L Max.	Loose Piece	Tape Mounted
22-16 509-3,260 [0.26-1.65]	.033 0.84	Orange	4	.218 5.54	.156 3.96	.337 8.56	.449 11.40	321884	2-321884-2
			5	.218 5.54	.156 3.96	.337 8.56	.449 11.40	321885	—
			M3	.281 7.14	.250 6.35	.431 10.95	.574 14.58	321889*	2-321889-3
			6	.312 7.92	.281 7.14	.462 11.73	.621 15.77	322872	—
			M3.5	.281 7.14	.250 6.35	.431 10.95	.574 14.58	321890*	—
			8	.312 7.92	.281 7.14	.462 11.73	.621 15.77	321895	—
			M4	.281 7.14	.250 6.35	.431 10.95	.574 14.58	321891*	—
			10	.312 7.92	.281 7.14	.462 11.73	.621 15.77	321896	2-321896-4
			4	.250 6.35	.171 4.34	.352 8.94	.480 12.19	322328	—
			6	.250 6.35	.171 4.34	.352 8.94	.480 12.19	322329	2-322329-2
			M3.5	.343 8.71	.281 7.14	.462 11.73	.636 16.15	322333	2-322333-3
			8	.343 8.71	.281 7.14	.462 11.73	.636 16.15	322334*	—
16-14 2,050-5,180 [1.04-2.62]	.033 0.84	Orange	M4	.343 8.71	.281 7.14	.462 11.73	.636 16.15	322335*	2-322335-5
			10	.468 11.89	.437 11.10	.618 15.70	.855 21.72	322339	—
			1/4	.468 11.89	.437 11.10	.618 15.70	.855 21.72	322340	—
			M6	.531 13.49	.546 13.87	.727 18.47	.995 25.27	322343	—
			3/8	.375 9.53	.281 7.14	.549 13.94	.739 18.77	323059	—
			6	.375 9.53	.281 7.14	.549 13.94	.739 18.77	323745*	—
			8	.375 9.53	.281 7.14	.549 13.94	.739 18.77	323680*	2-323680-5
			10	.531 13.49	.468 11.89	.736 18.69	1.004 25.50	323683*	2-323683-2
12-10 5,180-13,100 [2.62-6.64]	.042 1.07	Orange	1/4	.531 13.49	.468 11.89	.736 18.69	1.004 25.50	323746	—
			M6	.593 15.06	.531 13.49	.799 20.29	1.098 27.89	323747	—
			3/8	.406 10.31	.359 9.12	.743 18.87	.949 24.10	328822	—
			8	.406 10.31	.359 9.12	.743 18.87	.949 24.10	328822	—
			10	.406 10.31	.359 9.12	.743 18.87	.949 24.10	328822	—

*Available in small packaging quantities.

Uninsulated Terminals and Splices (Continued)

Solistrand High Temperature Spade Tongue Terminals



Non-Insulation Support

Temperature Rating and Material


Terminal Body — Nickel per
ASTM B162, 1200°F [649°C]

Related Product Data

Application Tooling — pages 17-21

Wire Size Circular Mils [mm ²]	Tongue Material Thickness Max.	Color Code	Stud Size	Dimensions					Part Number Loose Piece
				W	C Min.	E Max.	L Max.	X	
16-14 2,050-5,180 [1.04-2.62]	.033 0.84	Orange	8 M4	.385 9.78	.312 7.92	.493 12.52	.685 17.40	.187 4.75	323905


Solistrand High Temperature Splices



Style-A
Non-Insulation
Support
Butt Splice



Style-B
Non-Insulation
Support
Parallel Splice



Style-C
Non-Insulation
Support
Butt Splice

Temperature Rating and Material

Splice Body — Nickel per
ASTM B162, 1200°F [649°C]

Related Product Data


Application Tooling — pages 17-21

Wire Size Circular Mils [mm ²]	Material Thickness Max.	Color Code	Style	Dimensions			Part Numbers Loose Piece
				L Max.	ID Min.	OD Max.	
22-16 509-3,260 [0.26-1.65]	.033 0.84	Orange	A	.578 14.68	.061 1.55	.141 3.58	322324*
			B	.301 7.65	.061 1.55	.141 3.58	322326
			C	.529 13.44	.061 1.55	.141 3.58	323876
16-14 2,050-5,180 [1.04-2.62]	.033 0.84	Orange	A	.567 14.40	.085 2.16	.165 4.19	322345
			B	.301 7.65	.085 2.16	.165 4.19	322347
			C	.529 13.44	.085 2.16	.165 4.19	323878
12-10 5,180-13,100 [2.62-6.64]	.042 1.07	Orange	A	.567 14.40	.129 3.28	.226 5.74	323696*
			B	.333 8.46	.129 3.28	.226 5.74	323672
			C	.703 17.86	.129 3.28	.226 5.74	323698

*Available in small packaging quantities.

Uninsulated Terminals and Splices (Continued)

Diamond Grip Heat Resistant Ring Tongue Terminals



Insulation Support

Temperature Rating, Material and Finish

Terminal Body — Copper per
ASTM B152

Plating — Nickel per QQ-N-290,
650°F [343°C]

Metallic Sleeve — Nickel Silver per
ASTM B122

Related Product Data


Application Tooling — pages 17-21

Wire Size Circular Mills [mm ²]	Tongue Material Thickness Max.	Stud Size	Dimensions				Wire Insulation Diameter Max.	Part Numbers	
			W	C Min.	E Max.	L Max.		Loose Piece	Tape Mounted
22-16 509-3,260 [0.26-1.65]	.033 0.84	4	.218	.156	.512	.624	.140	322363	—
			5.54	3.96	13.00	15.85	3.56	322364	—
		6 M3.5	.218	.156	.530	.645	.110	323151	—
			5.54	3.96	13.46	16.38	2.79	323199	—
		8 M4	.281	.250	.611	.749	.140	322365	—
			7.14	6.35	15.52	19.02	3.56	323152	323152-1
		10	.281	.250	.611	.749	.140	322366	—
			7.14	6.35	15.52	19.02	3.56	323153	—
		1/4 M6	.469	.437	.793	1.031	.140	322367	—
			11.91	11.10	20.14	26.19	3.56	323154	—
16-14 2,050-5,180 [1.04-2.62]	.033 0.84	4	.250	.171	.527	.655	.170	322371	—
			6.35	4.34	13.39	16.64	4.32	322373	—
		6 M3.5	.343	.281	.637	.811	.170	323158	—
			8.71	7.14	16.18	20.60	4.32	323160	—
		8 M4	.250	.171	.549	.680	.130	322374	—
			6.35	4.34	13.94	17.27	3.30	323161	—
		10	.343	.281	.637	.811	.170	322375	—
			8.71	7.14	16.18	20.60	4.32	323162	—
		1/4 M6	.343	.281	.659	.836	.130	323066	—
			8.71	7.14	16.74	21.23	3.30	323067	—
12-10 5,180-13,100 [2.62-6.64]	.042 1.07	6 M3.5	.375	.302	.841	1.034	.230	323068	323068-1
			9.53	7.67	21.36	26.26	5.84	325154	—
		8 M4	.375	.302	.841	1.034	.230	323069	—
			9.53	7.67	21.36	26.26	5.84	—	—
		10	.375	.302	.841	1.034	.230	—	—
			9.53	7.67	21.36	26.26	5.84	—	—

Note: "C" dimension applies from edge of metal wire barrel to center of stud hole.

Uninsulated Terminals and Splices (Continued)

Diamond Grip Heat Resistant Splices



Insulation
Support
Butt Splice

Temperature Rating, Material and Finish

Splice Body — Copper per
ASTM B152

Plating — Nickel per QQ-N-290,
650°F [343°C]


Metallic Sleeve — Nickel Silver per
ASTM B122

Related Product Data

Application Tooling — pages 17-21

Wire Size Circular Mils [mm ²]	Material Thickness Max.	Dimension L Max.	Wire Insulation Diameter Max.	Part Numbers Loose Piece
22-16 509-3,260 [0.26-1.65]	.033 0.84	.889 22.58	.140 3.56	322823
16-14 2,050-5,180 [1.04-2.62]	.033 0.84	.889 22.58	.170 4.32	322825
12-10 5,180-13,100 [2.62-6.64]	.042 1.07	1.261 32.03	.230 5.84	323757

Diamond Grip High Temperature Ring Tongue Terminals



Insulation Support

Temperature Rating and Material

Terminal Body — See table, 1200°F
[649°C], Nickel per ASTM B162,
Alumel —, Chromel —

Metallic Sleeve — Nickel Silver per
ASTM B122

Related Product Data

Application Tooling — pages 17-21

Wire Size Circular Mils [mm ²]	Tongue Material Thickness Max.	Stud Size	Dimensions				Body Material	Sleeve Color Code	Wire Insulation Diameter Max.	Part Numbers	
			W	C Min.	E Max.	L Max.				Loose Piece	Tape Mounted
22-16 509-3,260 [0.26-1.65]	.033 0.84	4	.218 5.54	.156 3.96	.512 13.00	.624 15.85	Nickel	Orange	.140 3.56	321887	—
			.281 7.14	.250 6.35	.611 15.52	.749 19.02	Nickel	Orange	.140 3.56	321892	—
		6 M3.5	.312 7.92	.281 7.14	.637 16.18	.796 20.22	Nickel	Orange	.140 3.56	322873	—
			.312 7.92	.281 7.14	.637 16.18	.796 20.22	Chromel	Gray	.140 3.56	2-322873-1	—
		8 M4	.281 7.14	.250 6.35	.611 15.52	.749 19.02	Nickel	Orange	.140 3.56	321893	—
			.312 7.92	.281 7.14	.637 16.18	.796 20.22	Nickel	Orange	.140 3.56	321897	—
			.312 7.92	.281 7.14	.637 16.18	.796 20.22	Chromel	Gray	.140 3.56	1-321897-0	—
			.312 7.92	.281 7.14	.637 16.18	.796 20.22	Alumel	Green	.140 3.56	1-321897-3	—
		10	.468 11.89	.437 11.10	.793 20.14	1.031 26.19	Nickel	Orange	.140 3.56	184204-1	—
			.281 7.14	.250 6.35	.611 15.52	.749 19.02	Nickel	Orange	.140 3.56	321894	—
			.312 7.92	.281 7.14	.637 16.18	.796 20.22	Nickel	Orange	.140 3.56	321898	—
			.312 7.92	.281 7.14	.637 16.18	.796 20.22	Chromel	Gray	.140 3.56	1-321897-4	—
			.312 7.92	.281 7.14	.637 16.18	.796 20.22	Alumel	Green	.140 3.56	1-321898-0	—
			.468 11.89	.437 11.10	.793 20.14	1.031 26.19	Nickel	Orange	.140 3.56	322320	—
		1/4 M6	.468 11.89	.437 11.10	.793 20.14	1.031 26.19	Nickel	Orange	.140 3.56	322320	—

Note: "C" dimension applies from edge of metal wire barrel to center of stud hole.

Uninsulated Terminals and Splices (Continued)


Diamond Grip High Temperature Ring Tongue Terminals (Continued)

Wire Size Circular Mils [mm ²]	Tongue Material Thickness Max.	Stud Size	Dimensions				Body Material	Sleeve Color Code	Wire Insulation Diameter Max	Part Numbers	
			W	C Min.	E Max.	L Max.				Loose Piece	Tape Mounted
16-14 2,050-5,180 [1.04-2.62]	.033 0.84	6 M3.5	.250 6.35	.171 4.34	.527 13.39	.655 16.64	Nickel	Orange	.170 4.32	322332	—
			.343 8.71	.281 7.14	.637 16.18	.811 20.60	Nickel	Orange	.170 4.32	322336	2-322336-2
		8 M4	.343 8.71	.281 7.14	.637 16.18	.811 20.60	Nickel	Orange	.170 4.32	322337	1-322337-2
			.343 8.71	.281 7.14	.637 16.18	.811 20.60	Chromel	Gray	.170 4.32	1-322337-0	—
		10	.343 8.71	.281 7.14	.637 16.18	.811 20.60	Alumel	Green	.170 4.32	1-322338-1	—
			.343 8.71	.281 7.14	.637 16.18	.811 20.60	Nickel	Orange	.170 4.32	322338	1-322338-2
		10	.343 8.71	.281 7.14	.637 16.18	.811 20.60	Chromel	Gray	.170 4.32	1-322337-1	—
			.343 8.71	.281 7.14	.637 16.18	.811 20.60	Alumel	Green	.170 4.32	1-322338-0	—
		1/4 M6	.468 11.89	.437 11.10	.793 20.14	1.030 26.16	Nickel	Orange	.170 4.32	322341	—
		3/8	.531 13.49	.546 13.87	.902 22.91	1.170 29.72	Nickel	Orange	.170 4.32	322344	—
12-10 5,180-13,100 [2.62-6.64]	.042 1.07	6 M3.5	.375 9.53	.281 7.14	.815 20.70	1.008 25.60	Nickel	Orange	.230 5.84	323748	—
			.375 9.53	.281 7.14	.815 20.70	1.008 25.60	Nickel	Orange	.230 5.84	323749	—
		8 M4	.375 9.53	.281 7.14	.815 20.70	1.008 25.60	Chromel	Gray	.230 5.84	2-323749-1	—
			.375 9.53	.281 7.14	.815 20.70	1.008 25.60	Nickel	Orange	.230 5.84	323750	2-323750-5
		10	.375 9.53	.281 7.14	.815 20.70	1.008 25.60	Alumel	Green	.230 5.84	2-323750-1	—
			.531 13.49	.468 11.89	1.002 25.45	1.273 32.33	Nickel	Orange	.230 5.84	323751	—
		5/16 M8	.531 13.49	.468 11.89	1.002 25.45	1.273 32.33	Nickel	Orange	.230 5.84	323752	—

Note: "C" dimension applies from edge of metal wire barrel to center of stud hole.

Uninsulated Terminals and Splices (Continued)

Diamond Grip High Temperature Splices



Insulation
Support
Butt Splice

Temperature Rating and Material

Splice Body — See table, 1200°F
[649°C], Nickel per ASTM B162,
Alumel —, Chromel —

Metallic Sleeve — Nickel Silver per
ASTM B122

Related Product Data

Application Tooling — pages 17-21

Wire Size Circular Mils [mm ²]	Material Thickness Max.	Dimension	Splice Body Material	Sleeve Color Code	Wire Insulation Diameter Max.	Part Numbers
		L Max.				Loose Piece
22-16 509-3,260 [0.26-1.65]	.033 0.84	.889 22.58	Nickel	Orange	.140 3.56	322325
		.889 22.58	Alumel	Green	.140 3.56	1-322325-0
		.889 22.58	Chromel	Gray	.140 3.56	1-322325-1
16-14 2,050-5,180 [1.04-2.62]	.033 0.84	.889 22.58	Nickel	Orange	.170 4.32	322346
		.889 22.58	Alumel	Green	.170 4.32	1-322346-0
		.889 22.58	Chromel	Gray	.170 4.32	1-322346-1
12-10 5,180-13,100 [2.62-6.64]	.042 1.07	1.261 32.03	Nickel	Orange	.230 5.84	323699

Application Tooling Information for STRATO-THERM Insulated Heat Resistant and High Temperature Terminals and Splices

Wire Size Range AWG 26-10

Product Type	AMP Wire Size	Hand Tools	Pneumatic Tooling	Tooling For Tape Mounted Products
			Dies for 626 Pneumatic Tools 189721-[] and 189722-[] require Straight Action Adapter ¹ 217200-1 or "C" Head Adapter 318161-1 Dies also fit 69710-1 Hand Tool	Dies for 69875 AMP-TAPETRONIC AMP-O-LECTRIC ² Requires Applicator AMPOMATOR CLS IV ² Requires Applicators
Pre-Insulated Terminals	26-24	69692-1	69731	—
	22-20		69732	69936
	18-16	69693-1	69733	69937
	14		69734	—
	12-10	—	69735	—
Pre-Insulated Splices	22-20	—	69327	—
	18-16	—	69328	—
	14-12	—	69329	—

¹Straight Action Adapter 217200-1 is used with Tools 189721-1 or 189722-1. "C"Head Adapter 318161-1 is used with Tools 189721-2 or 189722-2. Both adapters require the use of non-ratchet tool holder 189928-1 or ratchet tool holder 356304-1.

²Call Tooling Assistance Center for Machine and Applicator part numbers.

Wire Size Range AWG 26-6

Product Type	AMP Wire Size	Hand Tools	Hydraulic and Battery Powered Tools With Interchangeable Dies		
			69097 ² "C" Head		69099 ² "C" Head
			Nest	Indent	Head
Post Insulated Terminals and Splices	26-24	45730	—	—	—
	22-20	46467, 46468 ¹	—	—	—
	18-16	46468	—	—	—
	8	—	46146	46145	69216
	6	—	46134	46133	69217

¹Part Number 55235-1 only

²These crimping heads are recommended for use only with AMP Hydraulic Hand Pump 314979-1, DYNA-CRIMP Hydraulic Power Units 69120-1 (115 VAC) and 69120-2 (230 VAC), and with DYNA-CRIMP II Battery Operated Hydraulic Power Unit 122271-1. See pages 20 & 21.

Application Tooling Information for STRATO-THERM Uninsulated Heat Resistant and High Temperature Terminals and Splices

Wire Size Range AWG 22-10

Product Type	AMP Wire Size	Hand Tools	Pneumatic Tooling	Tooling For Tape Mounted Products
			Crimping Heads for 626 Pneumatic Tool 189721-1 and 189722-1 ¹	Dies for 69875 AMP-TAPETRONIC AMP-O-LECTRIC ² Requires Applicator AMPOMATOR CLS IV ² Requires Applicators
Uninsulated Terminals and Splices with Insulation Support	22-16	46673 46673-1	356744-1	69930
	16-14	46988 59294	356744-2	69931
	12-10	59461	904870-1	69932
Uninsulated Terminals and Splices with Non-Insulation Support	22-16			69954
	16-14	46447	217206-1	69955
	12-10			69956

¹Crimping Heads require the use of non-ratchet tool holder 189767-1 or ratchet tool holder 356302-1.

²Call Tooling Assistance Center for Machine and Applicator part numbers.

Wire Size Range AWG 8-1/0


Product Type	AMP Wire Size	Hand Tools	Pneumatic Tooling	Hydraulic Tools With Self Contained Dies		Hydraulic and Battery Powered Tools with Interchangeable Dies				
			69015 Head	Hand Tool	Latch Head	59973-1 Hand Tool, 69065 ² & 69067 ² Latch Heads		69097 ² “C” Head		69099 ² “C” Head
						Nest	Indent	Nest	Indent	
Uninsulated Terminals and Splices with Non-Insulation Support	8	69355 ¹	49956	59975-1	69069 ²	48126	48355	—	—	69216
	6	59083 No CERTI-CRIMP	48172			48128	—	—	69217	
	4	—	48173			48129	48127	46135	46133	69218
	2	—	48174			48130	46136	45433		
	1/0	—	48183			—	—	48132	48131	46138

¹CERTI-CRIMPHand Tool.

²These crimping heads are recommended for use only with AMP Hydraulic Hand Pump 314979-1, DYNA-CRIMP Hydraulic Power Units 69120-1 (115 VAC) and 69120-2 (230 VAC), and with DYNA-CRIMP II Battery Operated Hydraulic Power Unit 122271-1. See Pages 20 & 21.

For additional tooling information, call 1-800-722-1111.

Application Tooling Information for STRATO-THERM Heat Resistant and High Temperature Terminals and Splices

Loose Form Terminal and Splice Tooling**CERTI-CRIMP Hand Tools**

**Straight Action Double
Action Hand Tool**



**Double Action
Hand Tool**



**Heavy Head Hand Tool
Part No. 69355**



**"C" Head Straight
Action Hand Tool
Part No. 69710-1**



T-Head Tool

Pneumatic Tools

**6-26 Pneumatic Tool
Part No. 189721-1**



Part No. 69015

Hydraulic Hand Tools

**Part No. 59975-1
(Self Contained Dies)**



**Part No. 59973-1
(Dies Required)**

For additional tooling information, call 1-800-722-1111.

Application Tooling Information for STRATO-THERM Heat Resistant and High Temperature Terminals and Splices (Continued)


Tape Mounted



AMP-TAPETRONIC Machine
69875, 68250-1
(Requires Dies)



AMP-O-ELECTRIC, Model "G" Machine
(Requires Applicator and Dies)



AMPOMATOR CLS IV Machine 217500-1
(Requires Applicators and Dies)

Latch Heads and Dies



Part No.
69065



Part No.
69067



Part No.
69099



Part No. 69069
(Self Contained Dies)



Part No.
69097

For additional tooling information, call 1-800-722-1111.

Application Tooling Information for STRATO-THERM Heat Resistant and High Temperature Terminals and Splices

DYNA-CRIMP II Battery Operated Hydraulic Power Unit



Part No. 122271-1⁴

Hand Operated Power Unit



Typical interchangeable hose, head and dies not included

314979-1² (Hose, head and dies not included)

Refer to the table below for accessories.


DYNA-CRIMP Electric Hydraulic Power Unit



Power Unit Only
(Includes Pressure Release)

115 Volts (60 Hz) — 69120-1³
230 Volts (60 Hz) — 69120-2³


AMP application tools are designed to produce a carefully controlled uniform pressure crimp, regardless of how they are powered. All tools shown are specially designed for AMP products and are precision machined from hard tool steel.




Handle
Control



Hose
Assembly



Foot
Control



Multidirectional
Valve

Power Units Accessories

For Use With Power Unit No.	Accessory Description	Accessory Part No.	Remarks
69120-1 ³ 69120-2 ³ 314979-1 ² 122271-1 ⁴	7' Handle Control Assembly—Hose & Cord	59907-7	
	15' Handle Control Assembly—Hose & Cord	1-59907-5	
	21' Handle Control Assembly—Hose & Cord	2-59907-1	
	28' Handle Control Assembly—Hose & Cord	2-59907-8	
	15' Foot Switch Assembly	68284-1	Need Hose Assembly
	3' Hose Assembly	59909-3	
	7' Hose Assembly	59909-7	
	15' Hose Assembly	1-59909-5	
	21' Hose Assembly	2-59909-1	
	2' Hose Assembly (1/4" I.D.)	314990-1	More Flexible, Lighter Weight.
69120-1 ³ 69120-2 ³	3' Hose Assembly (1/4" I.D.)	314990-2	Recommended for use with
	7' Hose Assembly (1/4" I.D.)	314990-3	DYNA-CRIMP II Battery
	15' Hose Assembly (1/4" I.D.)	314990-4	Operated Hydraulic Power Unit
	3-Way Multi-Directional Valve	59220 ¹	For use with
	3-Way Multi-Directional Valve (Elec.Ctl.)	59220-2 ¹	Foot Switch only

¹ Contact AMP Incorporated for usage recommendations.

² Also see AMP Customer Manual 409-5860.

³ Also see AMP Customer Manual 409-1950.

⁴ Also see AMP Customer Manual 409-5869.

Note: All Hoses and Handle Control Assemblies have a 3/8" high flow male coupler (311470-1) on each end.
All Power Units and Heads have a 3/8" high flow female coupler (311471-1).

For additional tooling information, call 1-800-722-1111.

Part Number Index

Note: This index lists all cataloged parts by base no. only. Complete part nos. (with prefixes and/or suffixes) are shown on the page(s) indicated.

Part No.	Page
34318	10
50829	5
50830	5
50831	5
50832	5
50834	5
50835	5
50836	5
50837	5
50838	5
50839	5
50840	5
50841	5
50844	6
50845	6
50846	6
50847	6
50848	6
53572	6
53587	6
55114	6
55235	8
184204	14
321884	11
321885	11
321887	14
321889	11
321890	11
321891	11
321892	14
321893	14
321894	14
321895	11
321896	11
321897	14
321898	14
322320	14
322324	12
322325	16
322326	12
322328	11
322329	11
322332	15
322333	11
322334	11
322335	11
322336	15
322337	15
322338	15
322339	11
322340	11
322341	15
322343	11
322344	15
322345	12
322346	16
322347	12
322363	13
322364	13
322365	13
322366	13

Part No.	Page
322367	13
322371	13
322373	13
322374	13
322375	13
322376	13
322693	9
322694	9
322695	9
322733	9
322797	9
322798	9
322799	9
322805	9
322822	10
322823	14
322824	10
322825	14
322872	11
322873	14
323030	10
323059	11
323060	9
323061	9
323062	9
323063	9
323064	9
323065	9
323066	13
323067	13
323068	13
323069	13
323151	13
323152	13
323153	13
323154	13
323158	13
323160	13
323161	13
323162	13
323165	9
323166	9
323167	9
323168	9
323169	9
323170	9
323171	9
323172	9
323173	10
323174	10
323175	10
323177	10
323180	10
323199	13
323219	9
323672	12
323680	11
323683	11
323696	12
323698	12
323699	16

Part No.	Page
323745	11
323746	11
323747	11
323748	15
323749	15
323750	15
323751	15
323752	15
323754	10
323755	10
323756	10
323757	14
323794	10
323795	10
323796	10
323876	12
323878	12
323905	12
324061	9
324370	8
325154	13
326760	8
326835	8
328822	11
328854	7
328855	7
328856	7
328857	7
328858	7
328859	7
328860	7
328861	7
329580	8
329583	8
329647	8
329716	8
330377	7
330378	7
330379	7
332433	5
332434	5
332438	5
332439	5
332446	6
332453	5
332454	5



Engineering Notes

Americas

Argentina – Buenos Aires
Phone: + 54-1-733-2000
Fax: + 54-1-717-0988

Brazil – Sao Paulo
Phone: + 55-11-861-1311
Fax: + 55-11-861-0397

Canada – Toronto
Phone: + 1-905-475-6222
Fax: + 1-905-474-5520

Chile – Santiago
Phone: + 56-2-236-4267
Fax: + 56-2-235-0061

Columbia – Bogota
Phone: + 57-1-369-0045
Fax: + 57-1-269-7525

Mexico – Mexico City
Phone: + 52-5-398-76-11
Fax: + 52-5-398-79-64

United States – Harrisburg, PA
Phone: + 1-717-564-0100
Fax: + 1-717-986-7575

For Latin/South American Countries not shown
Phone: +54-1-733-2015
Fax: +54-1-733-2083

Asia/Pacific

Australia – Sydney
Phone: + 61-2-9840-8200
Fax: + 61-2-9899-5649

India – Bangalore
Phone: + 91-80-845-3014
Fax: + 91-80-845-3038

Indonesia – Jakarta
Phone: + 6221-526-7852
Fax: + 6221-526-7856

Japan – Tokyo
Phone: + 81-44-844-8111
Fax: + 81-44-812-3207

Korea – Seoul
Phone: + 82-3274-0535
Fax: + 82-3274-0524

Malaysia – Kuala Lumpur
Phone: + 603-705-3055
Fax: + 603-705-3066

New Zealand – Auckland
Phone: + 64-9-634-4580
Fax: 64-9-634-4586

Peoples Republic of China
Hong Kong
Phone: + 852-2-35-1628
Fax: + 852-2-35-0243
Shanghai
Phone: + 86-21-6485-0602
Fax: + 86-21-6485-0728
Shunde
Phone: + 86-765-7751368
Fax: + 86-765-7752823

Philippines – Manila
Phone: + 632-811-0437
Fax: + 632-811-0441

Singapore – Singapore
Phone: + 65-482-0311
Fax: + 65-482-1012

Taiwan – Taipei
Phone: + 886-2-704-4815
Fax: + 886-2-704-4940

Thailand – Bangkok
Phone: + 91-662-513-9888
Fax: + 91-662-513-9889

Vietnam – Ho Chi Minh City
Phone: + 84-8823-2546
Fax: + 84-8823-1443

Europe/Middle East/Africa

Austria – Vienna
Inside: Phone: + 0222-277-97-0
Fax: + 0222-270-26-61
Outside: Phone: + 43-1-277-97-0
Fax: + 43-1-270-26-61

Belgium – Brussels
Phone: + 32-2-719-2511
Fax: + 32-2-725-4928

Bulgaria – Sofia
Phone: + 359-2-971-2152
Fax: + 359-2-971-2153

Croatia – Zagreb
Phone: + 385-1-67-04-46
Fax: + 385-1-69-16-04

Czech Republic – Kurim
Phone: + 420-5-41-162-111
Fax: + 420-5-41-162-223

Denmark – Viby
Phone: + 45-86-295-055
Fax: + 45-86-295-133

Egypt – Cairo
Phone: + 202-417-76-47
Fax: + 202-419-23-34

Estonia – Tallinn
Phone: + 372-6205-800
Fax: + 372-6205-804

Finland – Helsinki
Phone: + 358-9-512-3420
Fax: + 358-9-512-34250

France – Pontoise
Phone: + 33-1-34-20-88-88
Fax: + 33-1-34-20-86-00

Germany – Langen
Phone: + 49-6103-709-0
Fax: + 49-6103-709-223

Great Britain – London
Phone: + 44-181-954-2356
Fax: + 44-181-954-6234

Greece – Athens
Phone: + 30-1-902-5515
Fax: + 30-1-902-4237

Holland – 's-Hertogenbosch
Phone: + 31-73-624-6246
Fax: + 31-73-621-2365

Hungary – Budapest
Phone: + 36-1-344-2633
Fax: + 36-1-344-2634

Ireland – Dublin
Phone: + 353-1-820-3000
Fax: + 353-1-820-9790

Israel – Tel Aviv
Phone: + 972-3-645-07-07
Fax: + 972-3-649-24-13

Italy – Torino
Phone: + 39-11-4012-111
Fax: + 39-11-4031-116

Lithuania – Vilnius
Phone: + 370-2-231402
Fax: + 370-2-231403

Norway – Oslo
Phone: + 47-66-77-88-50
Fax: + 47-66-77-88-55

Poland – Warsaw
Phone: + 48-22-672-47-90/91/92
Fax: + 48-22-672-47-88

Portugal – Lisbon
Phone: + 351-1-387-70-16
Fax: + 351-1-387-71-72

Romania – Bucharest
Phone: + 40-1-311-3479/3596
Fax: + 40-1-312-0574

Russia
Moscow
Phone: + 7-095-926-5506/07/08/09
Fax: + 7-095-926-5505

St. Petersburg
Phone: + 7-812-325-3083
Fax: + 7-812-326-3288

Slovakia – Bystrica
Phone: + 421-88-761-120/121
Fax: + 421-88-761-122

Slovenia – Ljubljana
Phone: + 386-61-161-3270
Fax: + 386-61-161-3240

South Africa – Johannesburg
Phone: + 27-11-805-65-35
Fax: + 27-11-805-65-40

Spain – Barcelona
Phone: + 34-3-291-0330
Fax: + 34-3-201-7879

Sweden – Stockholm
Phone: + 46-8-580-833-00
Fax: + 46-8-580-194-70

Switzerland – Steinach
Phone: + 41-71-447-0447
Fax: + 41-71-447-0444

Turkey – Istanbul
Phone: + 90-212-281-8181
Fax: + 90-212-281-8184

For Middle East/African Countries not shown
Phone: +33-1-34-20-83-83
Fax: +33-1-34-20-86-09

Related Businesses

AMP Circuits Division
Greenville, SC, USA
Phone: + 1-864-297-4100
Fax: + 1-864-675-7099

AMP Circuits and Packaging, EMEA

Dublin, Ireland
Phone: + 353-1-820-6500
Fax: + 353-1-820-6501

AMP Packaging and Carroll Touch Systems Division
Round Rock TX, USA
Phone: + 1-512-244-5100
Fax: + 1-512-244-7040

AMP-Simel S.A.
Gevrey-Chambertin, France
Phone: + 33-3-8058-3200
Fax: + 33-3-8034-1015

ARA-Applied Robotics Division
Rousset, France
Phone: + 33-4-42-29-1200
Fax: + 33-4-42-29-1212

Carroll Touch International, Ltd.
Tokyo, Japan
Phone: + 81-03-5306-2100
Fax: + 81-03-5306-2105

DSM Decolletage S.A. Saint-Maurice
Phone: + 41-24-486-2486
Fax: + 41-24-486-2400

Fibernet Division
Rowville, Australia
Phone: + 61-3-9764-2111
Fax: + 61-3-9764-2120

Wellington, New Zealand
Phone: + 64-4-237-9195
Fax: + 64-4-237-9195

HTS Elektrotechnik GmbH
Neunkirchen, Germany
Phone: + 49-2247-305-0
Fax: + 49-2247-305-22


M/A-COM Division
Americas
Lowell, MA, USA
Phone: + 1-978-442-5000
Fax: + 1-978-442-5354
Europe/Middle East/Africa
Bracknell, England
Phone: + 44-1344-869-595
Fax: + 44-1344-300-020

Asia/Pacific
Hong Kong
Phone: + 85-2-2111-8088
Fax: + 85-2-2111-8087

Madison Cable Corporation
Worcester, MA, USA
Phone: + 1-508-752-7320
Fax: + 1-508-752-4230

Madison Cable Ltd.
Dundee, Scotland
Phone: + 44-1382-508080
Fax: + 44-1382-505060

Precision Interconnect Division
Portland, OR, USA
Phone: + 1-503-620-9400
Fax: + 1-503-620-7131



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[50830](#)