

4805 (1/15)

	6	101.19 [3.984][99.06 3.900]	39	80	-9-146491-0-
	6	98.65 [3.884][96.52 3.800]	38	78	-8-146491-9-
	6	96.11 [3.784][93.98 3.700]	37	76	-8-146491-8-
	6	93.57 [3.684][91.44 3.600]	36	74	-8-146491-7-
	6	91.03 [3.584][88.90 3.500]	35	72	-8-146491-6-
	6	88.49	86.36	34	70	-8-146491-5-
	6	85.95	83.82 3.300]	33	68	-8-146491-4-
	6	83.41	81.28 3.200]	32	66	-8-146491-3-
	6		78.74	31	64	-8-146491-2-
-	6		76.20	30	62	-8-146491-1-
	6	 75.79 [2.984][73.66	29	60	-8-146491-0-
	6	73.25 [2.884][71.12	28	58	-7-146491-9-
		70.71 [2.784][68.58 2.700]	27	56	-7-146491-8
OBSOLETE	6	68.17 [2.684][66.04 2.600]	26	54	-7-146491-7
	6	65.63 [2.584][63.50 2.500]	25	52	-7-146491-6
	6	63.09 [2.484][60.96 2.400]	24	50	-7-146491-5-
	6	60.55 [2.384][58.42 [2.300]	23	48	-7-146491-4
	6	58.01 [2.284][55.88 [2.200]	22	46	-7-146491-3-
	6	55.47 [2.184][53.34 2.100]	21	44	-7 146491 2
	6	52.93 [2.084][50.80 [2.000]	20	42	-7-146491-1
-	6	50.39 [1.984][48.26 1.900]	19	40	-7-146491-0-
	6	47.85 [1.884][45.72 1.800]	18	38	-6-146491-9-
	$\sqrt{6}$	45.31 [1.784][43.18 1.700]	17	36	-6-146491-8-
	$\sqrt{6}$	42.77 [1.684][40.64 1.600]	16	34	-6-146491-7-
	$\sqrt{6}$	40.23 [1.584][38.10 1.500]	15	32	-6-146491-6-
	$\sqrt{6}$	37.69 [1.484][35.56 1.400]	14	30	6-146491-5
	$\sqrt{6}$	35.15 [1.384][33.02 [1.300]	13	28	-6 146491 4
		32.61 [1.284][30.48 1.200]	12	26	-6-146491-3-
	6	30.07 [1.184][27.94 1.100]	11	24	-6-146491-2-
	6	27.53 [1.084][25.40 1.000]	10	22	-6-146491-1
	6	24.99 [.984]	22.86 [.900]	9	20	-6-146491-0-
	6	22.45 [.884]	 20.32 [.800]	8	18	-5-146491-9-
OBSOLETE	6	19.91 [.784]	 17.78 [.700]	7	16	-5-146491-8-
	6	 17.37 [.684]	 15.24 [.600]	6	14	-5-146491-7-
-	6	14.83 [.584]	12.70 [.500]	5	12	-5-146491-6-
		12.29 [.484]	10.16 [.400]	4	10	-5-146491-5-
	6	9.75 [.384]	7.62 [.300]	3	8	-5-146491-4-
	6	7.21 [.284]	5.08 [.200]	2	6	-5-146491-3-
	6	4.67 [.184]	 2.54 [.100]	1	4	-5-146491-2-
	6	2.13 [.084]		_	2	-5-146491-1-
	PLATING	G	F	E	NO. OF Positions	PART NUMBER

2.54 [.100]

THIS DRAWING IS A CO DIMENSIONS: mm [INCHES]

MATERIAL

OBSOLETE

		2				1	
			P LTR		REVISIONS	DATE DWN APVE	
			С	REVISED PER	ECO-16-006303	08AUG2016 NK MM	
				1			
	5		99.06 [3.900]	39	80	-4-146491-0-	
	5	98.65 [3.884]	96.52 [3.800]	38	78	-3-146491-9	
	5	96.11 [3.784]	93.98 [3.700]	37	76	-3-146491-8	
		93.57 [3.684]	91.44	36	74		
_	<u></u>	91.03	88.90	35	72	6491_6	
_	\wedge	[3.584]	86.36	34	70		
_	<u></u>	[3.484] 85.95	83.82	33	68		
-	<u></u> 	[3.384] 83.41	<u>[3.300]</u> 81.28				
-	<u> </u>	[3.284] 80.87	[3.200] 78.74	32	66	-3-146491-3-	
-	<u></u>	[3.184] 78.33		31	64		
-	<u></u>	[3.084]	[3.000]	30	62	-3-146491-1-	
-	5	75.79 [2.984]	<u> </u>	29	60	-3-146491-0	
	5	73.25 [2.884]	<u> </u>	28	58		
	5	70.71 [2.784]	68.58 [2.700]	27	56	-2-146491-8-	
	5	68.17 [2.684]	66.04 [2.600]	26	54	-2-146491-7-	
	5	65.63 [2.584]	 63.50 [2.500]	25	52	-2-146491-6-	
	5	63.09 [2.484]	60.96	24	50	_2_146491_5_	
-		60.55	58.42	23	48	_2_146491_4	
olete	\wedge	58.01	[2.300] 55.88	22	46		
	<u></u>	[2.284] 55.47	<u>[2.200]</u> 53.34	21	44	-2-146491-2	
	<u>_5</u> 	[2.184] 52.93	<u>[2.100]</u> 50.80			-2-146491-1	
-	<u></u>	[2.084] 50.39	[2.000] 48.26	20	42		
-	<u></u>	[1.984] 47.85		19	40		
-	<u></u>	[1.884]	[1.800]	18	38	-1-146491-9-	
-	5	45.31 [1.784]		17	36	-1-146491-8-	
	5		40.64 [1.600]	16	34	-1-146491-7	
	5	40.23 [1.584]	38.10 [1.500]	15	32	-1-146491-6-	
	5	37.69 [1.484]		14	30	-1-146491-5-	
	5	35.15 [1.384]	 	13	28	-1-146491-4	
	5	32.61		12	26		
_			27.94	11	24	_1_146491_2	
		[1.184]	_25.40	10	22		
	\wedge	[1.084] _24.99	22.86	9	20	_1_146491_0	
	<u>_5</u> 	[.984] 22.45	[.900] 20.32				
	<u></u>	[.884]	[.800]	8	18	-146491-9	
	<u></u>	[.784]		7	16	-146491-8-	
-	<u></u>	[.684]	[.600]	6	14	-146491-7-	
-	5	[.584]	[.500]	5	12	-146491-6-	
	5	12.29 [.484]		4	10	-146491-5-	
	5	9.75 [.384]		3	8	-146491-4-	
	5	7.21	5.08 [.200]	2	6	-146491-3-	
-		4.67	2.54	1	4	-146491-2-	
		2.13			2	-146491-1-	
	PLATING	[.084] G			NO. OF	PART NUMBER	
RAWING IS ,	A CONTROLLED I		HOFFMAN	11/8/95			
		ES UNLESS G. SPECIFIED: APVD	DUBNICZKI	11/22/95 11/22/95 NAME	-ETE	TE Connectivity	
IMENSIONS:	nm [INCHES] 0 PLC ± - 1 PLC ± -		G. DUBNICZKI		HEADER ASSEMBLY, MOD II, Stacking, double row,		
	1 PLC ±	_				-	
	1 PLC ± 2 PLC ± 3 PLC ±			SIZE		ST, UNSHROUDED	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: <u>4-146491-0</u>