






SIZE	A DIM	B DIM	C DIM $\pm .0050$	(L DIM)
09	.050	.229	.3085	(.100)
15	.0875	.304	.3835	(.175)
25	.150	.429	.5085	(.300)
37	.225	.579	.6585	(.450)
51	.3125	.754	.8335	(.625)
65	.400	.929	1.0085	(.800)



1. SHELL OPTIONS (TO BE SPECIFIED IN NANONICS PART NUMBER):
 METAL: 6061-T6 ALUMINUM, ELECTROLESS NICKEL PLATED PER MIL-C-26074 (STANDARD) OR GOLD PLATED PER MIL-G-45204
 303 STAINLESS STEEL, PASSIVATED PER SAE-AMS-QQ-P-35
 INSULATOR MATERIAL FOR ALL METAL SHELLS IS LIQUID CRYSTAL POLYMER (LCP) PER MIL-M-24519 OR PER ASTM D5138
 PLASTIC: LIQUID CRYSTAL POLYMER (LCP) PER MIL-M-24519 OR PER ASTM D5138
 2. STANDARD 1.0 X 0.25mm MOUNTING AND JACKSCREW THREADS ARE SHOWN FOR REFERENCE ONLY AND MUST BE SPECIFIED IN THE NANONICS PART NUMBER WHEN REQUIRED. 1.2 X 0.25mm THREADS ALSO AVAILABLE.
 3. MOUNTING HARDWARE IS AVAILABLE WITH THIS CONFIGURATION (NOT SHOWN). HARDWARE MUST BE SPECIFIED IN THE NANONICS PART NUMBER. CONSULT TYCO ELECTRONICS FOR DETAILS.
 4. SMT LEADS ARE BeCu, TIN LEAD PLATED 60/40 COMPOSITION PER SAE-AMS-P-81728.
 5. NANONICS TERMINATION CODE: L4
 6. NANONICS TERMINATION CODE: L42
 7. NANONICS TERMINATION CODE: L44
 8. THIS DRAWING PREVIOUSLY IDENTIFIED AS NANONICS **N10138/232**

THIS DRAWING IS A CONTROLLED DOCUMENT.			DWN D. RYAN 21 APR 92		tyco Electronics		Tyco Electronics Corporation Harrisburg, PA 17105		
DIMENSIONS: INCHES			TOLERANCES UNLESS OTHERWISE SPECIFIED:		CHK E. PAULUS 23 AUG 99		APPROVED M. STORRY 3 APR 01		
			1 PLC ± -		NAME RECEPTACLE ASSEMBLY, VERTICAL SURFACE MOUNT, TWO ROW DUALOBE, PLASTIC OR METAL		SIZE A2 CAGE CODE 00779 DRAWING NO C-1589484 RESTRICTED TO -		
			2 PLC ± -						
			3 PLC ± .010						
			4 PLC ± .005						
			ANGLES ± -						
			± 1						
MATERIAL SEE NOTES			FINISH SEE NOTES		WEIGHT -				
CUSTOMER DRAWING					SCALE 8.1		SHEET 1 OF 2		REV P

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
		P	LTR	DATE	DWN APVD
DF	D0		P	UPDATE PER 0H2Y-0164-04	12 MAY 04CASMKS

D

C

B



A

D


C

B

A



TYPICAL FOOT PLACEMENT
ON SOLDER PAD



SIZE 15 SHOWN FOR REFERENCE

TYPICAL PCB LAYOUT

$\triangle 9.$ POSITIONAL TOLERANCES FOR BASIC DIMENSIONED FEATURES ARE RELATIVE TO FIDUCIALS OR SOME SIMILAR DATUM REFERENCE DEFINED BY THE PCB DESIGNER.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN D. RYAN 21 APR 92	tyco Electronics Tyco Electronics Corporation Harrisburg, PA 17105			
DIMENSIONS: INCHES		CHK E. PAULUS 23 AUG 99				
	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD M. STORRY 3 APR 01	NAME			
		PRODUCT SPEC	RECEPTACLE ASSEMBLY, VERTICAL SURFACE MOUNT, TWO ROW DUALLOBE, PLASTIC OR METAL			
		APPLICATION SPEC				
MATERIAL -	FINISH -	WEIGHT -	SIZE A2	CAGE CODE 00779	DRAWING NO C=1589484	RESTRICTED TO -
CUSTOMER DRAWING			SCALE 8:1	SHEET 2	OF 2	REV P

1589484

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[STM037L4SN](#)