# SAFETY ORGANIZATIONS

THIS FILTER HAS BEEN FORMALLY RECOGNIZED, CERTIFIED OR APPROVED BY THE LISTED AGENCY. THEREFORE, ALL TEST/REQUIREMENTS SPECIFIED IN THE LATEST REVISION OF THE FOLLOWING AGENCY STANDARDS HAVE BEEN MET:

UL RECOGNIZED: LL 1283

CSA CERTIFIED: CSA 22.2, # 0,0.4,8

VOE APPROVED: EN 133 200

#### OPERATING SPECIFICATIONS

LINE CURRENT/VOLTAGE: 15 AMP, 120/250 VAC,

10 AMP/40°C, 250 VAC

LINE FREQUENCY:

50-60Hz

MAXIMUM LEAKAGE CURRENT,

EACH LINE TO GROUND:

2 μA @ 120V 60Hz 5 μA @ 250V 50Hz

DPERATING AMBIENT TEMP. RANGE: -10°C TO +40°C @ RATED CURRENT,  $I_r$ . IN AN AMBIENT,  $I_o$ , HIGHER THAN 40°C, THE MAXIMUM DPERATING CURRENT,  $I_o$ , IS AS FOLLOWS:  $I_r = I_r - \sqrt{100 - I_o}$ 

 $I_0 = I_r - \sqrt{\frac{100 - I_0}{60}}$ 

### RELIABILITY SPECIFICATIONS:

STORAGE TEMPERATURE: -40°C TD +85°C HUMIDITY: 21 DAYS @ 40°C 95% RH. CURRENT OVERLOAD TEST: 6 TIMES I<sub>r</sub> FOR 8 SECONDS CUSTOMER DRAWING
CATALOG # 15SRBS8
ECN # APPRVD. DATE
07-026555 PJD 08NDV07

# TEST SPECIFICATIONS:

INDUCTANCE: N/A mH

CAPACITANCE: (MEASURED @ IKHz, 0.250VAC MAX., 25°C±1°C)

LINE TO GROUND: N/A
LINE TO LINE: N/A
DISCHARGE RESISTOR: N/A

L/G AND L/L I.R.

ND DISCHARGE RESISTOR: 6000M (MIN.) @ 100VDC,


20°C AND 50% RH

# RECOMMENDED RECEIVING INSPECTION HIPOT:

LINE TO GROUND: 1500 VAC FOR 1 MINUTE LINE TO LINE: 1450 VOC FOR 1 MINUTE

# FILTER APPROVAL:

THE BEST WAY TO SELECT AND QUALIFY A FILTER IS FOR YOUR ENGINEERING TO TEST THE UNIT IN YOUR EQUIPMENT.



50A- 50A(MINIMUM) INSERTION LOSS						22	THIRD ANGLE	<b>=</b>
FREDUENCY MHz	1.0	5.0	10	50	100	300	PROJECTION UNLESS OTHERWISE SPECIFIED,	Tyco Electronics COXCON PRODUCTS, 620 S. BUTTERFIELD RD. NUMBELEIN IL 60060
COMMON dB	/	/	1	/	/	/	TOLERANCE TO BE ± .025  MATERIAL & FINISH: AS SUPPLIED  THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO	POWER LINE FILTER
DIFF. d8	/	/	/	/	1	/	TYCO ELECTRONICS CORPORATION NO 115 WORLDWICE SUBSTOLARIES NOW AFFELTATES. 17 MAY MOT GE DISCLOSED TO ANDRE OTHER THAN TYCO ELECTRONICS FERSONEL, WITHOUT WITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION.	SCALE: .75:) DATE:   DATACOG NO.   RE   DATACOG NO.   DATAC

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 15SRBS8