



Material Material Tube Material Material <th< th=""><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></th<>														
PRUDUCI CUDE (FIRST 5 DIGITS) MATERIAL TUBE SPACING No. TUBES 41 "C" "C" TUBE PUSITIUN PITCH HS024 / HC024 20 12.7 HS024 / HC030 20 12.7 HS044 / HC060 10 25.4 HS05 / HC090 10 10 25.4 HS127 / HC120 5 5 50.8 HS127 / HC120 5 10 25.4 HS254 / HC240 5 10.8 12.7 HS381 / HC390 2 127 12.7 HS381 / HC390 2 127 12.7 10.8 12.7 11.0 ACCUMULATIVE PITCH ERROR THRDUGH PACK IS ACCEPTABLE	LOC DIST				REVISIONS									
PRODUCT CODE (FIRST 5 DIGITS) MATERIAL TUBE SPACING No. TUBES AT 'C' HS024 / HC024 20 HS032 / HC030 20 HS04 / HC050 20 HS04 / HC060 10 HS052 / HC090 10 HS055 / HC090 10 HS055 / HC090 10 HS127 / HC120 5 S088 HC240 HS190 / HC180 5 HS254 / HC240 5 HS254 / HC240 5 HS254 / HC240 5 HS381 / HC390 2 HS381 / HC39		-	_	Р	LTR			DESCI	RIPTION			DATE	DWN	APVD
PRDDUCT CDDE (FIRST 5 DIGITS) No. TUBES AT "C" "C" TUBE POISITION PITCH HS024 / HC024 20 12.7 HS032 / HC030 20 12.7 HS04 / HC060 10 25.4 HS07 / HC180 5 50.8 HS127 / HC180 5 50.8 HS127 / HC180 5 50.8 HS254 / HC240 5 50.8 HS381 / HC390 2 127 HS381 / HC390 2 127 NDTES:- 1.0 25.4 HS381 / HC390 5 50.8 HS381 / HC390 2 127 NDTES:- 1. ND ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE		L			1	INITIAL	DRAWIN	IG				240CT201	1 AFK	MA
PRDDUCT CDDE (FIRST 5 DIGITS) No. TUBES AT "C" "C" TUBE POISITION PITCH HS024 / HC024 20 12.7 HS032 / HC030 20 12.7 HS044 / HC060 10 25.4 HS075 / HC090 10 25.4 HS127 / HC120 5 50.8 HS127 / HC180 5 50.8 HS127 / HC190 2 12.7 HS127 / HC180 5 50.8 HS127 / HC190 2 12.7 HS127 / HC180 5 50.8 HS254 / HC240 5 50.8 HS381 / HC390 2 127 NDTES:= 1. ND ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE														
PRDUCT CDDE (FIRST 5 DIGITS) No. TUBES AT "C" "C" TUBE POISITION PITCH HS024 / HC024 20 12.7 HS032 / HC030 20 12.7 HS048 / HC050 20 12.7 HS044 / HC060 10 25.4 HS095 / HC090 10 25.4 HS127 / HC120 5 50.8 HS190 / HC180 5 50.8 HS254 / HC240 5 50.8 HS381 / HC390 2 127 HS381 / HC390 2 127 NOTES:- 1. NO ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE														
PRDUCT CDDE (FIRST 5 DIGITS) No. TUBES AT "C" "C" TUBE POISITION PITCH HS024 / HC024 20 12.7 HS032 / HC030 20 12.7 HS048 / HC050 20 12.7 HS044 / HC060 10 25.4 HS095 / HC090 10 25.4 HS127 / HC120 5 50.8 HS190 / HC180 5 50.8 HS254 / HC240 5 50.8 HS381 / HC390 2 127 HS381 / HC390 2 127 NOTES:- 1. NO ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE														
PRDDUCT CDDE (FIRST 5 DIGITS) No. TUBES AT "C" "C" TUBE POISITION PITCH HS024 / HC024 20 12.7 HS032 / HC030 20 12.7 HS044 / HC060 10 25.4 HS075 / HC090 10 25.4 HS127 / HC120 5 50.8 HS127 / HC180 5 50.8 HS127 / HC190 2 12.7 HS127 / HC180 5 50.8 HS127 / HC190 2 12.7 HS127 / HC180 5 50.8 HS254 / HC240 5 50.8 HS381 / HC390 2 127 NDTES:= 1. ND ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE														
PRDDUCT CDDE (FIRST 5 DIGITS) No. TUBES AT "C" "C" TUBE POISITION PITCH HS024 / HC024 20 12.7 HS032 / HC030 20 12.7 HS04 / HC060 10 25.4 HS07 / HC180 5 50.8 HS127 / HC180 5 50.8 HS127 / HC180 5 50.8 HS254 / HC240 5 50.8 HS381 / HC390 2 127 HS381 / HC390 2 127 NDTES:- 1.0 25.4 HS381 / HC390 5 50.8 HS381 / HC390 2 127 NDTES:- 1. ND ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE														
PRDDUCT CDDE (FIRST 5 DIGITS) No. TUBES AT "C" "C" TUBE POISITION PITCH HS024 / HC024 20 12.7 HS032 / HC030 20 12.7 HS044 / HC050 20 12.7 HS045 / HC090 10 25.4 HS127 / HC120 5 50.8 HS127 / HC180 5 50.8 HS254 / HC240 5 50.8 HS254 / HC390 2 127														
PRDDUCT CDDE (FIRST 5 DIGITS) No. TUBES AT "C" "C" TUBE POISITION PITCH HS024 / HC024 20 12.7 HS032 / HC030 20 12.7 HS044 / HC060 10 25.4 HS075 / HC090 10 25.4 HS127 / HC180 5 50.8 HS127 / HC180 5 50.8 HS190 / HC180 5 50.8 HS284 / HC390 2 127						MATER	τ ιλτς	IIBE SP/						
NIGTES:- PITCH PITCH HS024 / HC024 20 12.7 HS032 / HC030 20 12.7 HS04 / HC060 10 25.4 HS05 / HC090 10 25.4 HS127 / HC120 5 50.8 HS190 / HC180 5 50.8 HS254 / HC390 2 127 HS381 / HC390 2 127 N□TES:- 1. N□ ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE														
HS024 / HC024 20 12.7 HS032 / HC030 20 12.7 HS04 / HC050 20 12.7 HS054 / HC060 10 25.4 HS07 / HC120 5 50.8 HS190 / HC180 5 50.8 HS381 / HC390 2 127 N□TES:- 1. N□ ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE	(FIRS	T 5 DI	(GITS)	No.			ıl ″U″							
HS032 / HC030 20 12.7 HS048 / HC050 20 12.7 HS064 / HC060 10 25.4 HS095 / HC090 10 25.4 HS127 / HC120 5 50.8 HS190 / HC180 5 50.8 HS254 / HC240 5 50.8 HS381 / HC390 2 127 N□TES:- 1. N□ ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE			<u> </u>											
HS048 / HC050 20 12.7 HS064 / HC060 10 25.4 HS095 / HC090 10 25.4 HS127 / HC120 5 50.8 HS190 / HC180 5 50.8 HS254 / HC240 5 50.8 HS381 / HC390 2 127 N□TES:= 1. ND ACCUMULATIVE PITCH ERROR THRDUGH PACK IS ACCEPTABLE														
HS064 / HC060 10 25.4 HS095 / HC090 10 25.4 HS127 / HC120 5 50.8 HS190 / HC180 5 50.8 HS254 / HC240 5 50.8 HS381 / HC390 2 127 N□TES:- 1. N□ ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE														
HS095 / HC090 10 25.4 HS127 / HC120 5 50.8 HS190 / HC180 5 50.8 HS254 / HC240 5 50.8 HS381 / HC390 2 127 N□TES:- 1. N□ ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE														
HS127 / HC120 5 50.8 HS190 / HC180 5 50.8 HS254 / HC240 5 50.8 HS381 / HC390 2 127 N□TES:- 1. N□ ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE														
HS190 / HC180 5 50.8 HS254 / HC240 5 50.8 HS381 / HC390 2 127 N□TES:- 1. N□ ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE														
<u>HS254 / HC240 5 50.8</u> <u>HS381 / HC390 2 127</u> N□TES:- 1. N□ ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE														
NOTES:- 1. NO ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE														
NOTES: 1. NO ACCUMULATIVE PITCH ERROR THROUGH PACK IS ACCEPTABLE														
1. ND ACCUMULATI∨E PITCH ERROR THROUGH PACK IS ACCEPTABLE	HS36	31 / Hi	C390			2			127					
	1.	ND A	CCUM	ULAI					THROUG	Н РА	CK IS	S ACCE	ΈΓΑ]	BLE
LED DOCUMENT. DWN 240CT2011	1. 2.	ND A Pac	ICCUM KAGI	ULAI	AS	REG	QUIRE	ED					:PTA]	BLE
CHK - TE Connectivity	1. 2.	ND A Pac	CCUM KAGI	ULAI	AS	REG 240ct201	QUIRE	ED					ΈΓΤΑ]	BLE
ERANCES UNLESS	1. 2. LED DOC	ND A PAC CUMENT.	CCUM KAGI	ULAI	AS	REG 240CT2011		ED					ΈΡΤΑ]	BLE
AFK TE Connectivity CHK - ERANCES UNLESS RWISE SPECIFIED: APVD - - HSI DOT MATRIX HS/HC DOUBLE	1. 2. ED DOC	ND A PAC CUMENT.	DWN AFK CHK APVD -	ULAI NG	AS	REG 240CT2011		ED HS	C TE dot ma	TE TRIX H	Conne IS/HC	ctivity DOUBLE	:PTA]	BLE
LED DOCUMENT: AFK CHK TE Connectivity CHK - - - - - ERANCES UNLESS RWISE SPECIFIED: APVD - NAME - - ± - - PRODUCT SPEC - - HSI DOT MATRIX HS/HC DOUBLE ± - - - SIDED NARROW ASSEMBLY (038)	1, 2, LED DOC ERANCES L RWISE SP ± - ± -	ND A PAC CUMENT.	DWN AFK CHK APVD -	ULAI NG	AS	REG 240CT2011		ED HS	C TE dot ma	TE TRIX H	Conne IS/HC	ctivity DOUBLE	:PTA]	BLE
LED DOCUMENT. AFK EXAMPLE CHK - - ERANCES UNLESS RWISE SPECIFIED: APVD - ± - - - ± - - - ± - - - ± 0.25 - - ± - - - ± 0.25 - - ± - - - ± - - - ± - - - ± - - - ± - - - ± - - - APPLICATION SPEC - -	1. 2. ED DOC ERANCES U RWISE SP ± - ± - ± 0.25 ± -	ND A PAC CUMENT.	DWN AFK CHK APVD PRODUCT	ULA NG	AS	REG 240CT2011		E D HS SIE	DOT MA	TE TRIX H	Conne IS/HC	ctivity DOUBLE		
LED DOCUMENT. AFK CHK TE Connectivity CHK - - - - - ERANCES UNLESS RWISE SPECIFIED: APVD - - NAME ± - - - - - - ± - - - SIDED NARROW ASSEMBLY (038) - ± - - - - - - ± - - - SIZE CAGE CODE DRAWING NO RESTRICTED TO	1. 2. ED DOC ERANCES U RWISE SP ± - ± 0.25 ± - ± 0.25 ± - ± -	ND A PAC CUMENT.	DWN AFK CHK APVD PRODUCT APPLICAT	ULA NG	AS	REG 240CT2011		E D HS SIE CAGE CODE	DOT MA DOT MA DED NARR	TE TRIX H 20W AS –	Conne IS/HC SSEMBL	ctivity DOUBLE		
LED DOCUMENT. AFK ERANCES UNLESS TE Connectivity ERANCES UNLESS RWISE SPECIFIED: APVD - NAME ± - + - HSI DOT MATRIX HS/HC DOUBLE ± - + SIDED NARROW ASSEMBLY (038) ± - + - ± - + SIZE ± - - - ± - - - ± - - - ± - - - ± - SIZE CAGE CODE DRAWING NO RESTRICTED TO - -	1. 2. ED DOC ERANCES U RWISE SP ± - ± 0.25 ± - ± 0.25 ± - ± -	ND A PAC CUMENT.	DWN AFK CHK APVD PRODUCT APPLICAT	ULA NG	AS	REG 240CT2011		E D HS SIE CAGE CODE	DOT MA DOT MA DED NARR	TE TRIX H 20W AS –	Conne IS/HC SSEMBL	ctivity DOUBLE		

THIS DRAWING IS A CO	ONTROLLED DOCUMENT.	DWN 240CT2011 AFK	_	
		СНК –		
DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD –	NAME	
mm	official stream to the stream	_		
	0 PLC ± - 1 PLC ± - 2 PLC ± 0.25 3 PLC ± - 4 PLC ± -	PRODUCT SPEC — APPLICATION SPEC	SIZE	С
	ANGLES ± -			
MATERIAL	FINISH	WEIGHT	A3	-
IRRADIATED POLTOLEFIN	_	CUSTOMER DRAWING		

С

В

А

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: EC7106-000