



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₃	REVISED ECN 97-0358-2	10/27/97	Tubag

ELECTRICAL	MECHANICAL	ENVIRONMENTAL	HOUSING	DIELECTRIC	CENTER CONTACT	COMPONENT	MATERIAL	FINISH		
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions MIL-STD-348A, Fig. <u>310-2</u>	Temperature Rating <u>-65°C To +125°C</u>	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PTFE FLUOROCARBON PER ASTM-D-1457	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	FRAC. ± 1/64	DEC. ±.005	ANGLES ± °	PASSIVATE PER QQ-P-35
Frequency Range (GHz) DC to <u>18</u>	Recommended Mating Torque <u>7-10 in-Lbs</u>	Vibration MIL-STD-202, Method 204, Condition B				DATE	RMK 4-30-69			
Volt Rating (VRMS MAX) @ Sea Level <u>335</u>	Mating Characteristics: Insertion (MAX Lbs) <u>3.0</u>	Shock MIL-STD-202, Method 213, Condition I				CHECKED BY	PW 5/14/69			
VSWR <u>1.05 + .005f GHz</u>	Withdrawal (MIN Oz) <u>1.0</u>	Thermal Shock MIL-STD-202, Method 107, Condition B,				APPD BY	SIR 5/14/69			
Insertion Loss (dB MAX) <u>.03 √f GHz</u>	Force to Engage and Disengage (In/Lbs MAX) <u>2</u>	Moisture Resistance MIL-STD-202, Method 106, Except Vibration				DRAWN BY				
RF Leakage (dB MIN) <u>-[60-f(GHz)]</u>	Center Contact Captivation Axial (Lbs) <u>6.0</u>	Shall Be Omitted				DATE				
Corona, 70,000 Ft (VRMS MIN) <u>250</u>	Radial (In/Oz) <u>4.0</u>	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray				DATE				
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1000</u>	Weight (Grams) <u>2.2</u>					DATE				
Contact Resistance (Milliohms MAX) Center Contact <u>3.0</u>						DATE				
Outer Contact <u>2.0</u>						DATE				
Cable to Housing <u>N/A</u>						DATE				
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>670</u>						DATE				
LR.(Megohms MIN) <u>10,000</u>						DATE				
							DRAWN BY		AMP Incorporated	
							CHECKED BY		140 Fourth Avenue	
							APPD BY		Waltham, MA 02451-7599	
							DATE		TITLE	
							DATE		OSM FLANGE MOUNT JACK RECEPTACLE STRAIGHT TERMINAL	
							DATE		SIZE	
							DATE		B	
							DATE		CODE IDENT NO.	
							DATE		26805	
							DATE		2052-1352-02	
							DATE		REV	
							DATE		01 ₃	
							DATE		SCALE	
							DATE		4 : 1	
							DATE		SHEET 1 OF 1	
							DATE			

.XXX = in
XX.X = mm (REF)

These drawings and specifications are the property of M/A-COM Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

USE ASS'Y PROCEDURE
NO. AP. N/A

AMP Incorporated			
140 Fourth Avenue			
Waltham, MA 02451-7599			
TITLE		OSM FLANGE MOUNT JACK RECEPTACLE STRAIGHT TERMINAL	
SIZE	CODE IDENT NO.	2052-1352-02	REV
B	26805		01 ₃
SCALE	4 : 1		SHEET 1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2052-1352-02](#)