

	REVISIONS				
R	₹EV	DESCRIPTION	DATE	APPROVED	
)4 1	REVISED	6/19/3/8/9 6/19/3/8/9/9	BAC	

.XXX = inXX.X = mm

	DIM "A"	DIM "B"
BEFORE	. <u>940</u> REF	.931 REF
CRIMPING	23.9	23.6
AFTER	.885 MAX	.811 REF
CRIMPING	22.5	20.6

DIM "A"	DIM "B"
.940 REF	.931 REF
23.9	23.6
.885 MAX	.811 REF
22.5	20.6

NOTES:

- 1. DESIGNED FOR USE WITH .141 DIA (RG 402/U) SEMI-RIGID CABLE
- 2. CAPTURED CENTER CONTACT
- 3. PICTORIAL VIEW BEFORE CRIMPING
- 4. MINIMUM STRAIGHT CABLE LENGTH .336
- 5. IT IS SUGGESTED TO BEND CABLE PRIOR TO CRIMPING

CABLE ENTRY DIAMETER MINIMUM	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	DRAWN BY D. CAM CHECKED BY R. G.
	FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1°	APP'D BY R.M.F.
HOUSING .1425	These drawings and specificat-	
CONTACT .037	7 Ions are the property of M/A-COM incorporated and shall	USE A
	not be reproduced or copied or	
	used in whole or in part as the basis for the manufacture or	
	sale of item(s) without written permission.	NO. A
	per incomu.	

HOUSING COUPLING NUT BUSHING	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
COMPONENT	MATERIAL	FINISH

DATE 11/19/82 AMP incorporated 12/9/82 140 Fourth Avenue Waltham, MA 02451-7599 AMP 12/13/82 OSN STRAIGHT CABLE PLUG SOLDERLESS COMPRESSION CRIMP ATTACHMENT USE ASSY PROCEDURE 408-04745 04. sze B 000E IDENT NO. 26805 NO. AP. (30-085) 3001-7641-02 SCALE 4:1 SHEET 1 OF 1

CUSTOMER DRAWING

AMP PART # 1057077-1 SHEET 1 OF 1 REV A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

<u>TE Connectivity</u>: 3001-7641-02