1

FEATURES

Lead (Pb)-Bearing High Stability Thin Film Chip Resistors

- Metal film layer on high quality ceramic
- SnPb termination plating, Pb content > 6 %
- Excellent overall stability at different environmental conditions ≤ 0.05 % (1000 h rated power at 70 °C)
- Low temperature coefficient and tight tolerances (± 0.1 %; ± 10 ppm/K)
- Single lot date code available

APPLICATIONS

- Military
- Avionics
- Industrial

TECHNICAL SPECIFICATIO	NS					
DESCRIPTION	TNPW0402	TNPW0603	TNPW0805	TNPW1206	TNPW1210 ⁽¹⁾	
Imperial size	0402	0603	0805	1206	1210	
Metric size code	RR1005M	RR1608M	RR2012M	RR3216M	RR3225M	
Resistance range	10 Ω to 100 k Ω	10 Ω to 332 k Ω	10 Ω to 1 $M\Omega$	10 Ω to 2 M Ω	10 Ω to 3.01 M Ω	
Resistance tolerance	± 1 %; ± 0.5 %; ± 0.1 %					
Temperature coefficient		± 50 ppm/K; ± 2	25 ppm/K; ± 15 ppm	/K; ± 10 ppm/K		
Climatic category (LCT/UCT/days)	55/125/56	55/125/56	55/125/56	55/125/56	55/125/56	
Rated dissipation, P_{70} ⁽²⁾	0.063 W	0.1 W	0.125 W	0.25 W	0.33 W	
Operating voltage, $U_{\text{max.}}$ AC _{RMS} or DC	50 V	75 V	150 V	200 V	200 V	
Permissible film temperature, $\mathcal{P}_{\text{F max.}}$	155 °C					
Operating Temperature Range		-5	5 °C to 125 °C (155 °	°C)		
Thermal resistance ⁽³⁾	870 K/W	550 K/W	440 K/W	220 K/W	170 K/W	
Insulation voltage:						
U _{ins} 1 min	75 V	100 V	200 V	300 V	300 V	
Continuous	75 V	75 V	75 V	75 V	75 V	
Failure rate: FIT observed	≤ 0.3 x 10 ⁻⁹ /h					

Notes

⁽¹⁾ The detail specification EN140401-801 does not cover this product size.

TNPW High Stability Thin Film Chip Resistors are the perfect choice for most fields of modern electronics where lead (Pb)-bearing terminations are mandatory and reliability and

(2) Rated voltage \(\sqrt{P \times R}\). The power dissipation on the resistor generates a temperature rise against the local ambient, depending on the heat flow support of the printed-circuit board (thermal resistance). The rated dissipation applies only if the permitted film temperature is not exceeded.

⁽³⁾ Measuring conditions in accordance with EN 140401-801.



Vishay



stability are of major concern.

www.vishay.com

SHAY

TNPW

Vishay

TEMPERATURE C	OEFFICIENT AND R	ESISTANCE RANGE			
TYPE	TCR	TOLERANCE	RESISTANCE	E-SERIES	
	±50 ppm/K	±1%	10 0 to 100 k0	E24; E96	
	195 ppm///	± 0.5 %	10 12 10 100 K12		
TNPW0402	±25 ppm/K	± 0.1 %		F04: F100	
	±15 ppm/K	± 0.1 %	47 Ω to 100 k Ω	E24, E192	
	±10 ppm/K	± 0.1 %			
	±50 ppm/K	±1%		E24; E96	
	· 05 mm///	± 0.5 %	10 Ω to 332 kΩ		
TNPW0603	±25 ppm/K	± 0.1 %		F04: F100	
	±15 ppm/K	± 0.1 %	47 O to 222 kO	E24; E192	
	±10 ppm/K	± 0.1 %	47 12 to 332 kg		
	±50 ppm/K	±1%		E24; E96	
	. 05	± 0.5 %	10 Ω to 1.0 MΩ		
TNPW0805	±25 ppm/K	± 0.1 %		F04. F100	
	±15 ppm/K	± 0.1 %	47.0 to 1.0 MO	E24, E192	
	±10 ppm/K	± 0.1 %	47 12 10 1.0 1012		
	±50 ppm/K	±1%		E24; E96	
	· 05 mm///	± 0.5 %	10 Ω to 2.0 MΩ		
TNPW1206	±25 ppm/K	± 0.1 %		F04: F100	
	±15 ppm/K	± 0.1 %	47 0 to 0.0 MO	E24; E192	
	±10 ppm/K	± 0.1 %	47 \\2 to 2.0 M\\2		
	±50 ppm/K	±1%	10 0 to 0.01 MO	E24; E96	
	. 05	± 0.5 %			
TNPW1210	±25 ppm/K	± 0.1 %		F0.4: F100	
	±15 ppm/K	± 0.1 %	47 Ω to 2.13 MΩ	E24; E192	
	±10 ppm/K	± 0.1 %	7		

PART NUMBER	AND PRODUCT	DESCRIPTION			
Part Number: TNPW	12061K32DETA				
ΤΝΡ	W 1 2	0 6 1	K 3 2	DET	A
		<u>_</u>			
TYPE/SIZE	RESISTANCE	TOLERANCE	TCR	PACKAGING	SPECIAL
TNPW0402 TNPW0603 TNPW0805 TNPW1206	R = Decimal K = Thousand M = Million (4 digits)		H = ± 50 ppm/K E = ± 25 ppm/K X = ± 15 ppm/K Y = ± 10 ppm/K	TP TD CN TA	Blank = Standard 0H = Single lot date code
TNPW1210			·	TC	
Product Description	TNPW-1206 1.32K 0.	5 % T-9 RT1			
TNPW-1206	1.32K	0.5 %	T-9	RT1	
TYPE/SIZE	RESISTANCE	TOLERANCE	TCR	PACKAGING	SPECIAL
TNPW-0402 TNPW-0603 TNPW-0805 TNPW-1206 TNPW-1210	Examples: 1K32 = 1320 Ω 99.68K = 99 680 Ω 360 = 360 Ω	± 0.1 % ± 0.5 % ± 1.0 %	T-2 = ± 50 ppm/K T-9 = ± 25 ppm/K T-10 = ± 15 ppm/K T-13 = ± 10 ppm/K	TP1 RT7 R52 RT1 RT6	Blank = Standard BV20545 = Single lot date code

Notes

• The products can be ordered using either the PRODUCT DESCRIPTION or the PART NUMBER.

www.vishay.com

Vishay

PACKAGING						
ТҮРЕ	CODE	QUANTITY	PACKAGING STYLE	WIDTH	PITCH	REEL DIAMETER
TNPW0402	$TP1 = TP^{(1)}$	1000		8 mm	2	180 mm/7"
TNPW0402	RT7 = TD	10 000		8 mm	2	180 mm/7"
TNPW0603 TNPW0805 TNPW1206 TNPW1210	R52 = CN ⁽¹⁾	1000	Tape and reel cardboard tape acc. IEC 60286-3 Type I	8 mm	4	180 mm/7"
TNPW0603 TNPW0805 TNPW1206 TNPW1210	RT1 = TA	5000		8 mm	4	180 mm/7"

Note

⁽¹⁾ 1000 pieces packaging quantity is only available for precision resistors with tolerance \pm 0.1 %.

DESCRIPTION

The production is strictly controlled and follows an extensive set of instructions established for reproducibility. A homogeneous film of metal alloy is deposited on a high grade ceramic body (Al_2O_3) and conditioned to achieve the desired temperature coefficient. A special laser is used to achieve the target value by smoothly cutting an appropriate groove in the resistive layer without damaging the ceramics. The resistor elements are covered by a protective coating designed for electrical, mechanical and climatic protection. The terminations receive a final tin-lead (SnPb) on nickel plating. The result of the determined production is verified by an extensive testing procedure performed on 100 % of the individual resistors. Only accepted products are placed into the tape in accordance with **IEC 60286-3, Type I**. Resistance marking is not applied on TNPW0402.

ASSEMBLY

The resistors are suitable for processing on automatic SMD assembly systems. They are suitable for automatic soldering using wave, reflow or vapour phase as shown in **IEC 61760-1** ⁽¹⁾. Solderability is specified for 2 years after production. The permitted storage time is 20 years.

The terminations are plated with SnPb solder, controlled for a minimum lead Pb content of 6 % for compliance with the respective requirements of Bellcore, MIL and ESCC specifications.

The encapsulation is resistant to all cleaning solvents commonly used in the electronics industry, including alcohols, esters and aqueous solutions.

The suitability of conformal coatings, if applied, shall be qualified by appropriate means to ensure the long-term stability of the whole system.

RELATED PRODUCTS

For ordering TNPW with lead free terminations please refer to latest edition of data sheet TNPW e3, (www.vishay.com/doc?28758).

TNPS ESCC high-reliability thin film chip resistors are the premium choice for design and manufacture of equipment, where mature technology and proven reliability are of utmost importance.

(www.vishay.com/doc?28789)

Revision: 24-Jan-14

3



TNPW

Vishay

10 Ω

TH

100 Ω

1 kΩ

4.75 kΩ 4 | | ||

10 kΩ

שניר

Frequency f in MHz

500 1000





Ш

50 100



60

20

0

- 20

- 40

- 60

- 80

%

ZI-RO in % 40 5 10

TNPW0603

Т



HF Performance



HF Performance

HF Performance

1



HF Performance

Non-Linearity

4 For technical questions, contact: thinfilmchip@vishay.com

TNPW



Vishay



Derating

Note

The solid line is based on IEC/EN reference test conditions which is considered as standard mode. However, above that the maximum permissible film temperature is 155 °C (dashed line).



Single-Pulse High Voltage Overload Test 10/700 µs EN 140000 4.27

TNPW0603

111

10-4



Single-Pulse High Voltage Overload Test 1.2/50 µs EN 140000 4.27



Single Pulse





Revision: 24-Jan-14

Continuous Pulse

0.01

10-5

Continuous Pulse Load $\hat{P}_{\max}^{0.01}$

5

Document Number: 31006

For technical questions, contact: thinfilmchip@vishay.com THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT

Vishay

ΤΝΡΥ



TEST AND REQUIREMENTS

All tests are carried out in accordance with the following specifications:

IEC 60115-1, generic specification (includes tests)

EN 140400, sectional specification (includes schedule for qualification approval)

EN 140401-801, detail specification (includes schedule for conformance inspection)

The testing also covers most of the requirements specified by EIA/ECA-703 and JIS-C-5201-1. The tests are carried out under standard atmospheric conditions in accordance with IEC 60068-1, 5.3. A climate category is applied, defined by the lower category temperature (LCT), the upper category temperature (UCT), and the number of days of the damp heat, steady-state test (56). Unless otherwise specified the following values apply: Temperature: 15 °C to 35 °C Relative humidity: 45 % to 75 % Air pressure: 86 kPa to 106 kPa (860 mbar to 1060 mbar).

The components are mounted for testing on boards in accordance with EN60115-1, 4.31 unless otherwise specified. The parameters stated in the Test Procedures and Requirements table are based on the required tests and permitted limits of EN140401-801.

TEST PRO		AND REQUI	REMENTS			
EN 60115-1 CLAUSE	IEC 60068-2 TEST METHOD	TEST	PROCEDURE	REQUIREM	ENTS PERMISSIBLE C	HANGE (∆R)
			Stability for product type:			
			TNPW0402 TNPW0603 TNPW0805 TNPW1206 TNPW1210	10 Ω to < 100 Ω	\geq 100 Ω to 3.01 $M\Omega$	10 Ω to 3.01 MΩ
4.5	-	Resistance	-	± 0.	1 %	± 1 %; ± 0.5 %
4.8.4.2	-	Temperature coefficient	At (20/- 55/20) °C and (20/125/20) °C	± 25 ppm/K; ± 15 p	opm/K; ± 10 ppm/K	± 50 ppm/K; ± 25 ppm/K
4.25.1	-	Endurance	U = √P ₇₀ x R or ≤ U _{max} ; 1.5 h on; 0.5 h off;			
			70 °C; 1000 h	\pm (0.1 % R + 0.02 Ω)	\pm (0.05 % R + 0.01 Ω)	\pm (0.25 % R + 0.05 Ω)
4.25.3	-	Endurance at upper category temperature	125 °C; 1000 h	± (0.1 % <i>R</i> + 0.02 Ω)	± (0.05 % <i>R</i> + 0.01 Ω)	± (0.5 % <i>R</i> + 0.05 Ω)
4.13	-	Short time overload	$U = 2.5 \text{ x } \sqrt{P_{70} \text{ x } R}$ $\leq 2 \text{ x } U_{\text{max.}}; 2 \text{ s}$	± (0.05 % <i>R</i> + 0.01 Ω)	± (0.02 % <i>R</i> + 0.01 Ω)	± (0.1 % <i>R</i> + 0.02 Ω)
4.24	78 (Cab)	Damp heat, steady state	(40 ± 2) °C; (93 ± 3) % RH; 56 days	± (0.1 % <i>R</i> + 0.02 Ω)	± (0.05 % <i>R</i> + 0.01 Ω)	± (0.5 % <i>R</i> + 0.05 Ω)
4.19	14 (Na)	Rapid change of temperature	30 min at - 55 °C: 30 min at 125 °C; 5 cycles	± (0.05 % <i>R</i> + 0.01 Ω)	± (0.02 % <i>R</i> + 0.01 Ω)	± (0.1 % <i>R</i> + 0.02 Ω)
4.18.2	58 (Td)	Resistance to soldering heat	Solder bath method; (260 ± 5) °C; (10 ± 1) s	± (0.05 % <i>R</i> + 0.01 Ω)	± (0.02 % <i>R</i> + 0.01 Ω)	± (0.1 % <i>R</i> + 0.02 Ω)
4.35	-	Flammability, needle flame test	IEC 60695-11-5; 10 s		No burning after 30 s	

6 For technical questions, contact: <u>thinfilmchip@vishay.com</u>



TNPW Vishay

DIMENSIONS



DIMENSIONS	S AND MASS					
ТҮРЕ	H (mm)	L (mm)	W (mm)	T _t (mm)	Т _ь (mm)	MASS (mg)
TNPW0402	0.35 ± 0.05	1.0 ± 0.05	0.5 ± 0.05	0.2 ± 0.10	0.2 ± 0.10	0.65
TNPW0603	0.45 ± 0.10	1.6 ± 0.10	0.85 ± 0.10	0.3 ± 0.20	0.3 ± 0.20	2
TNPW0805	0.45 ± 0.10	2.0 ± 0.15	1.25 ± 0.15	0.4 ± 0.20	0.4 ± 0.20	5.5
TNPW1206	0.55 ± 0.10	3.2 ± 0.15	1.6 ± 0.15	0.5 ± 0.25	0.5 ± 0.25	10
TNPW1210	0.60 ± 0.15	3.2 ± 0.15	2.45 ± 0.15	0.5 ± 0.25	0.5 ± 0.25	16

SOLDER PAD DIMENSIONS



SOLDER PAD DIMENSIONS						
	REFLOW SOLDERING WAVE SOLDERING					ì
ТҮРЕ	Y (mm)	X (mm)	G (mm)	Y (mm)	X (mm)	G (mm)
TNPW0402	0.4	0.6	0.5	-	-	-
TNPW0603	0.5	0.9	1.0	0.9	0.9	1.0
TNPW0805	0.7	1.3	1.2	0.9	1.3	1.3
TNPW1206	0.9	1.7	2.0	1.1	1.7	2.3
TNPW1210	0.9	2.5	2.0	1.1	2.5	2.3



Vishay

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Vishay:

TNPW06032742BR52 TNPW06035052BR52 TNPW04021003BT TNPW04024752BT TNPW06032321DR52
TNPW0603140KBETA TNPW06039761BR52 TNPW06033163BR52 TNPW06033741BR52 TNPW08052492DT
TNPW12061252BT TNPW060340R2DT TNPW08051402BT-T10 TNPW06037322DT TNPW12066343FT
TNPW06036650BR52 TNPW06031650BR52 TNPW06034532BR52 TNPW06038250DR52 TNPW06033830BR52
TNPW06031912BR52 TNPW06031023BR52 TNPW060316R2BR52 TNPW060310K7BECN TNPW06033321DR52
TNPW060333R2DR52 TNPW04023122BT TNPW04027682BT TNPW060322R1BR52 TNPW08051052BT
TNPW08055491BT TNPW08057591BT TNPW12063092BT TNPW060326R1DT-T2 TNPW12062M00BECN
TNPW08052672BT TNPW06031603BR52 TNPW06033243BR52 TNPW06034641BR52 TNPW06038062BR52
TNPW12105421BT TNPW12063742BT TNPW12064422BT TNPW12066572BT TNPW06031152BT
TNPW08058661BT TNPW04022871BT TNPW04021272BT TNPW06035761BT TNPW06036811BR52
TNPW080528K7BHTA TNPW12062001BT-T10 TNPW06031801BT TNPW080543R2DHBD TNPW080549R9BHBD
TNPW080549R9FHBD TNPW080551R1DHBD TNPW080583R5BHBD TNPW120615K0BYBD
TNPW12061K00FKBD TNPW12061M00BXBD TNPW1206205RBYBD TNPW120620K0BYBD TNPW120624K9BYBD
TNPW12062K49BXBD TNPW120639R2FHBD TNPW12063K74BYBD TNPW12064K87BXBD
TNPW120651R1BHBD TNPW120655R5BHBD TNPW1206590RBHBD TNPW120659R0BHBD
TNPW120660K4BYBD TNPW120660R4FHBD TNPW1206665RBYBD TNPW120668R1BHBD
TNPW120680R6BHBD TNPW120688K7BXBD TNPW1206909KBXBD TNPW1210200RBHBD
TNPW0603562RBECN TNPW08055100BT TNPW040210R0DT TNPW040259R0DT TNPW06031133BT
TNPW06031580BT TNPW06031820BT TNPW06032801BT TNPW06033570BT TNPW06036041BT