


Thick Film Planar Resistors, Through-Hole, High Voltage



APPLICATIONS

Applications include power supplies, transformers and any application requiring operation within an environment where high voltages are used.

FEATURES

- 30 000 V capability
- Very low voltage coefficient to less than 1 ppm/V
- Outstanding stability under adverse conditions
- Stable cermet resistive element bonded to a high-purity alumina substrate
- Tough epoxy-based coating and high voltage stability
- Dividers available, see Vishay Techno's TD datasheet (www.vishay.com/doc?68042)
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS*
Available
**HALOGEN
FREE**

Note

* This datasheet provides information about parts that are RoHS-compliant and / or parts that are non-RoHS-compliant. For example, parts with lead (Pb) terminations are not RoHS-compliant. Please see the information / tables in this datasheet for details.

STANDARD ELECTRICAL SPECIFICATIONS					
GLOBAL MODEL / SIZE	POWER RATING <i>P</i> _{25 °C} W	MAXIMUM WORKING VOLTAGE ⁽¹⁾ V	RESISTANCE RANGE ⁽²⁾ Ω	TOLERANCE ± %	TEMPERATURE COEFFICIENT ± ppm/°C
TR03C	0.25	0.8K	300 to 3M	1, 2, 5, 10, 20	100
			300 to 25M	1, 2, 5, 10, 20	200, 300
TR03X		2.5K	25M to 250M	1, 2, 5, 10, 20	200, 300
			260M to 2G	5, 10, 20	200, 300
			2.1G to 10G	5, 10, 20	500
TR05D	0.5	4K	500 to 25M	1, 2, 5, 10, 20	100
			3K to 200M	1, 2, 5, 10, 20	200, 300
TR05X		5K	30M to 1G	1, 2, 5, 10, 20	200, 300
			1.1G to 20G	5, 10, 20	200, 300
			21G to 100G	5, 10, 20	500
TR10F	1	6.5K	1K to 16M	1, 2, 5, 10, 20	100
			2K to 120M	1, 2, 5, 10, 20	200, 300
TR10X		10K	20M to 1G	1, 2, 5, 10, 20	200, 300
			1.1G to 15G	5, 10, 20	200, 300
			16G to 1T	5, 10, 20	500
TR15G	1.5	12.5K	1.5K to 45M	1, 2, 5, 10, 20	100
			5K to 340M	1, 2, 5, 10, 20	200, 300
TR15X		15K	60M to 1G	1, 2, 5, 10, 20	200, 300
			1.1G to 35G	5, 10, 20	200, 300
			36G to 1.5T	5, 10, 20	500
TR20H	2	17.5K	2K to 64M	1, 2, 5, 10, 20	100
			8K to 480M	1, 2, 5, 10, 20	200, 300
TR20X		20K	80M to 1G	1, 2, 5, 10, 20	200, 300
			1.1G to 50G	5, 10, 20	200, 300
			51G to 2T	5, 10, 20	500
TR30J	3	25K	3K to 82M	1, 2, 5, 10, 20	100
			8.5K to 620M	1, 2, 5, 10, 20	200, 300
TR30X		30K	80M to 1G	1, 2, 5, 10, 20	200, 300
			1.1G to 60G	5, 10, 20	200, 300
			61G to 3T	5, 10, 20	500

Notes

- Custom sizes available
 - Voltage coefficient: typically less than 1 ppm/V (tested per MIL-STD-202)
- (1) Continuous working voltage shall be $\sqrt{P \times R}$ or maximum working voltage, whichever is less.
- (2) All resistance values are calibrated at 100 V_{DC}. Calibration at other voltages available upon request.

GLOBAL PART NUMBER INFORMATION

New Global Part Numbering: TR20H1K00FKEB (preferred part number format)

T	R	2	0	H	1	K	0	0	F	K	E	B
GLOBAL MODEL TR	SIZE / POWER / VOLTAGE RATING				RESISTANCE VALUE		TOLERANCE		TCR	TERMINAL FINISH		PACKAGING
	03C = 0.25 W, med. voltage 03X = 0.25 W, max. voltage 05D = 0.5 W, med. voltage 05X = 0.5 W, max. voltage 10F = 1 W, med. voltage 10X = 1 W, max. voltage 15G = 1.5 W, med. voltage 15X = 1.5 W, max. voltage 20H = 2 W, med. voltage 20X = 2 W, max. voltage 30J = 3 W, med. voltage 30X = 3 W, max. voltage				R = Ω K = k Ω M = M Ω G = G Ω T = T Ω 400R = 400 Ω 10M0 = 10 M Ω 1T00 = 1 T Ω		F = $\pm 1.0\%$ G = $\pm 2.0\%$ J = $\pm 5.0\%$ K = $\pm 10.0\%$ M = $\pm 20.0\%$		K = 100 ppm N = 200 ppm M = 300 ppm P = 500 ppm	E = Sn100 R = Sn60/Pb40		B = bag S = strip

Historical Part Numbering: TR20H1001FKE3 (will continue to be accepted)

TR	20H	1001	F	K	e3
HISTORICAL MODEL	SIZE / POWER RATING	RESISTANCE VALUE	TOLERANCE	TCR	TERMINAL FINISH

Note

- For additional information on packaging, refer to the Through Hole Resistor Packaging document (www.vishay.com/doc?31544).

MECHANICAL SPECIFICATIONS

Resistive Element: thick film

Substrate: 96 % pure alumina

Encapsulation: epoxy base, conformal coating

Terminals: solder plated copper leads

Terminal Strength: 4.5 pounds pull-test


Power: derated from ambient temperature +25 °C

ENVIRONMENTAL SPECIFICATIONS

Temperature Range: -55 °C to +125 °C (for higher temperature range, consult factory)

Load Life: less than 0.15 %, 1000 h


DIMENSIONS in inches (millimeters)



MODEL	A (LENGTH)	B (HEIGHT)	C (LEAD SPACING)	D (LEAD DIA.)
TR03	0.300 \pm 0.030 (7.62 \pm 0.76)	0.210 \pm 0.021 (5.33 \pm 0.53)	0.200 \pm 0.020 (5.08 \pm 0.51)	0.025 \pm 0.002 (0.64 \pm 0.05)
TR05	0.500 \pm 0.050 (12.70 \pm 1.27)	0.300 \pm 0.030 (7.62 \pm 0.76)	0.400 \pm 0.040 (10.16 \pm 1.02)	0.025 \pm 0.002 (0.64 \pm 0.05)
TR10	1.00 \pm 0.100 (25.40 \pm 2.54)	0.350 \pm 0.035 (8.89 \pm 0.89)	0.900 \pm 0.090 (22.86 \pm 2.29)	0.032 \pm 0.002 (0.81 \pm 0.05)
TR15	1.50 \pm 0.150 (38.10 \pm 3.81)	0.350 \pm 0.035 (8.89 \pm 0.89)	1.40 \pm 0.140 (35.56 \pm 3.56)	0.032 \pm 0.002 (0.81 \pm 0.05)
TR20	2.00 \pm 0.200 (50.80 \pm 5.08)	0.350 \pm 0.035 (8.89 \pm 0.89)	1.90 \pm 0.190 (48.26 \pm 4.83)	0.032 \pm 0.002 (0.81 \pm 0.05)
TR30	3.00 \pm 0.300 (76.20 \pm 7.62)	0.400 \pm 0.040 (10.16 \pm 1.02)	2.90 \pm 0.290 (73.66 \pm 7.37)	0.032 \pm 0.002 (0.81 \pm 0.05)



DERATING





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Vishay:](#)

[TR05C5008FKW](#) [TR03C5008FKW](#) [TR20H1706F](#) [TR10F5005FKW](#) [TR10F1006FK](#) [TR10F2505KKW](#)
[TR20H100MFNRS](#) [TR10F1005J](#) [TR10F1006J](#) [TR15G1007J](#) [TR10F50M0GNRS](#) [TR10F10M0JKRB](#)
[TR10F200MFKRS](#) [TR20H10M0FNRS](#) [TR20H50M0FKES](#) [TR10X1G00FNEB](#) [TR10F100MJNES](#) [TR03X1G10KNRB](#)
[TR15X1G00JNEB](#) [TR10F100MFNES](#) [TR15G20M0FKES](#) [TR15G500MFNES](#) [TR20H100MFNES](#) [TR10X1G00JNES](#)
[TR10X5G00JNES](#) [TR20X500MFNES](#) [TR15G50M0FNES](#) [TR15X1G00JNES](#) [TR20H10M0FKES](#) [TR20H1M50FKES](#)
[TR20H20M0FKES](#) [TR20X2G00JNES](#) [TR15G10M0FKES](#) [TR15G200MFNES](#) [TR15G250MFNES](#) [TR15G300MFNES](#)
[TR15G330KFKES](#) [TR15G4M00FKES](#) [TR10F5M00FKES](#) [TR10F80M0FNES](#) [TR10X200MJNES](#) [TR10X2G00JNES](#)
[TR10X500MFNES](#) [TR15G100MFNES](#) [TR10F20K0FKES](#) [TR10F2K50FKES](#) [TR10F2M00FKES](#) [TR10F390KFKES](#)
[TR10F40M0FNES](#) [TR10F50M0FNES](#) [TR05D10M0FKES](#) [TR05D1M50FKES](#) [TR05D200KFKES](#) [TR05D22M0FKES](#)
[TR10F10M0FKES](#) [TR10F200MFKES](#) [TR05D50M0FKES](#) [TR10F500MFKEB](#) [TR15X47G0JPRS](#) [TR15G30M0GNEB](#)
[TR10F1G00FKRS](#) [TR10X22M0KNEB](#) [TR10X500MGNEB](#) [TR10X100GKMEB](#) [TR20X1G00GNEB](#) [TR30J400MMNES](#)
[TR10X10G0KMEB](#) [TR05X100MFNES](#) [TR15X4G70JNRS](#) [TR05D30M0GNEB](#) [TR10X300MFNES](#) [TR05D1M50FNEB](#)
[TR10F57M6FKEB](#) [TR05D325KFNEB](#) [TR10X2G20GKRS](#) [TR05D49M9FKES](#) [TR03C20M0FKRS](#) [TR20H200MFKEB](#)
[TR05D100MFKEB](#) [TR15G60M0GNEB](#) [TR10F200MKKRB](#) [TR10F300MFKRB](#) [TR05D470MKKES](#) [TR10F8M06FKEB](#)
[TR10F1G00KKEB](#) [TR10F10M0JKEB](#) [TR10F60M0JNRS](#) [TR10F200MKKRS](#) [TR30J1M00JMEB](#) [TR15G150MJNES](#)
[TR20H5M00FKEB](#) [TR20H10M0FKEB](#) [TR05D1M00FKES](#) [TR05D1G00JNEB](#) [TR30J400MFKES](#) [TR10F1G00FKEB](#)
[TR05D20M0FNRB](#) [TR05D100MJKES](#) [TR05D500MFNES](#) [TR05D68M0FKRB](#)