


Ultra Precision Power Resistor (8 Watts, TO-220)



COMPOSITION OF TYPE NUMBER


Example:

PD X 50R000 B

Tolerance
Resistance Value
TCR
Type

Resistance value, in ohm, is expressed by a series of six characters, five of which represent significant digits. R or K is a dual-purpose letter that designates both the value range (R for ohmic; K for kilo-ohm) and the location of decimal point.

CONFIGURATION (DIMENSIONS IN mm)



| Type | PD |
|----------------|-----------|
| L | 10.6 max. |
| W | 19.0±0.5 |
| W ₁ | 8.5±0.2 |
| W ₂ | 6.5±0.2 |
| W ₃ | 2.7±0.5 |
| T | 4.5±0.2 |
| T ₁ | 2.0±0.5 |
| T ₂ | 1.5±0.2 |
| F | 5.08±0.5 |
| l | 11.0±2 |
| t | 0.5±0.05 |
| a | 1.2±0.1 |
| b | 0.75±0.05 |
| D | Dia. 3.6 |

TCR, RESISTANCE RANGE, TOLERANCE, RATED POWER


| Type | TCR (ppm/°C) -25°C to +125°C* | Resistance Range (Ω) | Resistance Tolerance (%)**† | Rated Power (W) at 25°C |
|------|----------------------------------|----------------------|-----------------------------------|--|
| PD | 0±15 (W) | 0.1 to 1 | ±1 to ±5 (F, G, J) | 1.5 In free air and 8 On heat sink** |
| | 0±15 (W) 0±5 (X) | 1 to 5 | ±0.5 to ±5 (D, F, G, J) | |
| | 0±15 (W) 0±5 (X) 0±2.5 (Y) | 5 to 10 | ±0.1 to ±5 (B, D, F, G, J) | |
| | | 10 to 25 | ±0.05 to ±5 (A, B, D, F, G, J) | |
| | | 25 to 10k | ±0.02 to ±5 (Q, A, B, D, F, G, J) | |

* Symbols in parentheses are for type number composition.

† Resistance figures are the values obtained by measuring the leads at point 5.08±0.6 mm away from the root.


** For heat sinking, an aluminum chassis in 152.4 (L) x 101.6 (W) x 50.8 (H) x 1.0 mm (T) should be used.

POWER DERATING CURVE




| PERFORMANCE | | | |
|--|--|--|--|
| Parameters | Test Condition | MIL-R-39009 Specification | ALPHA Typical Test Data |
| Maximum Rated Operating Temperature Working Temperature Range Maximum Working Voltage Maximum Working Current | | 25°C -55°C to +155°C 250V 4A | |
| Power Conditioning | 25°C, Rated Voltage, 96 hrs. | ±0.2% | ±0.02% |
| Low Temperature Storage Dielectric Withstanding Voltage Insulation Resistance Low Temperature Operation Overload Moisture Resistance Terminal Strength | -55°C, No Load, 24 hrs. Atmo. Pres.: AC 1 kV, 1 min. Baro. Pres. 8 mHg: AC 500V, 1min. DC 500V, 2 min. -55°C, Rated Voltage Rated Voltage x 2.5, 5 sec. +65°C to -10°C, 90% RH to 98% RH, Rated Voltage, 10 cycles (240 hrs.) 0.908 kg (2 pounds), 10 sec. | ±0.3% ±0.2% over 10,000 MΩ ±0.3% ±0.3% ±0.5% ±0.2% | ±0.005% ±0.005% over 10,000 MΩ ±0.005% ±0.01% ±0.05% ±0.005% |
| Shock Vibration, High Frequency | 100G, 6 ms, Sawtooth Wave, X, Y, Z, each 3 shocks 20G, 10 Hz to 2,000 Hz to 10 Hz, 20min., X, Y, Z, each 4 hrs. | ±0.2% ±0.2% | ±0.005% ±0.005% |
| Life | 25°C, Rated Power, 1.5 hr. – ON, 0.5 hr. – OFF, 2,000 hrs. | ±1.0% | ±0.01% |
| High Temperature Exposure | 155°C, No Load, 2,000 hrs. | ±1.0% | ±0.01% |
| Solderability | 245°C, 5 sec. | over 95% coverage | |

FREQUENCY CHARACTERISTICS



TEMPERATURE OF RESISTOR SURFACE



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase.

To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Vishay Precision Group:

[PDW1K0000Q](#) [PDW20R000B](#) [PDWR10000F](#) [PDWR20000F](#) [PDWR40000F](#) [PDWR50000F](#) [PDY100R00A](#)
[PDY100R00B](#) [PDY10R000A](#) [PDY13R000A](#) [PDY15R000A](#) [PDY1K0000Q](#) [PDX2R0000D](#) [PDX2R0000F](#)
[PDX4R0000D](#) [PDX4R0000F](#) [PDX5R0000B](#) [PDX8R3000F](#) [PDWR80000F](#) [PDX10R000B](#) [PDX1K0000Q](#)
[PDX1R0000D](#) [PDX1R0000F](#) [PDX1R0000J](#)