

SPECIFICATION:

ABOVE 100 mm

ANGLE

DIMENSION
BELOW 10 mm

TOLERANCE ± 0.3 ± 0.5 ± 0.8 ± 3°

10~100 mm

1. RATING 12 VDC,50mA •

2. CONTACT RESISTANCE : $100 m\Omega$ MAX $^{\circ}$

3.INSULATION RESISTANCE:100m Ω MIN $~500~\mathrm{V}~\mathrm{DC}~^{\circ}$


4. BREAKDOWN VOLTAGE: 230 VDC 。

5. OPERATING FORCE: 250±50gf °

6.TOTAL TRAVEL: 0.35 \pm 0.1mm $^{\circ}$

7. OPERATING TEMPERATURE: -20°C $\sim 70^{\circ}C$ $^{\circ}$

8. LIFE CYCLE: 100,000 CYCLE •



		3D FILE NAME	01	VER.	DΩ	DESIGN	CHANGE DESCRIPTION
<u> </u>	TC012-N11AS2WTUBXX	2D FILE NAME	Ф Д	VIEW	ALAN	CONFIRM	
\ \ \	TC012-N11AS2WTUBXX	PART	1:1	SCALE	KAVEN	APPROVAL	
	TACT SWITCH	MODE	mm	UNIT	2010/11/18	DATA	

WB Well Buying

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Well Buying:

TC012-N11AS2WTUBXX