







































































## AVIP Connector Specifications

Part Number	Description	Specifications	Photos	
<b>Computer Connectors</b>				
AV100BK	One 15 Pin HD Female to Female, single plate	VGA Connector, 15 pin female to female Insulator: PBT glass fiber reinforced UL 94 VO (black) Contact: Brass Contact plating: Gold plated over nickel Shell: Tin plated	 Top	 ISO
AV1002BK	One 15 Pin HD Female to Five BNC on 4" Pigtails, single plate	VGA to BNC Connector, 15 pin female to 5 BNC female Contact resistance: 10 Ω Insulation resistance: 5 MΩ Dielectric withstanding voltage: 300 VDC / 10 msec Contact: Brass Contact plating: Gold plated over nickel Shell: Tin plated	 Front	 Right
			 Top	 ISO
AV400BK	One 9 Pin HD Female to Female, single plate	VGA connector, 9 pin female to female Insulator: PBT glass fiber, reinforced UL 94 (blue) Contact: Brass Contact plating: Gold plated over nickel Shell: Tin plated	 Front	 Right
			 Top	 ISO
AV4005BK	One USB B Female to USB A Female Adapter, single plate	USB A female to female Contact resistance: 10 Ω Insulation resistance: 5 MΩ Dielectric withstanding voltage: 300 VDC / 10 msec	 Front	 Right
			 Top	 ISO
<b>Video Connectors</b>				
AV2002BK	One RCA Female to BNC Female Adapter, single plate	BNC bulkhead jack to RCA jack adapter Contact resistance: Center contact: 5 mΩ, max at 0.2 VDC, 1 amp Outer contact: 2 mΩ, max at 0.2 VDC, 1 amp Insulation resistance: 500 mΩ min Dielectric withstanding voltage: 500 VAC for 1 minute	 Top	 ISO
AV2003BK	Two RCA Female to BNC Female Adapters, single plate	BNC bulkhead jack to RCA jack adapter Contact resistance: Center contact: 5 mΩ, max at 0.2 VDC, 1 amp Outer contact: 2 mΩ, max at 0.2 VDC, 1 amp Insulation resistance: 500 MΩ min Dielectric withstanding voltage: 500 VAC for 1 minute	 Front	 Right
			 Top	 ISO
AV3000BK	One HDMI Female to Female Barrel, single plate	HDMI 19 Pin female to female Contact resistance: 10Ω Insulation resistance: 5 MΩ Dielectric withstanding voltage: 300 VDC / 10 msec	 Front	 Right
			 Top	 ISO
AV5000BK	One BNC Female to Female Barrel, single plate	BNC bulkhead female to female Contact resistance: 3 mΩ, max at 1 amp Insulation resistance: 1000 MΩ Dielectric withstanding voltage: 1500 VAC for 1 minute Frequency range: 0-4 Ghz VSWR: 1.2 max 0-2 Ghz Impedance: 75 Ω	 Top	 ISO
AV5001BK	Two BNC Female to Female Barrels, single plate	BNC bulkhead female to female Contact resistance: 3 mΩ, max at 1 amp Insulation resistance: 1000 MΩ Dielectric withstanding voltage: 1500 VAC for 1 minute Frequency range: 0-4 Ghz VSWR: 1.2 max 0-2 Ghz Impedance: 75 Ω	 Front	 Right
			 Top	 ISO
AV5002BK	Three BNC Female to Female Barrels, double plates	BNC bulkhead female to female Contact resistance: 3 mΩ, max at 1 amp Insulation resistance: 1000 MΩ Dielectric withstanding voltage: 1500 VAC for 1 minute Frequency range: 0-4 Ghz VSWR: 1.2 max 0-2 Ghz Impedance: 75 Ω	 Front	 Right
			 Top	 ISO
AV5004BK	One Display Port Female to One Display Port Female on 10" Pigtail, single plate	Display Port 20 Pin female to female Contact resistance: 10Ω Insulation resistance: 5 MΩ Dielectric withstanding voltage: 300 VDC / 10 msec	 Front	 Right
			 Top	 ISO
AV9010BK	One F-Connector Female to Female Barrel, single plate	F81 bulkhead female to female Contact resistance: 5 mΩ Insulation resistance: 500 MΩ min Dielectric withstanding voltage: 500 VAC for 1 minute Impedance: 75Ω nominal VSWR: 1.2 max 0-1.500 Mhz	 Front	 Right
			 Top	 ISO

## Audio/Video Connectors

AV2004BK	One RCA Female to BNC Female Adapter, One 3.5mm Stereo Mini Jack to Solder tabs, single plate	<p>BNC bulkhead to jack to RCA jack            Contact resistance: 5 mΩ max at 0.2 VDC, 1 amp            Outer contact: 2 mΩ max at 0.2 VDC, 1 amp            Insulation resistance: 500 MΩ min            Dielectric withstanding voltage: 500 VAC for 1 minute</p> <p>3.5 MM stereo jack            Contact resistance: 30 mΩ max            Insulation resistance: 100 MΩ min            Dielectric withstanding voltage: 500 VAC for 1 minute            Life test: 5000 cycles unloading (20-30 cycles per minute)</p>	<p><b>Top</b></p>  <p><b>Front</b></p> 	<p><b>ISO</b></p>  <p><b>Right</b></p> 
AV5005BK	One DVI F/F Barrel with 3.5mm Stereo with solder tabs, triple plate	<p>DVI 29 pin female to female            Contact resistance: 10 mΩ max            Insulation resistance: 5 MΩ min            Dielectric withstanding voltage: 300 VDC / 10 msec</p> <p>3.5 mm stereo jack            Contact resistance: 30 mΩ max            Insulation resistance: 100 MΩ min            Dielectric withstanding voltage: 500 VAC for 1 minute            Life test: 5000 cycles unloading (20-30 cycles per minute)</p>	<p><b>Top</b></p>  <p><b>Front</b></p> 	<p><b>ISO</b></p>  <p><b>Right</b></p> 
<b>Audio Connectors</b>				
AV6001BK	Two RCA Female to Solder Cups White, single plate	<p>RCA phone jack            Delrin insulator color: red and white            Nut &amp; center pin: Nickel plate over bronze</p>	<p><b>Top</b></p>  <p><b>Front</b></p> 	<p><b>ISO</b></p>  <p><b>Right</b></p> 
AV7000BK	One 1/4" Stereo Phone Female to Solder Tabs, single plate	<p>1/4" stereo jack with solder tabs            Contact resistance: 30 mΩ max            Insulation resistance: 100 MΩ min            Dielectric withstanding voltage: 500 VAC for 1 minute</p>	<p><b>Top</b></p>  <p><b>Front</b></p> 	<p><b>ISO</b></p>  <p><b>Right</b></p> 
AV7004BK	One 3.5mm Stereo Mini Jack to Solder Tabs, single plate	<p>3.5 mm stereo jack with solder tabs            Contact resistance: 30 mΩ max            Insulation resistance: 100 MΩ min            Dielectric withstanding voltage: 500 VAC for 1 minute            Life Test: 5000 cycles unloading (20-30 cycles/min)</p>	<p><b>Top</b></p>  <p><b>Front</b></p> 	<p><b>ISO</b></p>  <p><b>Right</b></p> 
AV7005BK	One 3.5mm Stereo Mini Jack to Captive Screw Term, single plate	<p>3.5 mm stereo jack with captive screw terminal            Contact resistance: 30 mΩ max            Insulation resistance: 100 MΩ min            Dielectric withstanding voltage: 500 VAC for 1 minute</p>	<p><b>Top</b></p>  <p><b>Front</b></p> 	<p><b>ISO</b></p>  <p><b>Right</b></p> 
AV8008BK	One XLR 3-pin Male to Solder cups, double plates	<p>XLR 3 pin male            Metal shell: Die cast zinc alloy, nickel plated            Insulator: ABS, gray            Contact resistance: 50 mΩ max            Insulation resistance: 1000 MΩ min            Dielectric withstanding voltage: 1000 VAC for 1 minute            Current rating: 15A @ 125 VAC</p>	<p><b>Top</b></p>  <p><b>Front</b></p> 	<p><b>ISO</b></p>  <p><b>Right</b></p> 
AV8009BK	One XLR 3-pin Female to Solder cups, double plates	<p>XLR 3 pin female            Metal shell: Die cast zinc alloy, nickel plated            Insulator: ABS, gray            Contact resistance: 50 mΩ max            Insulation resistance: 1000 MΩ min            Dielectric withstanding voltage: 1000 VAC for 1 minute            Current rating: 15A @ 125 VAC</p>	<p><b>Top</b></p>  <p><b>Front</b></p> 	<p><b>ISO</b></p>  <p><b>Right</b></p> 
AV8010BK	One Mini XLR 3-pin Male to Solder Cups, single plate	<p>Mini XLR 3 pin male            Contact resistance: 50 mΩ max            Insulation resistance: 500 MΩ            Dielectric withstanding voltage: 1000 VAC for 1 minute            Current rating: 5A @ 125 VAC</p>	<p><b>Top</b></p>  <p><b>Front</b></p> 	<p><b>ISO</b></p>  <p><b>Right</b></p> 

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Wiremold:

[AV1000BK](#) [AV1002BK](#) [AV2002BK](#) [AV2003BK](#) [AV2004BK](#) [AV3000BK](#) [AV4000BK](#) [AV4005BK](#) [AV5000BK](#)  
[AV5001BK](#) [AV5002BK](#) [AV5004BK](#) [AV5005BK](#) [AV6001BK](#) [AV7000BK](#) [AV7004BK](#) [AV7005BK](#) [AV8008BK](#)  
[AV8009BK](#) [AV8010BK](#) [AV8011BK](#) [AV8012BK](#) [AV8013BK](#) [AV8014BK](#) [AV8015BK](#) [AV8016BK](#) [AV9003BK](#)  
[AV9004BK](#) [AV9008BK](#) [AV9010BK](#) [AV9012BK](#) [AV9014BK](#) [AV9015BK](#) [AV9016BK](#)