

ENGINEERING KITS: AUTOMOTIVE GRADE MOLDED INDUCTORS

- PA4340ANLKIT

PA4343ANLKIT

PA4349ANLKIT

- PA4341ANLKIT

- PA4344ANLKIT

- PA4342ANLKIT

- PA4346ANLKIT



KIT Description

The new PA434X"A" series is a higher operating temperature version of our molded inductor family. Designed for application temperatures from -55 to +155C these TS16949 certified inductors are ideally suited for many of today's sensitive Automotive applications. These new series is available for multiple cross reference sizes, and free samples available through our web portal.



Additional Information

The Molded powder inductors feature an iron powder core material that directly mold to the copper wire. This provides an optimal solution for designs that require high frequencies and high current with low DC resistance. These inductors have high EMI performance. And the reason for that, is the copper turns that are completely surrounded by magnetic material. This controls the flux in the package, eliminating the noise, and keeping the magnetic flux from straying outside the inductor. The Pulse "A" series inductor family is ideal for high current, non-isolated DC/DC converters and voltage regulators. The addition of the TS16949 certification allows these parts to be used in automotive applications where higher operating temp and reliability are required.



Datasheets

PA4340ANLT

- PA4343ANLT

PA4349ANLT

PA4341ANLT

PA4344ANLT

PA4342ANLT

PA4346ANLT

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pulse:

PA4344ANLKIT PA4346ANLKIT PA4349ANLKIT PA4340ANLKIT PA4342ANLKIT PA4343ANLKIT