

# DATA SHEET

## **SURFACE-MOUNT CERAMIC MULTILAYER CAPACITORS**

General Purpose & High Capacitance

Class 2, X7R

6.3 V TO 50 V

100 pF to 22  $\mu$ F

RoHS compliant & Halogen Free



## SCOPE

This specification describes X7R series chip capacitors with lead-free terminations.

## APPLICATIONS

- PCs, Hard disk, Game PCs
- DVDs, Video cameras
- Mobile phones
- Data processing

## FEATURES

- Supplied in tape on reel
- Nickel-barrier end termination
- RoHS compliant
- Halogen Free compliant

## ORDERING INFORMATION – GLOBAL PART NUMBER, PHYCOMP CTC & 12NC

All part numbers are identified by the series, size, tolerance, TC material, packing style, voltage, process code, termination and capacitance value.

### YAGEO BRAND ordering code

#### GLOBAL PART NUMBER (PREFERRED)

CC XXXX X X X7R X BB XXX  
(1) (2) (3) (4) (5)

#### (1) SIZE – INCH BASED (METRIC)

0201 (0603)  
0402 (1005)  
0603 (1608)  
0805 (2012)  
1206 (3216)  
1210 (3225)  
1812 (4532)

#### (2) TOLERANCE

J =  $\pm 5\%$  <sup>(1)</sup>  
K =  $\pm 10\%$   
M =  $\pm 20\%$

#### (3) PACKING STYLE

R = Paper/PE taping reel; Reel 7 inch  
K = Blister taping reel; Reel 7 inch  
P = Paper/PE taping reel; Reel 13 inch  
F = Blister taping reel; Reel 13 inch  
C = Bulk case

#### (4) RATED VOLTAGE

5 = 6.3 V  
6 = 10 V  
7 = 16 V  
8 = 25 V  
9 = 50 V

#### (5) CAPACITANCE VALUE

2 significant digits+number of zeros  
The 3rd digit signifies the multiplying factor, and letter R is decimal point  
Example: 103 =  $10 \times 10^3 = 10,000 \text{ pF} = 10 \text{ nF}$

## NOTE

I. Tolerance  $\pm 5\%$  is not available for full product range, please contact local sales force before ordering

## CONSTRUCTION

The capacitor consists of a rectangular block of ceramic dielectric in which a number of interleaved metal electrodes are contained. This structure gives rise to a high capacitance per unit volume.

The inner electrodes are connected to the two end terminations and finally covered with a layer of plated tin (NiSn). The terminations are lead-free. A cross section of the structure is shown in Fig.1.




Fig. 1 Surface mounted multilayer ceramic capacitor construction

## DIMENSION

Table I For outlines see fig. 2

| TYPE | L <sub>1</sub> (mm)      | W (mm)                    | T (MM)                   | L <sub>2</sub> / L <sub>3</sub> (mm) |      | L <sub>4</sub> (mm) |
|------|--------------------------|---------------------------|--------------------------|--------------------------------------|------|---------------------|
|      |                          |                           |                          | min.                                 | max. | min.                |
| 0201 | 0.6 ±0.03                | 0.3 ±0.03                 | Refer to<br>table 2 to 4 | 0.10                                 | 0.20 | 0.20                |
| 0402 | 1.0 ±0.05                | 0.5 ±0.05                 |                          | 0.15                                 | 0.30 | 0.40                |
| 0603 | 1.6 ±0.10 <sup>(1)</sup> | 0.8 ±0.10 <sup>(1)</sup>  |                          | 0.20                                 | 0.60 | 0.40                |
|      | 1.6 ±0.15 <sup>(2)</sup> | 0.8 ±0.15 <sup>(2)</sup>  |                          |                                      |      |                     |
| 0805 | 2.0 ±0.10 <sup>(1)</sup> | 1.25 ±0.10 <sup>(1)</sup> |                          | 0.25                                 | 0.75 | 0.55                |
|      | 2.0 ±0.20 <sup>(2)</sup> | 1.25 ±0.20 <sup>(2)</sup> |                          |                                      |      |                     |
| 1206 | 3.2 ±0.15 <sup>(1)</sup> | 1.6 ±0.15 <sup>(1)</sup>  |                          | 0.25                                 | 0.75 | 1.40                |
|      | 3.2 ±0.30 <sup>(2)</sup> | 1.6 ±0.20 <sup>(2)</sup>  |                          |                                      |      |                     |
| 1210 | 3.2 ±0.20 <sup>(1)</sup> | 2.5 ±0.20 <sup>(1)</sup>  |                          | 0.25                                 | 0.75 | 1.40                |
|      | 3.2 ±0.40 <sup>(2)</sup> | 2.5 ±0.30 <sup>(2)</sup>  |                          |                                      |      |                     |
| 1812 | 4.5 ±0.20 <sup>(1)</sup> | 3.2 ±0.20 <sup>(1)</sup>  |                          | 0.25                                 | 0.75 | 2.20                |
|      | 4.5 ±0.40 <sup>(2)</sup> | 3.2 ±0.40 <sup>(2)</sup>  |                          |                                      |      |                     |

## NOTE

1. Dimension for size 0603, C < 2.2 μF; 0805 to 1812, C ≤ 100nF
2. Dimension for size 0603, C = 1 μF; 50V; 0805 to 1812, C > 100 nF

## OUTLINES

For dimension see Table I




Fig. 2 Surface mounted multilayer ceramic capacitor dimension

**CAPACITANCE RANGE & THICKNESS FOR X7R**

Table 2 Sizes from 0201 to 0402

| CAP.   | 0201     |          |          |          |          | 0402     |          |          |          |          |
|--------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
|        | 6.3 V    | 10 V     | 16 V     | 25 V     | 50 V     | 6.3 V    | 10 V     | 16 V     | 25 V     | 50 V     |
| 100 pF |          |          |          |          |          |          |          |          |          |          |
| 150 pF |          |          |          |          |          |          |          |          |          |          |
| 220 pF |          |          |          |          |          |          |          |          |          |          |
| 330 pF |          |          |          |          | 0.3±0.03 |          |          |          |          |          |
| 470 pF |          |          |          |          |          |          |          |          |          |          |
| 680 pF |          |          |          |          |          |          |          |          |          |          |
| 1.0 nF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 |          |          |          |          |          |          |
| 1.5 nF |          |          |          |          |          |          |          |          |          |          |
| 2.2 nF |          |          |          |          |          |          |          |          |          | 0.5±0.05 |
| 3.3 nF |          |          |          |          |          | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |          |
| 4.7 nF |          |          |          |          |          |          |          |          |          |          |
| 6.8 nF |          |          |          |          |          |          |          |          |          |          |
| 10 nF  |          |          |          |          |          |          |          |          |          |          |
| 15 nF  |          |          |          |          |          |          |          |          |          |          |
| 22 nF  |          |          |          |          |          |          |          |          |          |          |
| 33 nF  |          |          |          |          |          |          |          |          |          |          |
| 47 nF  |          |          |          |          |          |          |          |          |          |          |
| 68 nF  |          |          |          |          |          |          |          |          |          |          |
| 100 nF |          |          |          |          |          |          |          |          |          | 0.5±0.05 |
| 150 nF |          |          |          |          |          |          |          |          |          |          |
| 220 nF |          |          |          |          |          | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |          |          |
| 330 nF |          |          |          |          |          |          |          |          |          |          |
| 470 nF |          |          |          |          |          | 0.5±0.05 | 0.5±0.05 |          |          |          |
| 680 nF |          |          |          |          |          |          |          |          |          |          |
| 1.0 µF |          |          |          |          |          | 0.5±0.05 |          |          |          |          |
| 2.2 µF |          |          |          |          |          |          |          |          |          |          |
| 4.7 µF |          |          |          |          |          |          |          |          |          |          |
| 10 µF  |          |          |          |          |          |          |          |          |          |          |
| 22 µF  |          |          |          |          |          |          |          |          |          |          |

**NOTE**

1. Values in shaded cells indicate thickness class in mm
2. Capacitance value of non E-6 series is on request
3. For product with 5% tolerance, please contact local sales force before ordering

**CAPACITANCE RANGE & THICKNESS FOR X7R**

Table 3 Sizes from 0603 to 0805

| CAP.   | 0603    |         |         |         |          | 0805     |          |          |          |          |
|--------|---------|---------|---------|---------|----------|----------|----------|----------|----------|----------|
|        | 6.3 V   | 10 V    | 16 V    | 25 V    | 50 V     | 6.3 V    | 10 V     | 16 V     | 25 V     | 50 V     |
| 100 pF |         |         |         |         |          |          |          |          |          |          |
| 150 pF |         |         |         |         |          |          |          |          |          |          |
| 220 pF |         |         |         |         |          |          |          |          |          |          |
| 330 pF |         |         |         |         |          |          |          |          |          |          |
| 470 pF |         |         |         |         |          |          |          |          |          |          |
| 680 pF |         |         |         |         |          |          |          |          |          |          |
| 1.0 nF |         |         |         |         |          |          |          |          |          |          |
| 1.5 nF |         |         |         |         |          |          |          |          |          |          |
| 2.2 nF |         |         |         |         |          | 0.6±0.1  | 0.6±0.1  | 0.6±0.1  | 0.6±0.1  | 0.6±0.1  |
| 3.3 nF |         |         |         |         |          |          |          |          |          |          |
| 4.7 nF |         |         |         |         | 0.8±0.1  |          |          |          |          |          |
| 6.8 nF |         |         |         |         |          |          |          |          |          |          |
| 10 nF  | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |          |          |          |          |          |          |
| 15 nF  |         |         |         |         |          |          |          |          |          |          |
| 22 nF  |         |         |         |         |          |          |          |          |          |          |
| 33 nF  |         |         |         |         |          |          |          |          |          |          |
| 47 nF  |         |         |         |         |          |          |          |          |          |          |
| 68 nF  |         |         |         |         |          | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 |
| 100 nF |         |         |         |         |          |          |          |          |          |          |
| 150 nF |         |         |         |         |          |          |          |          |          |          |
| 220 nF |         |         |         |         |          |          |          |          |          |          |
| 330 nF |         |         |         |         |          |          |          |          |          |          |
| 470 nF |         |         |         |         |          |          |          |          |          |          |
| 680 nF |         |         |         |         |          |          |          |          |          |          |
| 1.0 µF |         |         |         |         | 0.8±0.15 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 2.2 µF |         |         |         |         |          |          |          |          |          |          |
| 4.7 µF |         |         |         |         |          |          |          |          |          |          |
| 10 µF  |         |         |         |         |          |          |          |          |          |          |
| 22 µF  |         |         |         |         |          |          |          |          |          |          |

**NOTE**

1. Values in shaded cells indicate thickness class in mm
2. Capacitance value of non E-6 series is on request
3. For product with 5% tolerance, please contact local sales force before ordering

**CAPACITANCE RANGE & THICKNESS FOR X7R**

Table 4 Size 1206

| CAP.   | 1206     |          |          |          |         |                     |                     |         |
|--------|----------|----------|----------|----------|---------|---------------------|---------------------|---------|
|        | 6.3 V    | 10 V     | 16 V     | 25 V     | 50 V    |                     |                     |         |
| 100 pF | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 |          |         |                     |                     |         |
| 150 pF |          |          |          |          |         |                     |                     |         |
| 220 pF |          |          |          |          |         |                     |                     |         |
| 330 pF |          |          |          |          |         |                     |                     |         |
| 470 pF |          |          |          |          |         |                     |                     |         |
| 680 pF |          |          |          |          |         |                     |                     |         |
| 1.0 nF |          |          |          |          |         |                     |                     |         |
| 1.5 nF |          |          |          |          |         |                     |                     |         |
| 2.2 nF |          |          |          |          |         |                     |                     |         |
| 3.3 nF |          |          |          |          |         |                     |                     |         |
| 4.7 nF |          |          |          | 0.85±0.1 |         |                     |                     |         |
| 6.8 nF |          |          |          |          |         | 0.85±0.1            |                     |         |
| 10 nF  |          |          |          |          |         |                     |                     |         |
| 15 nF  |          |          |          |          |         |                     |                     |         |
| 22 nF  |          |          |          |          |         |                     |                     |         |
| 33 nF  |          |          |          |          |         |                     |                     |         |
| 47 nF  |          |          |          |          |         |                     |                     |         |
| 68 nF  |          |          |          |          |         |                     |                     |         |
| 100 nF |          |          |          |          |         |                     |                     |         |
| 150 nF |          |          |          |          |         |                     | 0.85±0.1 / 1.15±0.1 |         |
| 220 nF |          |          |          |          |         |                     |                     |         |
| 330 nF |          |          |          |          |         | 0.85±0.1 / 1.15±0.1 | 0.85±0.1            |         |
| 470 nF |          |          |          |          |         |                     | 0.85±0.1            | 1.0±0.1 |
| 680 nF |          |          |          |          |         |                     |                     |         |
| 1.0 µF | 1.15±0.1 | 1.15±0.1 | 1.15±0.1 | 1.15±0.1 | 1.6±0.2 |                     |                     |         |
| 2.2 µF |          |          |          |          |         |                     |                     |         |
| 4.7 µF |          |          | 1.6±0.2  | 1.6±0.2  |         |                     |                     |         |
| 10 µF  | 1.6±0.2  | 1.6±0.2  |          |          |         |                     |                     |         |
| 22 µF  |          |          |          |          |         |                     |                     |         |
| 47 µF  |          |          |          |          |         |                     |                     |         |

**NOTE**

1. Values in shaded cells indicate thickness class in mm
2. Capacitance value of non E-6 series is on request
3. For product with 5% tolerance, please contact local sales force before ordering
4. Please contact local sales force for special ordering code before ordering

**CAPACITANCE RANGE & THICKNESS FOR X7R**

Table 5 Sizes from 1210 to 1812

| CAP.   | 1210<br>6.3 V | 10 V     | 16 V     | 25 V     | 50 V     | 1812<br>50 V |
|--------|---------------|----------|----------|----------|----------|--------------|
| 100 pF |               |          |          |          |          |              |
| 150 pF |               |          |          |          |          |              |
| 220 pF |               |          |          |          |          |              |
| 330 pF |               |          |          |          |          |              |
| 470 pF |               |          |          |          |          |              |
| 680 pF |               |          |          |          |          |              |
| 1.0 nF |               |          |          |          |          |              |
| 1.5 nF |               |          |          |          |          |              |
| 2.2 nF |               |          |          |          |          |              |
| 3.3 nF |               |          |          |          |          |              |
| 4.7 nF |               |          |          |          |          |              |
| 6.8 nF |               |          |          |          |          |              |
| 10 nF  |               |          |          |          |          |              |
| 15 nF  |               |          |          |          | 0.85±0.1 | 0.85±0.1     |
| 22 nF  | 0.85±0.1      | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 |          |              |
| 33 nF  |               |          |          |          |          |              |
| 47 nF  |               |          |          |          |          |              |
| 68 nF  |               |          |          |          |          |              |
| 100 nF |               |          |          |          |          |              |
| 150 nF |               |          |          |          |          |              |
| 220 nF |               |          |          |          | 1.15±0.1 | 1.15±0.1     |
| 330 nF |               |          |          |          |          |              |
| 470 nF | 1.15±0.1      | 1.15±0.1 | 1.15±0.1 | 1.15±0.1 |          |              |
| 680 nF |               |          |          |          | 1.25±0.2 |              |
| 1.0 µF | 1.25±0.2      | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |          | 1.6±0.2      |
| 2.2 µF |               |          |          |          | 1.9±0.2  |              |
| 4.7 µF | 1.9±0.2       | 1.9±0.2  | 1.9±0.2  | 1.9±0.2  |          |              |
| 10 µF  |               |          |          |          | 2.5±0.3  |              |
| 22 µF  |               |          | 2.5±0.2  | 2.5±0.2  |          |              |
| 47 µF  | 2.5±0.2       | 2.5±0.2  |          |          |          |              |

**NOTE**

1. Values in shaded cells indicate thickness class in mm
2. Capacitance value of non E-6 series is on request
3. For product with 5% tolerance, please contact local sales force before ordering
4. Please contact local sales force for special ordering code before ordering

**THICKNESS CLASSES AND PACKING QUANTITY**

Table 6

| SIZE CODE | THICKNESS CLASSIFICATION | TAPE WIDTH<br>QUANTITY PER REEL | Ø180 MM / 7 INCH |                | Ø330 MM / 13 INCH |         | QUANTITY<br>PER BULK CASE |
|-----------|--------------------------|---------------------------------|------------------|----------------|-------------------|---------|---------------------------|
|           |                          |                                 | Paper            | Blister        | Paper             | Blister |                           |
| 0201      | 0.3 ±0.03 mm             | 8 mm                            | 15,000           | ---            | 50,000            | ---     | ---                       |
| 0402      | 0.5 ±0.05 mm             | 8 mm                            | 10,000           | ---            | 50,000            | ---     | 50,000                    |
| 0603      | 0.8 ±0.1 mm              | 8 mm                            | 4,000            | ---            | 15,000            | ---     | 15,000                    |
| 0805      | 0.6 ±0.1 mm              | 8 mm                            | 4,000            | ---            | 20,000            | ---     | 10,000                    |
|           | 0.85 ±0.1 mm             | 8 mm                            | 4,000            | ---            | 15,000            | ---     | 8,000                     |
|           | 1.25 ±0.2 mm             | 8 mm                            | ---              | 3,000          | ---               | 10,000  | 5,000                     |
| 1206      | 0.6 ±0.1 mm              | 8 mm                            | 4,000            | ---            | 20,000            | ---     | ---                       |
|           | 0.85 ±0.1 mm             | 8 mm                            | 4,000            | ---            | 15,000            | ---     | ---                       |
|           | 1.00 / 1.15 ±0.1 mm      | 8 mm                            | ---              | 3,000          | ---               | 10,000  | ---                       |
|           | 1.25 ±0.2 mm             | 8 mm                            | ---              | 3,000          | ---               | 10,000  | ---                       |
|           | 1.6 ±0.15 mm             | 8 mm                            | ---              | 2,500          | ---               | 10,000  | ---                       |
|           | 1.6 ±0.2 mm              | 8 mm                            | ---              | 2,000          | ---               | 8,000   | ---                       |
| 1210      | 0.6 / 0.7 ±0.1 mm        | 8 mm                            | ---              | 4,000          | ---               | 15,000  | ---                       |
|           | 0.85 ±0.1 mm             | 8 mm                            | ---              | 4,000          | ---               | 10,000  | ---                       |
|           | 1.15 ±0.1 mm             | 8 mm                            | ---              | 3,000          | ---               | 10,000  | ---                       |
|           | 1.15 ±0.15 mm            | 8 mm                            | ---              | 3,000          | ---               | 10,000  | ---                       |
|           | 1.25 ±0.2 mm             | 8 mm                            | ---              | 3,000          | ---               | ---     | ---                       |
|           | 1.5 ±0.1 mm              | 8 mm                            | ---              | 2,000          | ---               | ---     | ---                       |
|           | 1.6 / 1.9 ±0.2 mm        | 8 mm                            | ---              | 2,000          | ---               | ---     | ---                       |
|           | 2.0 ±0.2 mm              | 8 mm                            | ---              | 2,000<br>1,000 | ---               | ---     | ---                       |
| 1808      | 2.5 ±0.2 mm              | 8 mm                            | ---              | 1,000<br>500   | ---               | ---     | ---                       |
|           | 1.15 ±0.15 mm            | 12 mm                           | ---              | 3,000          | ---               | ---     | ---                       |
|           | 1.25 ±0.2 mm             | 12 mm                           | ---              | 3,000          | ---               | ---     | ---                       |
|           | 1.35 ±0.15 mm            | 12 mm                           | ---              | 2,000          | ---               | ---     | ---                       |
|           | 1.5 ±0.1 mm              | 12 mm                           | ---              | 2,000          | ---               | ---     | ---                       |
|           | 1.6 ±0.2 mm              | 12 mm                           | ---              | 2,000          | ---               | 8,000   | ---                       |
| 1812      | 2.0 ±0.2 mm              | 12 mm                           | ---              | 2,000          | ---               | ---     | ---                       |
|           | 0.6 / 0.85 ±0.1 mm       | 12 mm                           | ---              | 2,000          | ---               | ---     | ---                       |
|           | 1.15 ±0.1 mm             | 12 mm                           | ---              | 1,000          | ---               | ---     | ---                       |
|           | 1.25 ±0.2 mm             | 12 mm                           | ---              | 1,000          | ---               | ---     | ---                       |
|           | 1.5 ±0.1 mm              | 12 mm                           | ---              | 1,000          | ---               | ---     | ---                       |
|           | 1.6 ±0.2 mm              | 12 mm                           | ---              | 1,000          | ---               | ---     | ---                       |
|           | 2.0 ±0.2 mm              | 12 mm                           | ---              | 1,000          | ---               | ---     | ---                       |
|           | 2.5 ±0.2 mm              | 12 mm                           | ---              | 500            | ---               | ---     | ---                       |

**ELECTRICAL CHARACTERISTICS****X7R DIELECTRIC CAPACITORS; NISN TERMINATIONS**

Unless otherwise specified, all test and measurements shall be made under standard atmospheric conditions for testing as given in 5.3 of IEC 60068-1:

- Temperature: 15 °C to 35 °C
- Relative humidity: 25% to 75%
- Air pressure: 86 kPa to 106 kPa

Before the measurements are made, the capacitor shall be stored at the measuring temperature for a time sufficient to allow the entire capacitor to reach this temperature.

The period as prescribed for recovery at the end of a test is normally sufficient for this purpose.

Table 7

| DESCRIPTION                                                                                       | VALUE                                                                                                                                                                                                                                              |                                                                                                                                                                                                 |                                                                                                                                                                                                    |                                                                           |
|---------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|
| Capacitance range                                                                                 | 100 pF to 47 $\mu$ F                                                                                                                                                                                                                               |                                                                                                                                                                                                 |                                                                                                                                                                                                    |                                                                           |
| Capacitance tolerance                                                                             | $\pm 5\%$ , $\pm 10\%$ , $\pm 20\%$                                                                                                                                                                                                                |                                                                                                                                                                                                 |                                                                                                                                                                                                    |                                                                           |
| Dissipation factor (D.F.)                                                                         |                                                                                                                                                                                                                                                    |                                                                                                                                                                                                 |                                                                                                                                                                                                    |                                                                           |
| $\leq 10$ V                                                                                       | 47pF $\leq$ 0201 $\leq$ 10nF<br>150pF $\leq$ 0805 $\leq$ 2.2 $\mu$ F<br>Exception: 220nF $\leq$ 0402 $\leq$ 470nF<br>1206 $\geq$ 4.7 $\mu$ F<br>0402 = 1 $\mu$ F                                                                                   | 100pF $\leq$ 0402 $\leq$ 100nF<br>220 pF $\leq$ 1206 $\leq$ 2.2 $\mu$ F<br>0603 = 2.2 $\mu$ F<br>4.7 $\mu$ F $\leq$ 1210 $\leq$ 47 $\mu$ F                                                      | 100pF $\leq$ 0603 $\leq$ 1 $\mu$ F<br>2.2nF $\leq$ 1210 $\leq$ 2.2 $\mu$ F<br>0805 $\geq$ 4.7 $\mu$ F<br>0201 $\geq$ 12 nF                                                                         | $\leq 5\%$<br>$\leq 10\%$<br>$\leq 12.5\%$                                |
| 16 V                                                                                              | 47 pF $\leq$ 0201 $\leq$ 1.2nF<br>150 pF $\leq$ 0805 $\leq$ 560nF<br>Exception: 1.5 nF $\leq$ 0201 $\leq$ 10nF<br>1206 = 2.2 $\mu$ F<br>0402 = 220 nF<br>1210 = 22 $\mu$ F                                                                         | 100 pF $\leq$ 0402 $\leq$ 22nF<br>220pF $\leq$ 1206 $\leq$ 1 $\mu$ F<br>27nF $\leq$ 0402 $\leq$ 100nF<br>2.2 $\mu$ F $\leq$ 1210 $\leq$ 10 $\mu$ F<br>4.7 $\mu$ F $\leq$ 0805 $\leq$ 10 $\mu$ F | 100 pF $\leq$ 0603 $\leq$ 470nF<br>2.2nF $\leq$ 1210 $\leq$ 1 $\mu$ F<br>680 nF $\leq$ 0805 $\leq$ 2.2 $\mu$ F<br>470 nF $\leq$ 0603 $\leq$ 1 $\mu$ F<br>4.7 $\mu$ F $\leq$ 1206 $\leq$ 10 $\mu$ F | $\leq 3.5\%$<br>$\leq 5\%$<br>$\leq 10\%$                                 |
| 25 V                                                                                              | 47pF $\leq$ 0201 $\leq$ 470pF<br>150pF $\leq$ 0805 $\leq$ 180nF<br>Exception: 12 nF $\leq$ 0402 $\leq$ 47nF<br>1206 = 1 $\mu$ F<br>560pF $\leq$ 0201 $\leq$ 10nF<br>1206 = 2.2 $\mu$ F<br>270nF $\leq$ 0603 $\leq$ 1 $\mu$ F<br>1210 $\geq$ 4.7 uF | 100pF $\leq$ 0402 $\leq$ 10nF<br>220pF $\leq$ 1206 $\leq$ 680nF<br>47nF $\leq$ 0603 $\leq$ 220nF<br>56 nF $\leq$ 0402 $\leq$ 100 nF<br>1210=2.2 $\mu$ F<br>2.2uF $\leq$ 0805 $\leq$ 4.7uF       | 100pF $\leq$ 0603 $\leq$ 39nF<br>2.2nF $\leq$ 1210 $\leq$ 1 $\mu$ F<br>220nF $\leq$ 0805 $\leq$ 560 nF<br>680nF $\leq$ 0805 $\leq$ 1 $\mu$ F<br>1206 $\geq$ 4.7uF                                  | $\leq 2.5\%$<br>$\leq 3.5\%$<br>$\leq 5\%$<br>$\leq 10\%$                 |
| $\geq 50$ V                                                                                       | Exception: 0201 $\geq$ 47pF<br>0603 $\geq$ 47nF<br>0805=680 nF<br>0402=100nF<br>1206 $\geq$ 2.2 $\mu$ F                                                                                                                                            | 1 $\mu$ F $\geq$ 1206 $\geq$ 680nF<br>47nF $\geq$ 0402 $\geq$ 12 nF<br>0603 $\geq$ 1 $\mu$ F<br>1210 $\geq$ 2.2 $\mu$ F                                                                         | 470nF $\geq$ 0805 $\geq$ 330 nF<br>0805 $\geq$ 1 $\mu$ F                                                                                                                                           | $\leq 2.5\%$<br>$\leq 3.5\%$<br>$\leq 3.0\%$<br>$\leq 5\%$<br>$\leq 10\%$ |
| Insulation resistance after 1 minute at $U_r$ (DC)                                                | $R_{ins} \geq 10$ G $\Omega$ or $R_{ins} \times C_r \geq 500(100)$ seconds whichever is less                                                                                                                                                       |                                                                                                                                                                                                 |                                                                                                                                                                                                    |                                                                           |
| Maximum capacitance change as a function of temperature (temperature characteristic/coefficient): | $\pm 15\%$                                                                                                                                                                                                                                         |                                                                                                                                                                                                 |                                                                                                                                                                                                    |                                                                           |
| Operating temperature range:                                                                      | $-55$ °C to $+125$ °C                                                                                                                                                                                                                              |                                                                                                                                                                                                 |                                                                                                                                                                                                    |                                                                           |

**NOTE**

Capacitance tolerance  $\pm 5\%$  is not available for full product range, please contact local sales force before ordering




Fig. 3 Typical capacitance change as a function of temperature

Size 0201 10 nF / 16 V

Solid lines: Impedance / Dotted lines: ESR




Fig. 4 Impedance ESR vs. frequency characteristics for multilayer chip capacitors

Size 0402 100 nF / 16 V

Solid lines: Impedance / Dotted lines: ESR




Fig. 5 Impedance ESR vs. frequency characteristics for multilayer chip capacitors

Size 0603 1  $\mu$ F / 16 V

Solid lines: Impedance / Dotted lines: ESR




Fig. 6 Impedance ESR vs. frequency characteristics for multilayer chip capacitors

 Size 0805 1  $\mu$ F / 16 V

Solid lines: Impedance / Dotted lines: ESR




Fig. 7 Impedance ESR vs. frequency characteristics for multilayer chip capacitors

Size I206 1  $\mu$ F / 25 V

Solid lines: Impedance / Dotted lines: ESR




Fig. 8 Impedance ESR vs. frequency characteristics for multilayer chip capacitors

 Size I206 10  $\mu$ F / 10 V

Solid lines: Impedance / Dotted lines: ESR




Fig. 9 Impedance ESR vs. frequency characteristics for multilayer chip capacitors

**SOLDERING RECOMMENDATION**

Table 8

| SOLDERING METHOD | SIZE 0402     | 0603          | 0805          | 1206          | ≥ 1210      |
|------------------|---------------|---------------|---------------|---------------|-------------|
| Reflow           | ≥ 0.1 $\mu$ F | ≥ 1.0 $\mu$ F | ≥ 2.2 $\mu$ F | ≥ 4.7 $\mu$ F | Reflow only |
| Reflow/Wave      | < 0.1 $\mu$ F | < 1.0 $\mu$ F | < 2.2 $\mu$ F | < 4.7 $\mu$ F | ---         |

**TESTS AND REQUIREMENTS**

Table 9 Test procedures and requirements

| TEST                                     | TEST METHOD     | PROCEDURE                                                                                                                                                                                                                                                                                                                                            | REQUIREMENTS                     |
|------------------------------------------|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| Mounting                                 | IEC 60384-21/22 | 4.3 The capacitors may be mounted on printed-circuit boards or ceramic substrates                                                                                                                                                                                                                                                                    | No visible damage                |
| Visual Inspection and Dimension Check    | 4.4             | Any applicable method using $\times 10$ magnification                                                                                                                                                                                                                                                                                                | In accordance with specification |
| Capacitance <sup>(1)</sup>               | 4.5.1           | Class 2:<br>At 20 °C, 24 hrs after annealing<br>$f = 1$ KHz for $C \leq 10 \mu$ F, rated voltage $> 6.3$ V, measuring at voltage $1 V_{rms}$ at 20 °C<br>$f = 1$ KHz, for $C \leq 10 \mu$ F, rated voltage $\leq 6.3$ V, measuring at voltage $0.5 V_{rms}$ at 20 °C<br>$f = 120$ Hz for $C > 10 \mu$ F, measuring at voltage $0.5 V_{rms}$ at 20 °C | Within specified tolerance       |
| Dissipation Factor (D.F.) <sup>(1)</sup> | 4.5.2           | Class 2:<br>At 20 °C, 24 hrs after annealing<br>$f = 1$ KHz for $C \leq 10 \mu$ F, rated voltage $> 6.3$ V, measuring at voltage $1 V_{rms}$ at 20 °C<br>$f = 1$ KHz, for $C \leq 10 \mu$ F, rated voltage $\leq 6.3$ V, measuring at voltage $0.5 V_{rms}$ at 20 °C<br>$f = 120$ Hz for $C > 10 \mu$ F, measuring at voltage $0.5 V_{rms}$ at 20 °C | In accordance with specification |
| Insulation Resistance                    | 4.5.3           | At $U_r$ (DC) for 1 minute                                                                                                                                                                                                                                                                                                                           | In accordance with specification |

**NOTE:**

I. For individual product specification, please contact local sales.

| TEST                       | TEST METHOD           | PROCEDURE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | REQUIREMENTS                                                                                                                                                                                        |                 |   |      |   |                       |   |      |   |                       |   |      |                                                                                                                                                                                                                                                           |
|----------------------------|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---|------|---|-----------------------|---|------|---|-----------------------|---|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Temperature Characteristic | IEC 60384-21/224.6    | <p>Capacitance shall be measured by the steps shown in the following table.</p> <p>The capacitance change should be measured after 5 min at each specified temperature stage.</p> <table><tr><th>Step</th><th>Temperature(°C)</th></tr><tr><td>a</td><td>25±2</td></tr><tr><td>b</td><td>Lower temperature±3°C</td></tr><tr><td>c</td><td>25±2</td></tr><tr><td>d</td><td>Upper Temperature±2°C</td></tr><tr><td>e</td><td>25±2</td></tr></table> <p>(1) Class I</p> <p>Temperature Coefficient shall be calculated from the formula as below</p> $\text{Temp. Coefficient} = \frac{C2 - C1}{C1 \times \Delta T} \times 10^6 \text{ [ppm/°C]}$ <p>C1: Capacitance at step c</p> <p>C2: Capacitance at 125°C</p> <p>ΔT: 100°C(=125°C-25°C)</p> <p>(2) Class II</p> <p>Capacitance Change shall be calculated from the formula as below</p> $\Delta C = \frac{C2 - C1}{C1} \times 100\%$ <p>C1: Capacitance at step c</p> <p>C2: Capacitance at step b or d</p> | Step                                                                                                                                                                                                | Temperature(°C) | a | 25±2 | b | Lower temperature±3°C | c | 25±2 | d | Upper Temperature±2°C | e | 25±2 | <p>&lt;General purpose series&gt;</p> <p>Class I:</p> <p>Δ C/C: ±30ppm</p> <p>Class2:</p> <p>X7R: Δ C/C: ±15%</p> <p>Y5V: Δ C/C: 22~-82%</p> <p>&lt;High Capacitance series&gt;</p> <p>Class2:</p> <p>X7R/X5R: Δ C/C: ±15%</p> <p>Y5V: Δ C/C: 22~-82%</p> |
| Step                       | Temperature(°C)       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                     |                 |   |      |   |                       |   |      |   |                       |   |      |                                                                                                                                                                                                                                                           |
| a                          | 25±2                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                     |                 |   |      |   |                       |   |      |   |                       |   |      |                                                                                                                                                                                                                                                           |
| b                          | Lower temperature±3°C |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                     |                 |   |      |   |                       |   |      |   |                       |   |      |                                                                                                                                                                                                                                                           |
| c                          | 25±2                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                     |                 |   |      |   |                       |   |      |   |                       |   |      |                                                                                                                                                                                                                                                           |
| d                          | Upper Temperature±2°C |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                     |                 |   |      |   |                       |   |      |   |                       |   |      |                                                                                                                                                                                                                                                           |
| e                          | 25±2                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                     |                 |   |      |   |                       |   |      |   |                       |   |      |                                                                                                                                                                                                                                                           |
| Adhesion                   | 4.7                   | A force applied for 10 seconds to the line joining the terminations and in a plane parallel to the substrate                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Force<br>size ≥ 0603: 5N<br>size = 0402: 2.5N<br>size = 0201: 1N                                                                                                                                    |                 |   |      |   |                       |   |      |   |                       |   |      |                                                                                                                                                                                                                                                           |
| Bond Strength              | 4.8                   | <p>Mounting in accordance with IEC 60384-22 paragraph 4.3</p> <p>Conditions: bending 1 mm at a rate of 1 mm/s, radius jig 340 mm</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | <p>No visible damage</p> <hr/> <p>&lt;General Purpose series&gt;</p> <p>ΔC/C</p> <p>Class2:</p> <p>X7R: ±10%</p> <p>&lt;High Capacitance series&gt;</p> <p>ΔC/C</p> <p>Class2:</p> <p>X7R: ±10%</p> |                 |   |      |   |                       |   |      |   |                       |   |      |                                                                                                                                                                                                                                                           |

| TEST                         | TEST METHOD          | PROCEDURE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | REQUIREMENTS                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|------------------------------|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Resistance to Soldering Heat | 4.9                  | <p>Precondition: 150 +0/-10 °C for 1 hour, then keep for 24 ±1 hours at room temperature</p> <p>Preheating: for size ≤ 1206: 120 °C to 150 °C for 1 minute</p> <p>Preheating: for size &gt;1206: 100 °C to 120 °C for 1 minute and 170 °C to 200 °C for 1 minute</p> <p>Solder bath temperature: 260 ±5 °C</p> <p>Dipping time: 10 ±0.5 seconds</p> <p>Recovery time: 24 ±2 hours</p>                                                                                                                                                                                                                                                             | <p>Dissolution of the end face plating shall not exceed 25% of the length of the edge concerned</p> <hr/> <p>&lt;General Purpose series&gt;<br/> <math>\Delta C/C</math><br/>           Class2:<br/>           X7R: ±10%</p> <hr/> <p>&lt;High Capacitance series&gt;<br/> <math>\Delta C/C</math><br/>           Class2:<br/>           X7R: ±10%</p> <hr/> <p>D.F. within initial specified value<br/> <math>R_{ins}</math> within initial specified value</p> |
| Solderability                | IEC 60384-21/22 4.10 | <p>Preheated to a temperature of 80 °C to 140 °C and maintained for 30 seconds to 60 seconds.</p> <p>Test conditions for lead containing solder alloy<br/>           Temperature: 235 ±5 °C<br/>           Dipping time: 2 ±0.2 seconds<br/>           Depth of immersion: 10 mm<br/>           Alloy Composition: 60/40 Sn/Pb<br/>           Number of immersions: 1</p> <p>Test conditions for lead-free containing solder alloy<br/>           Temperature: 245 ±5 °C<br/>           Dipping time: 3 ±0.3 seconds<br/>           Depth of immersion: 10 mm<br/>           Alloy Composition: SAC305<br/>           Number of immersions: 1</p> | <p>The solder should cover over 95% of the critical area of each termination</p>                                                                                                                                                                                                                                                                                                                                                                                 |
| Rapid Change of Temperature  | 4.11                 | <p>Preconditioning:<br/>           150 +0/-10 °C for 1 hour, then keep for 24 ±1 hours at room temperature</p> <p>5 cycles with following detail:<br/>           30 minutes at lower category temperature<br/>           30 minutes at upper category temperature</p> <p>Recovery time 24 ±2 hours</p>                                                                                                                                                                                                                                                                                                                                            | <p>No visual damage</p> <hr/> <p>&lt;General Purpose series&gt;<br/> <math>\Delta C/C</math><br/>           Class2:<br/>           X7R: ±15%</p> <hr/> <p>&lt;High Capacitance series&gt;<br/> <math>\Delta C/C</math><br/>           Class2:<br/>           X7R: ±15%</p> <hr/> <p>D.F. meet initial specified value<br/> <math>R_{ins}</math> meet initial specified value</p>                                                                                 |

| TEST                         | TEST METHOD         | PROCEDURE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | REQUIREMENTS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------------------------------|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Damp Heat<br>with $U_r$ Load | IEC 60384-<br>21/22 | 4.13<br>1. Preconditioning, class 2 only:<br>150 $\pm$ 10 $^{\circ}$ C / 1 hour, then keep for<br>24 $\pm$ 1 hour at room temp<br>2. Initial measure:<br>Spec: refer to initial spec C, D, IR<br>3. Damp heat test:<br>500 $\pm$ 12 hours at 40 $\pm$ 2 $^{\circ}$ C;<br>90 to 95% R.H. 1.0 $U_r$ applied<br>4. Recovery:<br>Class 2: 24 $\pm$ 2 hours<br>5. Final measure: C, D, IR<br><br>P.S. If the capacitance value is less than the<br>minimum value permitted, then after the other<br>measurements have been made the capacitor<br>shall be preconditioned according to "IEC<br>60384 4.1" and then the requirement shall be<br>met. | No visual damage after recovery<br><br><General Purpose series><br>$\Delta C/C$<br>Class2:<br>X7R: $\pm$ 15%<br>D.F.<br>Class2:<br>X7R: $\leq$ 16V: $\leq$ 7%<br>$\geq$ 25V: $\leq$ 5%<br>$R_{ins}$<br>Class2:<br>X7R: $\geq$ 500 M $\Omega$ or $R_{ins} \times C_r \geq$ 25s<br>whichever is less<br><br><High Capacitance series( $\geq$ 1 $\mu$ F) and<br>CC0402xRX7R9BB104><br>$\Delta C/C$<br>Class2:<br>X7R: $\pm$ 20%<br>D.F.<br>Class2:<br>X7R: 2 x initial value max<br>$R_{ins}$<br>Class2:<br>X7R: 500 M $\Omega$ or $R_{ins} \times C_r \geq$ 25(5)s<br>whichever is less |

| TEST          | TEST METHOD          | PROCEDURE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | REQUIREMENTS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Endurance     | IEC 60384-21/22 4.14 | <p>1. Preconditioning, class 2 only:<br/>150 +0/-10 °C /1 hour, then keep for<br/>24 ±1 hour at room temp</p> <p>2. Initial measure:<br/>Spec: refer to initial spec C, D, IR</p> <p>3. Endurance test:<br/>Temperature: X7R: 125 °C<br/>Specified stress voltage applied for 1,000 hours:<br/>Applied 2.0 × U<sub>r</sub> for general products<br/>Applied 1.5(1.0) × U<sub>r</sub> for high cap. products</p> <p>4. Recovery time: 24 ±2 hours</p> <p>5. Final measure: C, D, IR</p> <p>P.S. If the capacitance value is less than the minimum value permitted, then after the other measurements have been made the capacitor shall be preconditioned according to "IEC 60384 4.1" and then the requirement shall be met.</p> | <p>No visual damage</p> <hr/> <p>&lt;General Purpose series&gt;<br/>ΔC/C<br/>Class2:<br/>X7R: ±15%<br/>D.F.<br/>Class2:<br/>X7R: ≤ 16V: ≤ 7%<br/>≥ 25V: ≤ 5%</p> <p>R<sub>ins</sub><br/>Class2:<br/>X7R: ≥ 1,000 MΩ or R<sub>ins</sub> × C<sub>r</sub> ≥ 50s<br/>whichever is less</p> <p>&lt;High Capacitance series(≥ 1 uF) and CC0402xRX7R9BB104&gt;<br/>ΔC/C<br/>Class 2:<br/>X7R: ±20%<br/>D.F.<br/>Class 2:<br/>X7R: 2 × initial value max</p> <p>R<sub>ins</sub><br/>Class 2:<br/>X7R: 1,000 MΩ or R<sub>ins</sub> × C<sub>r</sub> ≥ 50(10)s<br/>whichever is less</p> |
| Voltage Proof | IEC 60384-1 4.6      | <p>Specified stress voltage applied for 1~5 seconds</p> <p>U<sub>r</sub> ≤ 100 V: series applied 2.5 U<sub>r</sub></p> <p>Charge/Discharge current is less than 50 mA</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | No breakdown or flashover                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

**REVISION HISTORY**

| REVISION   | DATE          | CHANGE NOTIFICATION | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------------|---------------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version 12 | May 26, 2015  | -                   | - I210, 25V dissipation factor updated                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Version 11 | Jan. 06, 2015 | -                   | - 0402, 100nF, 50V Dissipation factor (D.F.) updated.                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Version 10 | Jul. 08, 2014 | -                   | - Dimension updated                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Version 9  | Aug. 19, 2013 | -                   | - Dimension updated                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Version 8  | Oct 13, 2011  | -                   | - Dimension updated                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Version 7  | Jan 13, 2011  | -                   | - Dimension updated                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Version 6  | Oct 13, 2010  | -                   | - Rated voltage of 0201 extend to 50 V<br>- Capacitance range of 0201 X7R 6.3V to 16V extend to 100 pF<br>- Capacitance range of 0805 X7R 10V extend to 10 µF<br>- Capacitance range of 0805 X7R 50V extend to 1 µF<br>- Capacitance range of 1210 X7R 10V extend to 22 µF<br>- Figures of impedance ESR updated                                                                                                                                                                                  |
| Version 5  | Jul 27, 2010  | -                   | - Dimension on 0603 and 1206 case size updated                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Version 4  | Apr 21, 2010  | -                   | - The statement of "Halogen Free" on the cover added<br>- Dimension updated                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Version 3  | Oct 26, 2009  | -                   | - Capacitance range of 0402 X7R 25 V extend to 100 nF                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Version 2  | May 11, 2009  | -                   | - Product range updated                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Version 1  | Apr 24, 2009  | -                   | - Ordering code updated                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Version 0  | Apr 15, 2009  | -                   | - New datasheet for general purpose and high capacitance X7R series with RoHS compliant<br>- Replace the "6.3V to 50V" part of pdf files: X7R_10V_9, X7R_16V-to-100V_9, X7R_16-to-500V_9, UP-X5R_X7R_HighCaps_6.3-to-25V_11, UY-X5R_X7R_HighCaps_6.3-to-25V_11<br>- Combine 0201 from pdf files: UP-NP0X5RX7RY5V_0201_6.3-to-50V_2 and UY-NP0X5RX7RY5V_0201_6.3-to-50V_2<br>- Define global part number<br>- Description of "Halogen Free compliant" added<br>- Test method and procedure updated |

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Yageo:

[CC1206KKX7R8BB334](#)