




A TURNED BRASS SINGLE NUT FIXING PANEL SOCKET
AVAILABLE IN NICKEL OR GOLD PLATED FINISH.
A CHOICE OF RED OR BLACK INSULATOR IS USEFUL
FOR IDENTIFICATION PURPOSES.
SINGLE NUT FIXING MAKES THESE ADAPTABLE SOCKETS
SUITABLE FOR STACKING ADJACENT TO ONE ANOTHER.
COLOUR ID RINGS ARE ALSO AVAILABLE, SUPPLIED IN
PACKS OF 50 PIECES



DIMENSIONS



COLOUR ID WASHER		MATERIAL
434-0000	WHITE	ACETAL
434-0100	BLACK	ACETAL
434-0500	RED	ACETAL

MATERIAL PROPERTIES	
HOUSING	BRASS
HOUSING PLATING	NICKEL PLATE OR GOLD FLASH
INSULATION	ACETAL, DELRIN 500P BK602
NUT & WASHER	BRASS
SOCKET CONTACT	BRASS 0.3mm THICK
SOCKET CONTACT PLATING	SILVER OR GOLD PLATE
NUT & WASHER PLATING	NICKEL PLATE OR GOLD FLASH
SOLDER TAG	BRASS
SOLDER TAG PLATING	SILVER OR GOLD PLATING
COLOURED WASHER	NORYL SE1, RED OR BLACK
ELECTRICAL PROPERTIES	
CURRENT	5A
VOLTAGE	50V
INSULATION RESISTANCE	100MΩ @ 500V - DC
TEMPERATURE	
ACETAL, DELRIN, 500P BK602	RTI 105°C CTI 600V UL94-HB CLTE -40°C TO 23°C 9.0E-5cm/cm °C
NORYL RESIN SE1	RTI 110°C CTI 400V UL95-V1 CLTE -40°C TO 40°C 8.0E-5cm/cm °C
PANEL FITTING	
PANEL THICKNESS	3mm MAXIMUM
MOUNTING HOLE	7.2Ø mm

PART NUMBER	COLOUR	PLATING
431-0100	BLACK	NICKEL
431-0500	RED	NICKEL
432-0100	BLACK	GOLD
432-0500	RED	GOLD

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Deltron:](#)

[432-0500](#)