



Product: [1334A](#)

Fieldbus, 1 Pr #18 Str TC, PO Ins, OS+TC Brd, PVC Jkt, CMG

[Request Sample](#)

Product Description

Fieldbus, 1 Pair 18AWG (7x26) Tinned Copper, PO Insulation, Overall Beldfoil®+Tinned Copper Braid(65%) Shield, Orange PVC Outer Jacket, CMG

Technical Specifications

Product Overview

| | |
|------------------------|--|
| Suitable Applications: | harsh environment digital and serial two-way communication, oil and gas extraction and refining sites, petrochemical, Profibus process automation or Foundation FieldBus process automation, extreme temperature environments, exposure to humidity/moisture, dust, and oil, remote locations long distance applications, etc. |
|------------------------|--|

Construction Details

| Conductor | | | | |
|-----------|-----------------|------|-----------|--------------------|
| Element | No. of Elements | Size | Stranding | Material |
| Pair(s) | 1 | 18 | 7x26 | TC - Tinned Copper |

| Insulation | |
|--------------------|---------------|
| Material | Color Code |
| PP - Polypropylene | Blue & Orange |

| Outer Shield | | |
|--------------|-------------------------|----------|
| Shield Type | Material | Coverage |
| Tape | Bi-Laminate (Alum+Poly) | 100% |
| Braid | Tinned Copper (TC) | 65% |

| Outer Jacket | | | |
|--------------------------|-------------------|--------------------|---------|
| Material | Nom. Thickness | Nom. Diameter | Ripcord |
| PVC - Polyvinyl Chloride | 0.065 in (1.7 mm) | 0.287 in (7.29 mm) | Yes |

Electrical Characteristics

| Electricals | | | | | |
|------------------------|----------------------------|---------------------------------|-------------------------------|------------------------|------------------------|
| Nom. Conductor DCR | Max. Capacitance Unbalance | Nom. Capacitance Cond-to-Shield | Nom. Characteristic Impedence | Nom. Velocity of Prop. | Max. Current |
| 7.2 Ohm/1000ft | 1.2 pF/ft (3.9 pF/m) | 45 pF/ft | 100 Ohm | 66% | 5.2 Amps per Conductor |
| Nom. Outer Shield DCR: | 3.8 Ohm/1000ft (12 Ohm/km) | | | | |

| High Frequency (Nominal/Typical) | |
|-----------------------------------|--|
| Nom. Insertion Loss (Attenuation) | |
| 0.069 dB/100ft | |

| High Frequency | |
|-----------------------------------|--|
| Max. Insertion Loss (Attenuation) | Max./Min. Input Impedance (unFitted) [Ohm] |
| 0.091 dB/100ft | 100 |

| Voltage | |
|-------------------|--|
| UL Voltage Rating | |
| 300 V RMS | |

Mechanical Characteristics

Temperature

| UL Temperature | Operating |
|----------------|-----------------|
| 90°C | -40°C to +105°C |

Bend Radius

| Stationary Min. | Installation Min. |
|-------------------|-------------------|
| 3.37 in (85.6 mm) | 3.37 in (85.6 mm) |

| | |
|--------------------|--------------------|
| Max. Pull Tension: | 44.8 lbs (20.3 kg) |
| Bulk Cable Weight: | 60 lbs/1000ft |

Standards and Compliance

| | |
|----------------------------------|---|
| Environmental Suitability: | Indoor, Outdoor, Sunlight Resistance, UV Resistance, Oil Resistance, Oil Resistance |
| Flammability / Reaction to Fire: | UL1685 FT4 Loading, 1202, IEC 60332-3-24 |
| CPR Compliance: | CPR Euroclass: Eca |
| NEC / UL Compliance: | Article 725, Article 727, Article 800, CMG, ITC, PLTC |
| CEC / C(UL) Compliance: | CMG |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance: | UKCA Mark |

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.566 Revision Date: 04-30-2024 |
|----------------------|--|

Part Numbers

Variants

| Item # | Color | Putup Type | Length | UPC | Footnote |
|---------------|-------------|------------|----------|--------------|----------|
| 1334A 0061000 | Blue, Light | Reel | 1,000 ft | 612825112143 | C |
| 1334A 0063280 | Blue, Light | Reel | 3,280 ft | 612825112150 | C |
| 1334A 0031000 | Orange | Reel | 1,000 ft | 612825112112 | C |
| 1334A 0033280 | Orange | Reel | 3,280 ft | 612825112136 | C |

© 2024 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Belden Wire & Cable:](#)

[1334A 0031000](#) [1334A 0061000](#) [1334A 0033280](#) [1334A 0031640](#)