



Product: [1829P](#)

Broadband Coax, Series 6, 18 AWG Solid BCCS, Foil + 60% AL Braid, Flamarrest® Jkt, CMP

Product Description

Broadband Coax, Series 6, 18 AWG Solid Bare Copper Covered Steel Conductor, FEP Insulation, Foil + 60% Aluminum Braid Shield, Flamarrest® Jacket, CMP

Technical Specifications

Product Overview

Suitable Applications:	Broadband, Cable Television (CATV), RF drop cable, Direct Broadcast Satellite (DBS), Over-The-Air (OTA) antennas
Suitable Applications:	Broadband, Cable Television (CATV), RF drop cable, Direct Broadcast Satellite (DBS), Over-The-Air (OTA) antennas

Construction Details

Series Type:	6
Series Type:	6

Conductor

Size	Stranding	Nom. Diameter	Material
18 AWG	Solid	0.040 in	BCCS - Bare Copper Covered Steel

Conductor

Size	Stranding	Nom. Diameter	Material
18 AWG	Solid	0.040 in	BCCS - Bare Copper Covered Steel

Insulation

Material	Nom. Insulation Diameter	Color Code
FEP - Fluorinated Ethylene Propylene (Foam)	0.170 in (4.32 mm)	White

Insulation

Material	Nom. Insulation Diameter	Color Code
FEP - Fluorinated Ethylene Propylene (Foam)	0.170 in (4.32 mm)	White

Outer Shield

Layer	Outer Shield Type	Material	Material Trade Name	Coverage
1	Tape	Tri-Laminate (Alum+Poly+Alum)	Duobond® II	100%
2	Braid	Aluminum		60%

Outer Shield

Layer	Outer Shield Type	Material	Material Trade Name	Coverage
1	Tape	Tri-Laminate (Alum+Poly+Alum)	Duobond® II	100%
2	Braid	Aluminum		60%

Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.235 in (5.97 mm)

Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.235 in (5.97 mm)

Overall Cable Diameter (Nominal):	0.235 in (5.97 mm)
Overall Cable Diameter (Nominal):	0.235 in (5.97 mm)

Electrical Characteristics

Return Loss (RL)

Frequency	Min. Structural Return Loss
5 - 2500 MHz	15 dB
2500 - 3000 MHz	10 dB

Return Loss (RL)

Frequency	Min. Structural Return Loss
5 - 2500 MHz	15 dB
2500 - 3000 MHz	10 dB

Attenuation

Frequency	Nom. Attenuation
1 MHz	0.3 dB/100ft
10 MHz	0.7 dB/100ft
50 MHz	1.6 dB/100ft
100 MHz	2.1 dB/100ft
200 MHz	2.9 dB/100ft
400 MHz	4.3 dB/100ft
700 MHz	6.1 dB/100ft
750 MHz	6.4 dB/100ft
900 MHz	7.1 dB/100ft
1000 MHz	7.6 dB/100ft
1450 MHz	9.6 dB/100ft
1800 MHz	11.0 dB/100ft
2250 MHz	12.7 dB/100ft
3000 MHz	15.1 dB/100ft

Attenuation

Frequency	Nom. Attenuation
1 MHz	0.3 dB/100ft
10 MHz	0.7 dB/100ft
50 MHz	1.6 dB/100ft
100 MHz	2.1 dB/100ft
200 MHz	2.9 dB/100ft
400 MHz	4.3 dB/100ft
700 MHz	6.1 dB/100ft
750 MHz	6.4 dB/100ft
900 MHz	7.1 dB/100ft
1000 MHz	7.6 dB/100ft
1450 MHz	9.6 dB/100ft
1800 MHz	11.0 dB/100ft
2250 MHz	12.7 dB/100ft
3000 MHz	15.1 dB/100ft

Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
28 Ohm/1000ft	9 Ohm/1000ft (30 Ohm/km)	16.3 pF/ft (53.5 pF/m)	75 Ohm	83%

Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
28 Ohm/1000ft	9 Ohm/1000ft (30 Ohm/km)	16.3 pF/ft (53.5 pF/m)	75 Ohm	83%

Voltage

UL Voltage Rating
300 V (CMP)

Voltage

UL Voltage Rating

300 V (CMP)

Mechanical Characteristics

Temperature

Operating
-20°C to +75°C

Temperature

Operating
-20°C to +75°C

Bend Radius

Installation Min.
2.4 in (61 mm)

Bend Radius

Installation Min.
2.4 in (61 mm)

Max. Pull Tension:	150 lbs (68 kg)
Max. Pull Tension:	150 lbs (68 kg)
Bulk Cable Weight:	25 lbs/1000ft
Bulk Cable Weight:	25 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor
Environmental Suitability:	Indoor - Plenum, Indoor
Sustainability:	CA Prop 65
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	NFPA 262
Flammability / Reaction to Fire:	NFPA 262
CEC / C(UL) Compliance:	CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	1829A
Non-Plenum Number:	1829A

History

Update and Revision:	Revision Number: 0.474 Revision Date: 04-29-2024
Update and Revision:	Revision Number: 0.474 Revision Date: 04-29-2024

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
1829P 010100	Black	Reel	100 ft	612825124078
1829P 010U250	Black	UnReel	250 ft	612825124054
1829P 010U500	Black	UnReel	500 ft	612825124061
1829P 010U1000	Black	UnReel	1,000 ft	612825124047
1829P 877100	Natural	Reel	100 ft	612825124115
1829P 877U250	Natural	UnReel	250 ft	612825124092
1829P 877U500	Natural	UnReel	500 ft	612825124108
1829P 8771000	Natural	Reel	1,000 ft	612825124122
1829P 877U1000	Natural	UnReel	1,000 ft	612825124085

Variants

Item #	Color	Putup Type	Length	UPC
1829P 010100	Black	Reel	100 ft	612825124078

1829P 010U250	Black	UnReel	250 ft	612825124054
1829P 010U500	Black	UnReel	500 ft	612825124061
1829P 010U1000	Black	UnReel	1,000 ft	612825124047
1829P 877100	Natural	Reel	100 ft	612825124115
1829P 877U250	Natural	UnReel	250 ft	612825124092
1829P 877U500	Natural	UnReel	500 ft	612825124108
1829P 8771000	Natural	Reel	1,000 ft	612825124122
1829P 877U1000	Natural	UnReel	1,000 ft	612825124085

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Belden Wire & Cable:](#)

[1829P 010U500](#) [1829P 877100](#) [1829P 877U250](#) [1829P 010U1000](#) [1829P 010100](#) [1829P 877U500](#) [1829P 010U250](#)