



Product: [2183P](#)

4K UHD Media Cable, 4 Pr #23, F/UTP Flamarrest® Jacket, CMP

Product Description
4 Pair 23 AWG Solid Bare Copper Conductors, FEP Insulation, F/UTP, Helical TC Drain, Ripcord, Flamarrest® Jacket, Plenum CMP-LP (0.6A)

Technical Specifications

Product Overview

Suitable Applications:	HDBaseT, Full 5-Play, 4K (UHD/DCI), POH, POE
Suitable Applications:	HDBaseT, Full 5-Play, 4K (UHD/DCI), POH, POE

Construction Details

Conductor

Size	Stranding	Material
23 AWG	Solid	BC - Bare Copper

Conductor

Size	Stranding	Material
23 AWG	Solid	BC - Bare Copper

Insulation

Material	Nom. Thickness	Color Code
FEP - Fluorinated Ethylene Propylene	0.010 in (0.25 mm)	Western Electric (Modified)

Insulation

Material	Nom. Thickness	Color Code
FEP - Fluorinated Ethylene Propylene	0.010 in (0.25 mm)	Western Electric (Modified)

Outer Shield

Shield Type	Material	Coverage	Drainwire Type	Notes
Tape	Bi-Laminate (Alum+Poly)	100%	26 AWG (Solid) TC	Two drain wires applied helically for added flexibility

Outer Shield

Shield Type	Material	Coverage	Drainwire Type	Notes
Tape	Bi-Laminate (Alum+Poly)	100%	26 AWG (Solid) TC	Two drain wires applied helically for added flexibility

Outer Jacket

Material	Nom. Thickness	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	0.018 in (0.46 mm)	0.270 in	Yes

Outer Jacket

Material	Nom. Thickness	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	0.018 in (0.46 mm)	0.270 in	Yes

Overall Cable Diameter (Nominal):	0.270 in
Overall Cable Diameter (Nominal):	0.270 in

Electrical Characteristics

Electricals

Nom. Conductor DCR	Nom. Velocity of Prop.	Max. Current
22.7 Ohm/1000ft	72%	3.1 Amps per Conductor at 25°C

Electricals

Nom. Conductor DCR	Nom. Velocity of Prop.	Max. Current
22.7 Ohm/1000ft	72%	3.1 Amps per Conductor at 25°C

Voltage

UL Voltage Rating
300 V

Voltage

UL Voltage Rating
300 V

Mechanical Characteristics

Temperature

UL Temperature	Operating	Installation	Storage
90°C	-20°C to +90°C	0°C To +75°C	-20°C to +75°C

Temperature

UL Temperature	Operating	Installation	Storage
90°C	-20°C to +90°C	0°C To +75°C	-20°C to +75°C

Bend Radius

Stationary Min.	Installation Min.
2.7 in (69 mm)	2.7 in

Bend Radius

Stationary Min.	Installation Min.
2.7 in (69 mm)	2.7 in

Max. Pull Tension:	45 lbs (20 kg)
Max. Pull Tension:	45 lbs (20 kg)
Bulk Cable Weight:	36 lbs/1000ft
Bulk Cable Weight:	36 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor, Outdoor
Environmental Suitability:	Indoor - Plenum, Indoor, Outdoor
Flammability / Reaction to Fire:	NFPA 262 (UL 910), FT6
Flammability / Reaction to Fire:	NFPA 262 (UL 910), FT6
CPR Compliance:	CPR Euroclass: Eca
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMP-LP (0.6A), CL3P
NEC / UL Compliance:	Article 800, CMP-LP (0.6A), CL3P
CEC / C(UL) Compliance:	CMP
CEC / C(UL) Compliance:	CMP
IEEE Compliance:	POE per 802.3af & POE+ 802.3at-2009
IEEE Compliance:	POE per 802.3af & POE+ 802.3at-2009
ISO/IEC Compliance:	11801 ed 2.2 (2011) Class D
ISO/IEC Compliance:	11801 ed 2.2 (2011) Class D
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2017-07-10
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2017-07-10
UK Regulation Compliance:	UKCA Mark
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	2183R

Non-Plenum Number:	2183R
--------------------	-------

Product Notes

Notes:	Values Above 100 MHz are for Engineering Information Only. Print Includes Descending Footage Markings.
Notes:	Values Above 100 MHz are for Engineering Information Only. Print Includes Descending Footage Markings.

History

Update and Revision:	Revision Number: 0.413 Revision Date: 12-22-2023
Update and Revision:	Revision Number: 0.413 Revision Date: 12-22-2023

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
2183P 010A250	Black	Reel-in-Box	250 ft	612825392958
2183P 0101000	Black	Reel	1,000 ft	612825391678
2183P 010A1000	Black	Reel-in-Box	1,000 ft	612825391708
2183P 010Z1000	Black	ReelTuff Box	1,000 ft	612825433231
2183P D15A1000	Blue	Reel-in-Box	1,000 ft	612825391685
2183P D15Z1000	Blue	ReelTuff Box	1,000 ft	612825433286
2183P 009A1000	White	Reel-in-Box	1,000 ft	612825391692
2183P 009Z1000	White	ReelTuff Box	1,000 ft	612825433187

Variants

Item #	Color	Putup Type	Length	UPC
2183P 010A250	Black	Reel-in-Box	250 ft	612825392958
2183P 0101000	Black	Reel	1,000 ft	612825391678
2183P 010A1000	Black	Reel-in-Box	1,000 ft	612825391708
2183P 010Z1000	Black	ReelTuff Box	1,000 ft	612825433231
2183P D15A1000	Blue	Reel-in-Box	1,000 ft	612825391685
2183P D15Z1000	Blue	ReelTuff Box	1,000 ft	612825433286
2183P 009A1000	White	Reel-in-Box	1,000 ft	612825391692
2183P 009Z1000	White	ReelTuff Box	1,000 ft	612825433187

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Belden Wire & Cable:](#)

[2183P 009A1000](#)