

🙀 Prod	luct: <u>38208</u> ⊠
	ype PV Wire, #8 Str TC, XLPO Ins, PVC Jkt, 600V PV 90C Dry/We
	Request Sample
Product Description UL Type PV Wire, 8AWG (133(7x19)x	(29) Tinned Copper, XLPO Insulation, PVC Outer Jacket, 600V PV 90C Dry/Wet USE-2 RHW-2 SUN RES
Technical Specifications	
Product Overview	
Suitable Applications:	Interconnection wiring of grounded and ungrounded photovoltaic power systems as described in Section 690.31(A) of the 2008 NEC.
Physical Characteristics (Overall)	
Conductor	
AWG Stranding Material No. of 0 8 133x29 TC - Tinned Copper 1	Conductors
Conductor Count:	1
Insulation	
Material Nominal Wall T	hickness
XLP, XLPO, XLPE (Thermoset) 0.063 in XLP, XLPO, XLPE (Thermoset)	
Outer Jacket Material Nominal Diameter No	ominal Wall Thickness
	033 in
Electrical Characteristics	
Conductor DCR	
Nominal Conductor DCR 0.61 Ohm/1000ft	
Current	
Element Single Conductor in Free Aair @ 30C Ambient 8	Max. Recommended Current [A] 30 Amps Single Conductor in Free Air
Voltage	
UL Voltage Rating 600 V	
Temperature Range	
UL Temp Rating:	90°C Wet/Dry
Operating Temperature Range:	-40°C To +90°C

Mechanical Characteristics

Bulk Cable Weight:	98 lbs/1000ft
Max. Pull Tension:	213 lbs
Min. Bend Radius/Minor Axis:	3.625 in

Standards

NEC/(UL) Compliance:	PV, RHW-2, USE-2
UL AWM Style Compliance:	N/A
Military Compliance:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Sunlight Resistance:	

Flammability, LS0H, Toxicity Testing

Yes

No

UL Flammability:	VW-1
UL voltage rating:	600 V RMS
Plenum/Non-Plenum	

Plenum (Y/N):

Related Part Numbers

Variants

Item #	Color	Put-Up Type	Length	UPC
38208 0105000	Black	Reel	5,000 ft	612825147619
Footnote:				C - CRATE RE
Product Note	es			
Notes:		Separator mate		
History				
Update and Revision:		Revision Num		

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

38208 0101000 38208 0105000