

Max. Pull Tension:

Min Bend Radius/Minor Axis:

213 lbs 3.625 in

*	Product: <u>38208</u> ☑	
	UL Type PV Wire, #8 Str TC, XLPO Ins, PVC Jkt, 600V PV 90C E	Dry/Wet
Product Description UL Type PV Wire, 8AWG (1	33(7x19)x29) Tinned Copper, XLPO Insulation, PVC Outer Jacket, 600V PV 90C Dry/Wet USE-2 RHW-2 SL	JN RES
Technical Specification	IS	
Product Overview		
Suitable Applications:	Interconnection wiring of grounded and ungrounded photovoltaic power systems as described in Section 690.31(A) of the 2008 NEC.	
Physical Characteristics (Overall)	
Conductor		
AWG Stranding Material 8 133x29 TC - Tinned Cop	opper 1	
Conductor Count:	1	
Insulation		
Material No. XLP, XLPO, XLPE (Thermoset) 0.0	ominal Wall Thickness	
XLP, XLPO, XLPE (Thermoset)		
Outer Jacket Material		
Material Nominal	Diameter Nominal Wall Thickness	
PVC - Polyvinyl Chloride 0.364 in	0.033 in	
Electrical Characteristics		
Conductor DCR		
Nominal Conductor DCR 0.61 Ohm/1000ft		
Current		
Element Single conductor in free air @ 30 am	Max. Recommended Current [A] nbient 80 Amps Single Conductor in Free Air	
Voltage		
UL Voltage Rating 600 V		
Temperature Range		
UL Temp Rating:	90°C Wet/Dry	
Operating Temp Range:	-40°C To +90°C	
Mechanical Characteristic	s	
Bulk Cable Weight:	98 lbs/1000ft	

Standards

NEC/(UL) Compliance:	PV, RHW-2, USE-2
UL AWM Style Compliance:	N/A
Military Compliance:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU RoHS Compliance Date (yyyy-mm-dd):	2009-09-01
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Sunlight Resistance:	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	600 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No

Part Number

Variants

ltem #	Color	Putup Type	Lengt	h UPC
38208 0105000	Black	Reel	5,000	ft 612825147619
Footnote:			С	- CRATE REEL PU
Product Note	es			
Notes:			S	eparator material o
History				

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: 38208 0101000 38208 0105000