

Product: <u>5100UP</u> ☑ Audio Cable, 2 Conductor 14 AWG, BC, Unshielded, CL3

Product Description

Audio Cable, Rated-CL3, 2-14 AWG highly flexible stranded bare copper conductors with PVC insulation, PVC jacket with ripcord

Technical Specifications

Product Overview

Suitable Appli	cations:	Sec	Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls					
onstructi	on Details							
	on Details							
Conductor								
Element	No. of Eleme							
Conductor(s)	2	14 AV	VG 42x30	BC - Bare Copper				
nsulation								
Element	Mater		Nom. Thickn					
Conductor(s)	PVC - Polyvir	nyl Chloride	0.020 in (0.51	mm) 0.115 in (2.92	mm)	Black, White		
Outer Jacket								
Mater		lom. Thicki		Diameter Ripcord				
PVC - Polyvin	yl Chloride 0.	018 in (0.46	6 mm) 0.266 in	(6.76 mm) Yes				
Overall Cable	Diameter (Nor	minal): 0.26	66 in (6.76 mm)					
Electrical (Characteris	stics						
	Characteris	stics						
Electricals			Nom Copositi	nnoo Cond to Cond	Me	x Current		
Electricals Element	Nom. Condu	ctor DCR		ance Cond-to-Cond /m)		x. Current r conductor @ 30°		
Electricals Element Conductor(s)	Nom. Condu	ctor DCR	Nom. Capacita 29 pF/ft (95 pF/			x. Current r conductor @ 30°		
Electricals Element Conductor(s) Voltage	Nom. Condu 2.42 Ohm/100	ctor DCR						
Electricals Element Conductor(s) Voltage UL Voltage R	Nom. Condu 2.42 Ohm/100	ctor DCR						
Electricals Element Conductor(s) Voltage	Nom. Condu 2.42 Ohm/100	ctor DCR						
Electricals Element Conductor(s) Voltage UL Voltage R 300 V (CL3)	Nom. Condu 2.42 Ohm/100	ctor DCR 00ft						
Electricals Element Conductor(s) Voltage UL Voltage R 300 V (CL3)	Nom. Condu 2.42 Ohm/100	ctor DCR 00ft						
Electricals Element Conductor(s) Voltage UL Voltage R 300 V (CL3) Mechanica	Nom. Condu 2.42 Ohm/100 ating	otor DCR 00ft pristics						
Electricals Element Conductor(s) Voltage UL Voltage R 300 V (CL3) Mechanica Temperature	Nom. Condu 2.42 Ohm/100 ating	ctor DCR 00ft pristics						
Electricals Element Conductor(s) Voltage UL Voltage R 300 V (CL3) Mechanica Temperature UL Temperat	Nom. Condu 2.42 Ohm/100 atting	ctor DCR 00ft pristics						
Electricals Element Conductor(s) Voltage UL Voltage R 300 V (CL3) Mechanica Temperature UL Temperat 75°C	Nom. Condu 2.42 Ohm/100 tating Il Characte ure Operat -20°C to -	ctor DCR 00ft pristics ting +75°C						
Electricals Element Conductor(s) Voltage UL Voltage R 300 V (CL3) Mechanica Temperature UL Temperat 75°C Bend Radius	Nom. Condu 2.42 Ohm/100 tating Il Characte -20°C to - in. Installatio	ctor DCR 00ft eristics ting +75°C						
Electricals Element Conductor(s) Voltage UL Voltage R 300 V (CL3) Mechanica Temperature UL Temperature UL Temperature Stationary M	Nom. Condu 2.42 Ohm/100 ating all Characte -20°C to - in. Installatio) 2.7 in (69 in	ctor DCR 00ft eristics +75°C m Min. mm)		/m)				

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor
Flammability / Reaction to Fire:	UL 1685 UL loading , IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 725, CL3
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:

Revision Number: 0.491 Revision Date: 02-15-2024

Part Numbers

Variants

ltem #	Color	Putup Type	Length	UPC	Footnote
5100UP 010500	Black	Reel	500 ft	612825156529	
5100UP 010U500	Black	UnReel	500 ft	612825433484	
5100UP 0101000	Black	Reel	1,000 ft	612825156550	С
5100UP 010U1000	Black	UnReel	1,000 ft	612825156536	
5100UP 010Z1000	Black	ReelTuff Box	1,000 ft	612825156611	
5100UP 008U500	Gray	UnReel	500 ft	612825156505	
5100UP 0081000	Gray	Reel	1,000 ft	612825156451	С
5100UP 008U1000	Gray	UnReel	1,000 ft	612825156468	
5100UP 005500	Green, Dark	Reel	500 ft	612825156413	
5100UP 005U500	Green, Dark	UnReel	500 ft	612825156475	
5100UP 0051000	Green, Dark	Reel	1,000 ft	612825156444	
5100UP 005U1000	Green, Dark	UnReel	1,000 ft	612825156420	
5100UP 009500	White	Reel	500 ft	612825156482	
5100UP 009U500	White	UnReel	500 ft	612825156543	
5100UP 0091000	White	Reel	1,000 ft	612825156512	
5100UP 009U1000	White	UnReel	1,000 ft	612825156499	

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

<u>5100UP 008U1000</u> <u>5100UP 0101000</u> <u>5100UP 005500</u> <u>5100UP 0051000</u> <u>5100UP 0081000</u> <u>5100UP 009500</u> 5100UP 0091000 <u>5100UP 010500</u>