



Product: <u>5220FL</u>

Fire Alarm, #16-2c BC, Shielded, FPLR

Product Description

Fire Alarm Cable, Riser-FPLR, 2-16 AWG solid bare copper conductors with polypropylene insulation, overall Beldfoil® shield, PVC jacket with ripcord

Technical Specifications

Product Overview

| Suitable Appl | ications: | Fire Alarm, Monitor/De | etection, Circuits: Audio | o, Control, Initiating, Notification, Noisy Env | rironment | |
|--|--|---|---------------------------|---|-----------|--------------|
| onstruct | ion Details | | | | | |
| onductor | | | | | | |
| Element | No. of Elements | Size Stranding | Material | | | |
| Conductor(s) | | | C - Bare Copper | | | |
| sulation | | | | | | |
| Element | Material | Nom. Thickness N | lom. Insulation Diame | ter Color Code | | |
| Conductor(s) | PP - Polypropyler | e 0.007 in (0.18 mm) 0 | .065 in (1.7 mm) | Black, Red | | |
| uter Shield | | | | | | |
| hield Type | Material | Coverage Dra | ainwire Type | | | |
| Гаре | Bi-Laminate (Alum | n+Poly) 100% 24 A | WG (Solid) TC | | | |
| uter Jacket | | | | | | |
| Mater | | Thickness Nom. Dia | | | | |
| VC - Polyvir | nyl Chloride 0.017 | in (0.43 mm) 0.170 in (4 | .32 mm) Yes | | | |
| | | 0.170 11 (4. | . , | | | |
| | | l): 0.170 in (4.32 mm) | | | | |
| Overall Cable | | I): 0.170 in (4.32 mm) | | | | |
| Dverall Cable | e Diameter (Nomina | I): 0.170 in (4.32 mm) | | | | |
| Overall Cable | e Diameter (Nomina | I): 0.170 in (4.32 mm) | | m. Capacitance Cond-to-Other (Conds + | · Shield) | Max. Current |
| Dverall Cable lectrical lectricals Element | Diameter (Nomina Characteristic | I): 0.170 in (4.32 mm) | e Cond-to-Cond No | m. Capacitance Cond-to-Other (Conds + 3 pF/ft (387 pF/m) | | Max. Current |
| Overall Cable ilectrical lectricals Element Conductor(s) | Diameter (Nomina Characteristic |): 0.170 in (4.32 mm) S DCR Nom. Capacitanc | e Cond-to-Cond No | | | |
| Dverall Cable lectrical ectricals Element Conductor(s) bltage | Characteristic Nom. Conductor 3.9 Ohm/1000ft |): 0.170 in (4.32 mm) S DCR Nom. Capacitanc | e Cond-to-Cond No | | | |
| Dverall Cable | Piameter (Nomina Characteristic Nom. Conductor 3.9 Ohm/1000ft |): 0.170 in (4.32 mm) S DCR Nom. Capacitanc | e Cond-to-Cond No | | | |
| Overall Cable Contricals Element Conductor(s) oltage JL Voltage F 300 V (FPLR) | Piameter (Nomina Characteristic Nom. Conductor 3.9 Ohm/1000ft Rating | DCR Nom. Capacitanc 65.5 pF/ft (215 pF | e Cond-to-Cond No | | | |
| Dverall Cable lectricals Element Conductor(s) bltage JL Voltage F 800 V (FPLR) | Piameter (Nomina Characteristic Nom. Conductor 3.9 Ohm/1000ft | DCR Nom. Capacitanc 65.5 pF/ft (215 pF | e Cond-to-Cond No | | | |
| Dverall Cable clectricals Element Conductor(s) oltage JL Voltage F 300 V (FPLR) lechanica emperature | e Diameter (Nomina Characteristic Nom. Conductor 3.9 Ohm/1000ft Rating) al Characteris | DCR Nom. Capacitanc 65.5 pF/ft (215 pF | e Cond-to-Cond No | | | |
| Overall Cable lectrical ectricals Element Conductor(s) bltage JL Voltage F 600 V (FPLR) lechanica emperature JL Temperat | e Diameter (Nomina Characteristic Nom. Conductor 3.9 Ohm/1000ft Rating) al Characteris | 1): 0.170 in (4.32 mm) S DCR Nom. Capacitanc 65.5 pF/ft (215 pF) tics | e Cond-to-Cond No | | | |
| Dverall Cable lectricals Element Conductor(s) bitage JL Voltage F 300 V (FPLR) lechanica emperature JL Temperat 75°C | e Diameter (Nomina Characteristic Nom. Conductor 3.9 Ohm/1000ft Rating) al Characteriss | 1): 0.170 in (4.32 mm) S DCR Nom. Capacitanc 65.5 pF/ft (215 pF) tics | e Cond-to-Cond No | | | |
| Dverall Cable Conductor(s) Conductor(s) Oltage JL Voltage F 300 V (FPLR) Conductor(s) | e Diameter (Nomina Characteristic Nom. Conductor 3.9 Ohm/1000ft Rating) al Characterist ture Operating -20°C to +75° lin. Installation M | 1): 0.170 in (4.32 mm) S DCR Nom. Capacitanc 65.5 pF/ft (215 pF tics C | e Cond-to-Cond No | | | |

Bulk Cable Weight:

23 lbs/1000ft

Standards and Compliance

| Environmental Suitability: | Indoor - Riser, Indoor |
|----------------------------------|---|
| Flammability / Reaction to Fire: | UL 1666 Riser, IEC 60332-1-2 |
| CPR Compliance: | CPR Euroclass: Eca |
| NEC / UL Compliance: | Article 760, FPLR |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance: | UKCA Mark |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |
| Plenum Number: | 6220FL |

History

Revision Number: 0.463 Revision Date: 02-15-2024

Part Numbers

Update and Revision:

Variants

| ltem # | Color | UPC | Footnote |
|----------------|-------|--------------|----------|
| 5220FL D151000 | Blue | 612825158301 | |
| 5220FL 0021000 | Red | 612825158318 | С |
| 5220FL 0091000 | White | 612825158325 | |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

5220FL 0021000 5220FL 0091000 5220FL D151000