



Product: <u>5400FE</u> ☑

Security & Sound, 2 Conductor 20 AWG, BC, Shielded, CMR

## **Product Description**

Security & Commercial Audio Cable, Riser-CMR, 2-20 AWG stranded bare copper conductors with polypropylene insulation, Beldfoil® shield and PVC jacket with ripcord

### **Technical Specifications**

#### **Product Overview**

Suitable Applications:	ntercom/PA Systems, Sound/Audio Systems	
0 1 1 5 1 1		

#### **Construction Details**

#### Conductor

Element	No. of Elements	Size	Stranding	Material
Conductor(s)	2	20 AWG	7x28	BC - Bare Copper

#### Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Conductor(s)	PP - Polypropylene	0.008 in (0.20 mm)	0.052 in (1.3 mm)	Black, Red

#### Outer Shield

Shield Type	Material	Coverage	Drainwire Type
Таре	Bi-Laminate (Alum+Poly)	100%	24 AWG (7x32) TC

## Outer Jacket

Material	Nom. Thickness	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	0.017 in (0.43 mm)	0.142 in (3.61 mm)	Yes
Overall Cable Diameter (1	Nominal):	0.142 in (3.61 mn	n)

#### **Electrical Characteristics**

#### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	10.3 Ohm/1000ft	40 pF/ft (130 pF/m)	72 pF/ft (240 pF/m)	8 Amps per conductor @ 25°C

#### Voltage

UL Voltage Rating

#### **Mechanical Characteristics**

#### Temperature

<b>UL Temperature</b>	Operating
75°C	-20°C to +75°C

#### Bend Radius

Stationary Min.	Installation Min.		
1.4 in (36 mm)	1.4 in (36 mm)		

Max. Pull Tension:	30.7 lbs (13.9 kg)
Bulk Cable Weight:	13 lbs/1000ft

#### **Standards and Compliance**

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Reaction to Fire:	UL 1666 Riser, IEEE 1202 FT4, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca; CPR UKCA Class: Eca
NEC / UL Compliance:	Article 800, CMR
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6400FE

#### **History**

Update and Revision:	Revision Number: 0.511 Revision Date: 03-29-2023	
opauto una reviolon.	Tovision Humber, 0.0 11 Novision Bute. 00 25 2020	

#### **Part Numbers**

#### Variants

Item #	Color	Putup Type	Length	UPC/EAN	Footnote
5400FE.00305	Chrome	Reel	305 m	8719605008497	
5400FE 008500	Gray	Reel	500 ft	612825161929	
5400FE 008U500	Gray	UnReel	500 ft	612825423294	
5400FE 0081000	Gray	Reel	1,000 ft	612825161943	С
5400FE 008U1000	Gray	UnReel	1,000 ft	612825161936	
5400FE 008Z1000	Gray	ReelTuff Box	1,000 ft	612825161967	

#### © 2024 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Belden Wire & Cable:

5400FE 008500 5400FE 008U500 5400FE 0081000