

# Product: <u>5508FE</u> ☑ Security & Sound, #22-10c, BC, Shielded, CMR

# **Product Description**

Security & Sound Cable, Riser-CMR, 10-22 AWG stranded bare copper conductors with polyolefin insulation, Beldfoil® shield and PVC jacket with ripcord

## **Technical Specifications**

### Product Overview

Max. Pull Tension:

Suitable Applications:		Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls, Noisy Environment						
Construction Details								
Conductor								
Element No. of E	lements Size	Stranding	Materia					
Conductor(s) 10	22	7x30	BC - Bare C	opper				
Insulation								
Material N	om. Thickness	Nom. Ins	ulation Diam	eter	Color Code			
PP - Polypropylene 0.0	008 in (0.20 mm)	0.062 in (*	1.6 mm)	BI	ack, Red, White, Green, Brown, Blue, Orar	ge, Yellow, Purple, Gray		
Outer Shield								
Shield Type	Material	Coverage	Drainwire	Туре				
Tape Bi-Lamin	ate (Alum+Poly)	100%	24 AWG (7	k32) TC				
Outer Jacket								
Material	Nom. Thick	ness No	m. Diameter	Ripc	ord			
PVC - Polyvinyl Chlorid	e 0.018 in (0.46	6 mm) 0.21	7 in (5.51 mm	) Yes				
Electrical Characteristics								
Electricals								
Nom. Conductor DCR	Nom. Capacita	ance Cond-	to-Cond No	m. Cap	acitance Cond-to-Other (Conds + Shield	Max. Current		
17.41 Ohm/1000ft 22.5 pF/ft (73.		3 pF/m)		40.5 pF/ft (133 pF/m)		2 Amps per Conductor at 25°C		
Voltage								
UL Voltage Rating 300 V								
Mechanical Characteristics								
Temperature								
UL TemperatureOperating75°C-20°C To +75°C								
Bend Radius								
Stationary Min.     Installation Min.       2.17 in (55.1 mm)     2.17 in (55.1 mm)								

96.5 lbs (43.8 kg)

Bulk Cable Weight:	32 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Outdoor		
Flammability / Reaction to Fire:	UL1666 Riser		
NEC / UL Compliance:	Article 800, CMR		
CEC / C(UL) Compliance:	CMG		
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)		
APAC Compliance:	China RoHS II (GB/T 26572-2011)		
Plenum Number:	6508FE		

### History

Update and Revision:

Revision Number: 0.428 Revision Date: 02-03-2025

### **Part Numbers**

### Variants

ltem #	Color	UPC	Footnote
5508FE 0081000	Gray	612825163947	С
5508FE 008U1000	Gray	612825163923	
5508FE 008U500	Gray	612825163930	

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

5508FE 008U500 5508FE 0081000