

# **Product Description Technical Specifications Product Overview** Suitable Applications: Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls **Construction Details** ay

UL Temperature Operating		
75°C 0°C to +75°C		
Bend Radius		
Stationary Min. Installation Min.		
2.8 in (71 mm) 2.8 in (71 mm)		
Max. Pull Tension:	224 lbs (102 kg)	

## Product: 6308UE

Security & Sound, #18-10c, BC, CMP

Security & Sound Cable, Plenum-CMP 10-18 AWG stranded bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

Conductor											
Element	No. of Elem	ents Siz	e S	tranding		Material					
Conductor(s)	10	18 AV	VG 7	x26	BC ·	- Bare Copper					
Insulation											
Element	Mate	orial	Non	n. Thickn	ess	Nom. Insulat	ion Diameter		Color	Code	
Conductor(s)	PVC - Polyv Chloride	inyl	0.00	9 in (0.23	mm)	0.063 in (1.6 r	nm)	Black, Red, White, O	Green, Brown,	Blue, Oranç	ge, Yellow, Purple, Gra
Outer Jacket											
Mater	rial	Nom. Thick	ness	Nom. I	Diame	eter Ripcore	1				
PVC - Polyvin	yl Chloride	0.015 in (0.38	3 mm)	0.278 in	(7.06	mm) Yes					
Overall Cable	Diameter (No	ominal):		0.278 ir	ר) ו	6 mm)					
Electrical	Character	istics									
Electricals											
Element	Nom. Cond	uctor DCR	Nom.	Capacita	ince	Cond-to-Cond	М	ax. Current			
Conductor(s)	6.5 Ohm/100	DOft	32.5	pF/ft (107	pF/m	)	9.8 Amps p	er conductor @ 25°C	]		
Voltage											
UL Voltage R 300 V	tating										
Mechanica	I Charact	eristics									
Temperature											
UL Temperat 75°C	o°C to +										
Bend Radius											
Stationary M 2.8 in (71 mm											
Max. Pull Ten	sion:			224 lbs	(102	kg)					
Bulk Cable W	eight:			71 lbs/1	1000fi	t					

Environmental Suitability:	Indoor - Plenum, Indoor
Flammability / Reaction to Fire:	NFPA 262, UL 910 (Plenum), FT6, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	5308UE

### History

Update and Revision:

Revision Number: 0.424 Revision Date: 01-20-2023

#### **Part Numbers**

#### Variants

 Item #
 Color
 UPC

 6308UE 8771000
 Natural
 612825175629

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

6308UE 8771000