



Product: 6500UE ☑

Security & Sound, 2 Conductor 22 AWG, BC, CMP

## **Product Description**

Security & Commercial Audio Cable, Plenum-CMP 2-22 AWG stranded bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

## **Technical Specifications**

#### **Product Overview**

| Suitable Applications: |             | Se                                      | Security System, Intercom/PA, Audio/Speaker, Noisy Environment |              |           |          |  |  |
|------------------------|-------------|---|--|--------------|-----------|----------|--|--|
| Constructi             | on Deta     | ils                                     |  |              |           |          |  |  |
| onductor               |             |   |  |              |           |          |  |  |
| Element                | Number o    | f Element                               | AWG  | Stranding    | Mate      | erial    |  |  |
| Conductor(s)           | 2           |   | 22   | 7x30         | BC - Bare | e Copper |  |  |
| sulation               |             |   |  |              |           |          |  |  |
| Element                | Ma          | aterial                                 | Т  | hickness [in | ] Color C | ode      |  |  |
| Conductor(s)           | PVC - Pol   | yvinyl Chlor                            | ide 0  | .008         | Black, F  | Red      |  |  |
| ıter Jacket I          | Material    |   |  |              |           |          |  |  |
| Mater                  | ial         | Thickness                               | Nor  | n. Diameter  | Ripcord   |          |  |  |
| PVC - Polyvin          | yl Chloride | 0.015 in                                | 0.12   | 20 in        | Yes       |          |  |  |
| Cable Diamet           | er (Nominal | ): 0.1                                  | 3 in   |              |           |          |  |  |
| lectrical (            | Characte    | ristics                                 |  |              |           |          |  |  |
| -icoti ioui ·          | Jiididott   | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, |  |              |           |          |  |  |

| Element      | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Max. Current                   |
|--------------|--------------------|-------------------------------|--------------------------------|
| Conductor(s) | 16.4 Ohm/1000ft    | 55 pF/ft                      | 2.8 Amps per Conductor at 25°C |

## Voltage



### **Mechanical Characteristics**

| Temperature      |              |              |
|------------------|--------------|--------------|
| <b>UL Rating</b> | Operating    | Installation |
| 75°C             | 0°C to +75°C | 0°C To +75°C |

#### **Bend Radius**

| Stationary Min.   | Installation Min | in. |
|-------------------|------------------|-----|
| 1.5 in            | 1.3 in           | Ī   |
| Max. Pull Tension | n:               | 24  |
| Bulk Cable Weigl  | ht:              | 8   |

## **Standards and Compliance**

| Environmental Suitability:      | Indoor - Plenum, Indoor   |
|---------------------------------|---|
| Flammability / Fire Resistance: | NFPA 262, FT6, IEC 60332-1-2  |
| NEC / UL Compliance:            | Article 800, CMP  |
| CEC / C(UL) Compliance:         | CMP   |
| CPR Euroclass:                  | Eca   |
| European Directive Compliance:  | EU CE Mark, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance:                | China RoHS II (GB/T 26572-2011)   |
| Non-Plenum Number:              | 5500UE  |

#### **History**

| Update and Revision: | Revision Number: 0.319 Revision Date: 08-12-2020 |
|----------------------|--|

#### © 2020 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: 6500UE 8771000 6500UE 877C1000