

Product: <u>734D1P</u> ☑



DS-3 and DS-4, 734D Series, #20-1 SPC Coax, CMP

### **Product Description**

20 AWG solid .032" (.81mm) silver-plated copper conductor(s), foam, foam FEP insulation, Beldfoil® + tinned copper braid shield (85% coverage), Flamarrest® jacket.

#### **Technical Specifications**

#### **Physical Characteristics (Overall)**

Conduc	Conductor				
AWG	Stranding	Material	Nom	inal Diameter	No. of Coax
20	Solid	SCCS - Silvered Copper Covered Steel	0.032	2 in	1
Condu	ctor Count:			1	

#### Insulation

Material	Nominal Diameter
FEP - Fluorinated Ethylene Propylene (Foam)	0.148 in

#### Outer Shield

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Bi-Laminate (Alum+Poly)	Beldfoil®	100%
Braid	2	Tinned Copper (TC)		85%

#### Outer Jacket

Material	Material Trade Name	Nominal Diameter
PVC - Polyvinyl Chloride	Flamarrest®	0.215 in

#### **Electrical Characteristics**

#### Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance	Nominal Outer Shield DCR	Outer Conductor DCR
10 Ohm/1000ft	10 Ohm/1000ft	2.4 Ohm/1000ft	2.4 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Shield 17.3 pF/ft

#### Inductance

Nominal Inductance

#### Impedance

Nominal Characteristic Impedance
75 Ohm

#### Return Loss (RL)

Frequency [MHz] 15-95 MHz

#### Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.27 ns/ft	80%

#### High Frequency

Min. RL (Return Loss) [dB]

## Voltage

UL Voltage Rating
300 V RMS

#### **Temperature Range**

Operating Temp Range:	0°C To +75°C

#### **Mechanical Characteristics**

Bulk Cable Weight:	32 lbs/1000ft
Max. Pull Tension:	52 lbs
Min. Bend Radius/Minor Axis:	2 in

#### **Standards**

NEC/(UL) Compliance:	СМР
CEC/C(UL) Compliance:	CMP
RG Type:	59
Other Specification:	Telcordia Specification GR-139-CORE

#### **Applicable Environmental and Other Programs**

Environmental Space:	Indoor - Plenum
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No
MII Order #39 (China RoHS):	Yes

#### Suitability

Suitability - Burial:	No
Suitability - Indoor:	Yes

## Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT6
UL Flammability:	NFPA 262
UL voltage rating:	300 V RMS

### Plenum/Non-Plenum

Plenum (Y/N):	Yes

#### **Part Number**

Non-Plenum Number: 734D1	
--------------------------	--

#### Variants

Item #	Color	Put-Up Type	Length	UPC
734D1P 008500	Gray	Reel	500 ft	612825184423
734D1P 0081000	Gray	Reel	1,000 ft	612825184416

Footnote: C - CRATE REEL PUT-UP.

### History

Update and Revision:

Revision Number: 0.170 Revision Date: 12-15-2021

#### © 2022 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: 734D1P 0081000 734D1P 008500