

Product: <u>7916AP</u> ☑

Broadband Coax, Series 6, 18 AWG Solid BC, Quad Shield, Flamarrest® Jkt, CMP

Product Description

Broadband Coax, Series 6, 18 AWG Solid Bare Copper Conductor, FEP Insulation, Foil + 60% Aluminum Braid + Foil + 40% Aluminum Braid Shield, Flamarrest® Jacket, CMP

Technical Specifications

Product Overview

| Suitable Applications: | Broadband, Cable Television (CATV), RF drop cable, Direct Broadcast Satellite (DBS), Over-The-Air (OTA) antennas |
|------------------------|--|
| | |

Construction Details

| Series | Type |
|--------|-------|
| Jenes | Type. |

Conductor

| Size | Stranding | Nom. Diameter | Material |
|--------|-----------|---------------|------------------|
| 18 AWG | Solid | 0.040 in | BC - Bare Copper |

6

Insulation

| Material | Nom. Insulation Diameter | Color Code |
|---|--------------------------|------------|
| FEP - Fluorinated Ethylene Propylene (Foam) | 0.170 in (4.32 mm) | White |

Outer Shield

| Layer | Outer Shield Type | Material | Material Trade Name | Coverage |
|-------|-------------------|-------------------------------|---------------------|----------|
| 1 | Таре | Tri-Laminate (Alum+Poly+Alum) | Duobond® II | 100% |
| 2 | Braid | Aluminum | | 60% |
| 3 | Таре | Tri-Laminate (Alum+Poly+Alum) | Duofoil® | 100% |
| 4 | Braid | Aluminum | | 40% |

Outer Jacket

| Material | Nom. E | Diameter | |
|---------------------------------------|----------|-------------|----------|
| PVC - Polyvinyl Chloride | 0.248 in | (6.30 mm) | |
| Overall Cable Diameter (Nominal): 0.2 | | 0.248 in (6 | 6.30 mm) |

Electrical Characteristics

Return Loss (RL)

| Frequency | Min. Structural Return Loss |
|-----------------|-----------------------------|
| 5 - 1000 MHz | 20 dB |
| 1000 - 2250 MHz | 15 dB |
| 2250 - 3000 MHz | 10 dB |

Attenuation

| Frequency | Nom. Attenuation |
|-----------|------------------|
| 1 MHz | 0.3 dB/100ft |
| 10 MHz | 0.7 dB/100ft |
| 50 MHz | 1.6 dB/100ft |
| 100 MHz | 2.1 dB/100ft |

| 200 MHz | 2.9 dB/100ft |
|----------|--------------|
| 400 MHz | 4.3 dB/100ft |
| 700 MHz | 6.1 dB/100ft |
| 750 MHz | 6.4 dB/100ft |
| 900 MHz | 7.1 dB/100ft |
| 1000 MHz | 8.2 dB/100ft |

Electricals

| Nom. Conductor DCR | Nom. Outer Shield DCR | Nom. Capacitance Cond-to-Shield | Nom. Characteristic Impedance | Nom. Velocity of Prop. |
|--------------------|----------------------------|---------------------------------|-------------------------------|------------------------|
| 6.4 Ohm/1000ft | 4.8 Ohm/1000ft (16 Ohm/km) | 16.3 pF/ft (53.5 pF/m) | 75 Ohm | 83% |

Voltage

UL Voltage Rating 300 V (CMP)

Mechanical Characteristics

Temperature

| UL Temperature | Operating |
|----------------|----------------|
| 75°C | -20°C to +75°C |

Bend Radius

Installation Min.

| 2.5 in (64 mm) | |
|--------------------|-------------------|
| Max. Pull Tension: | 137 lbs (62.1 kg) |
| Bulk Cable Weight: | 39 lbs/1000ft |

Standards and Compliance

| Environmental Suitability: | Indoor - Plenum, Indoor |
|----------------------------------|--|
| Sustainability: | CA Prop 65 |
| Flammability / Reaction to Fire: | NFPA 262 |
| CEC / C(UL) Compliance: | СМР |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |
| Non-Plenum Number: | 7916A |

History

Revision Number: 0.473 Revision Date: 04-29-2024

Part Numbers

Update and Revision:

Variants

| ltem # | Color | Putup Type | Length | UPC | Footnote |
|-----------------|---------|------------|----------|--------------|----------|
| 7916AP 8771000 | Natural | Reel | 1,000 ft | 612825191131 | С |
| 7916AP 877U1000 | Natural | UnReel | 1,000 ft | 612825001836 | |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

7916AP 8771000