

Product: <u>8021</u> ⊠						
Bus Bar Wire, #22 Sol TC						
# Request Sample						

Product Description

Bus Bar Wire, 22AWG (Solid) Tinned Copper, QQ-W-343G

## **Technical Specifications**

#### Product Overview

Suitable Appli	cations:		bus bar				
Constructi	on Dota	ile					
Constructi	on Dela	13					
Conductor							
Element	No. of Ele	ments	Size	Stranding	Material		
Conductor(s)	1	2	22 AWG	Solid	TC - Tinned Copper		
Overall Cable Diameter (Nominal): 0.025 in (0.64 mm)							
Electrical C	Inaracte	ristics	; 				
Electricals							
Nom. Conduc	tor DCR		Max	Current			
16.3 Ohm/100		Sinale co			30°C: 18 A		
16.3 Ohm/1000ft Single conductor in free air @ 30°C: 18 A							
Voltage							
UL Voltage R	ating						
600 V RMS							
Mechanica	I Charao	cteristi	CS				
<b>T</b>							
Temperature							
UL Temperat		erating To +80°C	~				
80.0	-40°C	10 +80 °C	- -				

#### Bend Radius

Stationary Min. Installation Min.	
0.25 in (6.4 mm) 0.25 in (6.4 mm)	
Max. Pull Tension:	5 lbs (2.3 kg)
Bulk Cable Weight:	2 lbs/1000ft

### **Standards and Compliance**

Environmental Suitability:	Outdoor
Sustainability:	CA Prop 65
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
History	
Update and Revision:	Revision Number: 0.450 Revision Date: 07-03-2024

#### **Part Numbers**

#### Variants

Item #	Color	Putup Type	Length	UPC
8021 000100	None	Reel	100 ft	612825194347
8021 0001000	None	Reel	1,000 ft	612825194354

#### © 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

8021 000100 8021 0001000