

L	
83	
CL 98	

## Product: <u>83269</u> ☑

Mil-Spec Coax, 50 Ohm, RG-188, 26 AWG Str SCCS, 95% SC Braid, PTFE Tape Jkt, Commercial Non-QPL

## **Product Description**

Mil-Spec Coax, 50 Ohm, RG-188, 26 AWG (7x34) Silvered Copper Covered Steel Conductor, PTFE Insulation, 95% Silvered Copper Braid Shield, PTFE Tape Jacket, Commercial, non-QPL

## **Technical Specifications**

#### **Product Overview**

Quitable	Applications	٨٠	
Suitable Applications: Aerospace wireless communication			
Constru	uction De	tails	
RG Type:	RG Type: 188		
Conducto	r		
Size Stranding Nom. Diam		Nom. Diameter	Material
26 AWG 7x34 0.020 in		0.020 in	SCCS - Silvered Copper Covered Steel

#### Insulation

Material	Nom. Insulation Diameter	Color Code
PTFE - Polytetrafluoroethylene	0.058 in (1.5 mm)	White

## Outer Shield

Layer	Outer Shield Type	Material	Coverage				
1	Braid	Silvered Copper (SC)	95%				
Outer Jacket							
	Material	Nom. Diameter					

PTFE - Polytetrafluoroethylene		100 in (2.54 mm)	
Overall Cable Diameter (Nomina	al):	0.100 in (2.54 mm)	

## **Electrical Characteristics**

#### Attenuation

Frequency	Nom. Attenuation		
1 MHz	1.2 dB/100ft		
10 MHz	2.7 dB/100ft		
50 MHz	5.6 dB/100ft		
100 MHz	8.3 dB/100ft		
200 MHz	12.0 dB/100ft		
400 MHz	17.5 dB/100ft		
700 MHz	23.7 dB/100ft		
900 MHz	27.3 dB/100ft		
1000 MHz	29.0 dB/100ft		

#### Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
91.2 Ohm/1000ft	8.5 Ohm/1000ft (28 Ohm/km)	29 pF/ft (95 pF/m)	50 Ohm	70%

#### **Mechanical Characteristics**

#### Temperature

Operating -70°C to +200°C

#### Bend Radius

## Installation Min.

1	in	(25	mm)	

Max. Pull Tension:	21 lbs (9.5 kg)
Bulk Cable Weight:	11 lbs/1000ft

### **Standards and Compliance**

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor	
Sustainability:	: CA Prop 65	
Military Compliance:	Commercial, non-QPL product (similar to M17/113-RG188)	
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)	
APAC Compliance: China RoHS II (GB/T 26572-2011)		

#### **History**

Update and Revision:

Revision Number: 0.506 Revision Date: 04-29-2024

#### **Part Numbers**

#### Variants

ltem #	Color	Putup Type	Length	UPC	Footnote
83269 009100	White	Reel	100 ft	612825203766	E
83269 009500	White	Reel	500 ft	612825203780	E
83269 0091000	White	Reel	1,000 ft	612825203773	E

## © 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

83269 0091000 83269 009100 83269 009500