



Product: <u>83317E</u> ☑

Electronic, 2 C #26 Str SPC, TFE Ins, OA SPC Brd, TFE Tape Jkt, MIL-W-16878/4 (Type E)

😭 Request Sample

Product Description

High Temperature Electronic, 2 Conductor 26AWG (7x34) Silver Plated Copper, TFE Insulation, Overall Silver Plated Copper Braid(85%) Shield, TFE Tape Outer Jacket, MIL-W-16878/4 (Type E)

Technical Specifications

	Suitable Applications:			pe E) Spec; Extreme H	h/Low Temperatu	e Environme
Construction Details						
Conductor						
Element	No. of Elements	Size	Stranding	Material		
Conductor(s)	2	26 AWG	7x34	SC - Silvered Copper		
Insulation						
Element	Materi	al	Nom.	Thickness Nom. Insu	ation Diameter	Color Code
Conductor(s)	PTFE - Polytetraf	luoroethyle	ene 0.010 ir	n (0.25 mm) 0.039 in (0	99 mm) V	Vhite, Black
Quter Shield						
Shield Type Material Coverage						
Braid Silvered Copper (SC) 85%						
	Outer Jacket					
Outer Jacket		Material Nom. Thickness Nom. Diameter				
	terial	Nom. Thi	ckness	Nom. Diameter		

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	39 Ohm/1000ft	20.8 pF/ft (68.2 pF/m)	35.5 pF/ft (116 pF/m)	3 Amps per conductor @ 25°C

Voltage

Voltage Rating 600 V

Mechanical Characteristics

Temperature

UL Temperature	Operating
200°C	-65°C to +200°C

Bend Radius

Stationary Min.	Installation Min.		
1.21 in (30.7 mm)	1.21 in (30.7 mm)		

Max. Pull Tension:	7 lbs (3.2 kg)
Bulk Cable Weight:	12 lbs/1000ft

Standards and Compliance

Sustainability:	CA Prop 65
CPR Compliance:	CPR Euroclass: Eca; CPR UKCA Class: Eca
NEMA Compliance:	NEMA HP3
Military Compliance:	MIL-W-16878/4 (Type E insulated conductors)
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes:	Teflon® is a registered trademark of E. I. duPont de Nemours

History

Update and Revision:

Revision Number: 0.531 Revision Date: 02-15-2024

Part Numbers

Variants

ltem #	Color	Putup Type	Length	UPC	Footnote
83317E 009100	White	Reel	100 ft	612825203926	E
83317E 009500	White	Reel	500 ft	612825203933	E
83317E 0091000	White	Reel	1,000 ft	612825347514	E

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

and Co. used under license by Belden, Inc.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

83317E 009500 83317E 0091000 83317E 009100