



Product: <u>83333E</u> ☑

Electronic, 3 C #24 Str SPC, TFE Ins, OA SPC Brd, TFE Tape Jkt, MIL-W-16878/4 (Type E)

😭 Request Sample

Product Description

High Temperature Electronic, 3 Conductor 24AWG (19x36) Silver Plated Copper, TFE Insulation, Overall Silver Plated Copper Braid(85%) Shield, TFE Tape Outer Jacket, MIL-W-16878/4 (Type E)

Technical Specifications

Product Overview

Suitable Appli	cations.	10112-00	- 1007 0/4 (Ty		rightew remperat	are Environments, u		og signals & voltage control
onstructi	on Details							
onductor								
Element	No. of Elements	Size	Stranding	Material				
Conductor(s)	3	24 AWG	19x36	SC - Silvered Copp	per			
nsulation								
Element	Materi	al	Nom.	Thickness Nom. I	nsulation Diameter	Color Code		
Conductor(s)	PTFE - Polytetraf	luoroethyle	ne 0.010 ir	n (0.25 mm) 0.044 ii	n (1.1 mm)	White, Black, Red		
Shield Type Braid Duter Jacket	Material Silvered Copper (erage					
Ma	terial	Nom. Thi	ckness	Nom. Diameter				
PTFE - Polyte	trafluoroethylene	0.011 in (0	.28 mm) 0.	137 in (3.48 mm)				
Overall Cable	Diameter (Nomina	I): 0.137 i	n (3.48 mm)					
lectrical (Characteristic	S						
Element	Nom. Conductor	DCR No	m. Capacita	ance Cond-to-Cond	Nom. Capacitance	e Cond-to-Other (Co	onds + Shield)	Max. Current

Voltage

Voltage Rating 600 V

Mechanical Characteristics

UL Temperature Operating 200°C -65°C to +200°C

Bend Radius

Stationary Min.	Installation Min.		
1.37 in (34.8 mm)	1.37 in (34.8 mm)		

Max. Pull Tension:	17.7 lbs (8.03 kg)	
Bulk Cable Weight:	17 lbs/1000ft	

Standards and Compliance

Sustainability:	CA Prop 65				
CPR Compliance:	CPR Euroclass: Fca				
NEMA Compliance:	NEMA HP3				
Military Compliance:	MIL-W-16878/4 (Type E except stranding), (insulated conductors)				
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)				
APAC Compliance:	China RoHS II (GB/T 26572-2011)				

Product Notes

Notes:

Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

History

Update and Revision: Revision Number: 0.525 Revision Date: 01-20-2023

Part Numbers

Variants

ltem #	Color	Putup Type	Length	UPC	Footnote
83333E 009100	White	Reel	100 ft	612825204169	E
83333E 0091000	White	Reel	1,000 ft	612825204176	E

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

83333E 009100