



Product: <u>83756</u> ☑

Electronic, 6 C #14 Str TC, FEP Ins, OS+TC Brd, Red FEP Jkt, CMP FPLP

Request Sample

Product Description

High Temperature Electronic, 6 Conductor 14AWG (7x22) Tinned Copper, FEP Insulation, Overall Beldfoil®+Tinned Copper Braid(85%) Shield, Red FEP Outer Jacket, CMP FPLP

Technical Specifications

Product Overview

Suitable Applications: fire alarms; extreme high/low temperature environments; indoor/outdoor applications; low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...)

Construction Details

Conductor

Element	No. of Elements	Size	Stranding	Material	
Conductor(s)	6	14 AWG	7x22	TC - Tinned Copper	

Insulation

Element	Material	Nom. Thickness	Color Code
Conductor(s) FEP - Fluorinated Ethylene Propylene	0.016 in (0.41 mm)	Black, White, Red, Green, Orange, Blue

Outer Shield

Shield Type	Material	Coverage
Таре	Bi-Laminate (Alum+Poly)	100%
Braid	Tinned Copper (TC)	85%

Outer Jacket

	Material	Nom. Thickness	Nom. Diameter
	FEP - Fluorinated Ethylene Propylene	0.017 in (0.43 mm)	0.376 in (9.55 mm)
ĺ	Overall Cable Diameter (Nominal): 0.3	376 in (9.55 mm)	

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	2.3 Ohm/1000ft (7.5 Ohm/km)	30 pF/ft (98 pF/m)	52 pF/ft (170 pF/m)	12.5 Amps per Conductor at 25°C

Voltage

UL Voltage Rating
300 V (CMP)

Mechanical Characteristics

Temperature

UL Temperature	Operating
200°C	-70°C to +200°C
Max. Pull Tension	:
Bulk Cable Weigh	t:

Standards and Compliance

Flammability / Reaction to Fire:	NFPA 262
NEC / UL Compliance:	Article 760, Article 800
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes:	Gas Resistant	
140100.	Suo i tosistant	

History

Update and Revision:	Revision Number: 0.366 Revision Date: 11-27-2023

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC	Footnote
83756 002500	Red	Reel	500 ft	612825205722	С

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

83756 002500