



Product: <u>83954</u> ☑

Type TX Thermocouple, 1 Pr #20 Str, FEP Ins Blu, Red, Blue FEP Jkt, 300V CL3P 200C PLTC SUN RES

Product Description

Type TX Thermocouple, 1 Pair 20AWG (7x28) OFHC+Constantan, FEP Insulation Blu, Red Color Code, Blue FEP Outer Jacket, CL3P 200C PLTC SUN RES

Technical Specifications

Product Overview

Suitable Applications: Industrial Control, Raceways Cable trays and ducts, Digital Control, Instruments (4-20ma, 0-10v, ...), low voltage digital control (24v, ...), RTD, control circuits, distributed control system (DCS), programmable logic controller (PLC), Solenoids, Valves, actuators, positioners

Construction Details

Conductor

Element	No. of Elements	Size	Stranding	Material
Conductor(s)	2	20 AWG	7x28	Copper & Constantan

Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Conductor(s)	FEP - Fluorinated Ethylene Propylene	0.01 in (0.25 mm)	0.058 in (1.5 mm)	Blue, Red

Inner Shield

Material No Shield

Outer Shield

Shield Type	Material	Coverage	Drainwire Type	
Tape	Bi-Laminate (Alum+Poly)	100%	22 AWG (7x30) TC	

Outer Jacket

	Material		Nom. Thickness	Nom. Diameter
FEP - Fluorin	inated Ethylene	Propylene	0.012 in (0.30 mm)	0.145 in
Overall Cable (Nominal):	le Diameter	0.145 in		

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR
Copper	10 Ohm/1000ft
Constantan	283 Ohm/1000ft (928 Ohm/km)

Voltage

UL Voltage Rating 300 V

Mechanical Characteristics

Temperature

UL Temperature Operating

-70°C To +200°C

Bend Radius

Stationary Min.	Installation Min.
1.45 in (36.8 mm)	1.45 in

Max. Pull Tension:	41 lbs (19 kg)	
Bulk Cable Weight:	18 lbs/1000ft	

Standards and Compliance

Environmental Suitability:	Indoor, Outdoor, Sunlight Resistance
Flammability / Reaction to Fire:	NFPA 262 (UL 910)
NEC / UL Compliance:	Article 725
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.405 Revision Date: 07-03-2024

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC	Footnote
83954 0061000	Blue, Light	Reel	1,000 ft	612825206057	С

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

83954 0061000