



Product: <u>8410</u> ☑

Microphone Cable, 1 Conductor 25 AWG, TC

Product Description

25 AWG stranded (7x33) composite copper conductor, EPDM rubber insulation, rayon braid + TC braid shield (80% coverage), cotton serve, cotton serve, EPDM rubber jacket.

Technical Specifications

Product Overview

Suitat	ole Application	ns:		Mic	rophone, Musi	cal Instrument			
Phys	ical Char	acteristics (Overal)						
0	- 4								
Condu AWG			N	laterial				Nominal Diameter	No. of Coa
25	Stranded	TC+TCCS - Tinned Copp			pper Covered	Steel (High		0.021 in	1
		Conductivity)						0.0211	•
Condu	uctor Count:			1					
nsulat	tion								
		laterial	Nominal Diameter		III Thickness				
EPDN	1 - Ethylene F	Propylene Diene Monomer	0.154 in	0.058 in					
Outer \$	Shield								
Туре	Mater	ial Coverage [%]							
Braid	Rayon®	80%							
Braid	Tinned Cop	per (TC) 80%							
Jutor	Jacket								
outer		A aterial	Nominal Diameter	Nominal Wa	III Thickness	Separator Mat	erial		
EPDN		Propylene Diene Monomer		0.024 in		Cotton Serve			
Elect	rical Cha	racteristics							
Condu	ctor DCR								
Nomi	nal Conduct	or DCR Nominal Condu	ctor DCR Conductor	r Resistance	Nominal Out	ter Shield DCR	Outer Co	nductor DCR	
45.1 C	Dhm/1000ft	45.1 Ohm/1000ft			5.8 Ohm/100	Oft	5.8 Ohm/	1000ft	
Capaci	itance								
-		Conductor to Shield							
33 pF	/ft								
mnod	anco								
Impeda		ristic Impedance							
•	nal Characte	ristic Impedance							
Nomi 52 Oh	nal Characte m	ristic Impedance							
Nomii 52 Oh Curren	nal Characte Im It								
Nomi 52 Oh Curren Max.	nal Characte im It Recommend	ristic Impedance ed Current [A] Juctor at 25°C							

Voltage

Non-UL Voltage Rating 3000 V DC

Temperature Range

Non-UL Temp Rating:	60°C
Operating Temperature Range:	-30°C To +60°C

Mechanical Characteristics

Bulk Cable Weight:	37 lbs/1000ft
Max. Pull Tension:	60 lbs
Min. Bend Radius/Minor Axis:	2.5 in

Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes	
Plenum/Non-Plenum		
Plenum (Y/N):	No	

Related Part Numbers

10 010500 Black Reel 500 ft 612825206309

Update and Revision:

Revision Number: 0.364 Revision Date: 01-10-2024

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

8410 010500