



**Product:** <u>8675</u> ☑

Electronic, 2 C #14 Str BC, PVC Ins

# Request Sample

# **Product Description**

Electronic, 2 Conductor 14AWG (19x26H) Bare Copper, PVC Insulation

# **Technical Specifications**

## **Product Overview**

Suitable Applications: low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio

### **Construction Details**

#### Conductor

Element	No. of Elements	Size	Stranding	Material
Conductor(s)	2	14 AWG	19x26	BC - Bare Copper

#### Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code	
Conductor(s)	PVC - Polyvinyl Chloride	0.023 in (0.58 mm)	0.122 in (3.10 mm)	Brown, Red	

# Outer Shield

Material No Shield

# Outer Jacket

	Material	Nom. Thickness	Nom. Diameter
	PVC - Polyvinyl Chloride	0.023 in (0.58 mm)	0.168 x 0.29 in
Ī	Overall Cable Diameter (	Nominal): 0.168 x 0.	29 in

# **Electrical Characteristics**

# Electricals

Nom. Conductor DCR	Max. Current
7.06 Ohm/1000ft	8.5 Amps per Conductor at 25°C

# Voltage

Voltage Rating 300 V

# **Mechanical Characteristics**

#### Temperature

UL Temperature	Operating
75°C	-20°C To +75°C

# Bend Radius

Stationary Min.	Installation N	viin.
0.4872 in (12.37 mm)	0.4872 in	
Max. Pull Tension:	9	95 lbs

Bulk Cable Weight: 44 lbs/1000ft
----------------------------------

#### **Standards and Compliance**

European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

### **History**

Update and Revision:	Revision Number: 0.404 Revision Date: 02-15-2024

#### **Part Numbers**

#### Variants

Item #	Color	Putup Type	Length	UPC	Footnote
8675 060500	Chrome	Reel	500 ft	612825214021	С

#### © 2024 Belden, Inc.

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

8675 060500