



Product: <u>9116P</u> ☑

Broadband Coax, Series 6, 18 AWG Solid BCCS, Foil + 60% AL Braid, Flamarrest® Jkt, CMP

Product Description

Broadband Coax, Series 6, 18 AWG Solid Bare Copper Covered Steel Conductor, FEP Insulation, Foil + 60% Aluminum Braid Shield, Flamarrest® Jacket, CMP

Technical Specifications

Product Overview

| Suitable Applications: | Broadban | sion (CATV), RF | drop cal | ble, Over-Th | ne-Air (OTA) a | antennas | | | |
|--------------------------------------|------------------------------|-----------------|---------------|-------------------|------------------|----------|--|--|--|
| Construction Detai | Is | | | | | | | | |
| RG Type: | 6 | | | | | | | | |
| Conductor | | | | | | | | | |
| Size Stranding No | m. Diameter | Materia | ıl | | | | | | |
| 18 AWG Solid 0.0 | 40 in BCCS | 6 - Bare Copper | Covered Steel | ľ | | | | | |
| Materia FEP - Fluorinated Ethylen | | | ion Diameter | Color Co White | de | | | | |
| | e i ropyiene (i eani) | 0.170 11 (4.02 | , | · · · · · · | | | | | |
| | | | | | | | | | |
| Duter Shield | | | | | | | | | |
| | e Mater | ial | Material Trad | e Name | Coverage | | | | |
| Duter Shield | e Mater Tri-Laminate (Alu | | | e Name | Coverage 100% | | | | |

| Material | Nom. Diameter |
|---------------------------|-----------------------|
| PVC - Polyvinyl Chloride | 0.235 in (5.97 mm) |
| Overall Cable Diameter (I | Nominal): 0.235 in (5 |

Electrical Characteristics

Return Loss (RL)

| Frequency | Min. Structural Return Loss |
|--------------|-----------------------------|
| 5 - 1000 MHz | 20 dB |

Attenuation

| Frequency | Nom. Attenuation |
|-----------|------------------|
| 1 MHz | 0.3 dB/100ft |
| 10 MHz | 0.7 dB/100ft |
| 50 MHz | 1.6 dB/100ft |
| 100 MHz | 2.1 dB/100ft |
| 200 MHz | 2.9 dB/100ft |
| 400 MHz | 4.3 dB/100ft |
| 700 MHz | 6.1 dB/100ft |
| 750 MHz | 6.4 dB/100ft |

| 900 MHz | 7.1 dB/100ft |
|----------|--------------|
| 1000 MHz | 7.6 dB/100ft |

Electricals

| Nom. Conductor DCR | Nom. Outer Shield DCR | Nom. Capacitance Cond-to-Shield | Nom. Characteristic Impedance | Nom. Velocity of Prop. |
|--------------------|--------------------------|---------------------------------|-------------------------------|------------------------|
| 28 Ohm/1000ft | 9 Ohm/1000ft (30 Ohm/km) | 16.3 pF/ft (53.5 pF/m) | 75 Ohm | 83% |

Voltage

UL Voltage Rating 300 V (CMP)

Mechanical Characteristics

| Operating -20°C to +75°C | |
|---|---------------------------------------|
| Bend Radius | |
| Installation Min. | |
| 3 in (76 mm) | |
| Max. Pull Tension: | 150 lbs (68 kg) |
| Bulk Cable Weight: | 25 lbs/1000ft |
| | |
| Standards and Complian | |
| Environmental Suitability: | Indoor - Plenum, Indoor |
| | |
| Environmental Suitability: | Indoor - Plenum, Indoor |
| Environmental Suitability: Sustainability: | Indoor - Plenum, Indoor CA Prop 65 |

History

Update and Revision:

APAC Compliance:

Non-Plenum Number:

Revision Number: 0.473 Revision Date: 04-29-2024

China RoHS II (GB/T 26572-2011)

9116, 9116R

Part Numbers

Variants

| ltem # | Color | Putup Type | Length | UPC | Footnote |
|----------------|---------|------------|----------|--------------|----------|
| 9116P 010U500 | Black | UnReel | 500 ft | 612825224501 | |
| 9116P 0101000 | Black | Reel | 1,000 ft | 612825224464 | С |
| 9116P 010U1000 | Black | UnReel | 1,000 ft | 612825224471 | |
| 9116P 8771000 | Natural | Reel | 1,000 ft | 612825224495 | С |
| 9116P 877U1000 | Natural | UnReel | 1,000 ft | 612825224525 | |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

9116P 877U1000 9116P 8771000 9116P 010U1000 9116P 010U500 9116P 0101000