

Product: <u>9201</u> 2

52 Ohm, RG58, 20 AWG



Product Description

RG-58/U type, 20 AWG solid .033" bare copper conductor, polyethylene insulation, bare copper braid shield (80% coverage), PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

ondu	ctor					
AWG	Stranding	Material	Nominal Diameter	No. of Coax		
20	Solid	BC - Bare Copper	0.033 in	1		
Condu	ictor Count:			1		
sulat	ion					
Μ	laterial	Nominal Diameter				
PE - F	olyethylene	0.116 in				
uter S	Shield Mater	ial	_			
Гуре	Materia		%1			
Braid	Bare Coppe					
uter .	Jacket Mater	rial				
	Material	Nominal Dia	ameter			
PVC -	Polyvinyl Ch	loride 0.193 in				
leat	rical Cha	racteristics				
ieci		racteristics				
ondu	ctor DCR					
Nor	ninal Condu DCR	ctor Nominal C	onductor DCR Con	ductor Resistance	Nominal Outer Shield DCR	Outer Conductor D
	m/1000ft	10 Ohm/10	0.064		5.5 Ohm/1000ft	5.5 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Shield
28.5 pF/ft

Inductance

Nominal Inductance

Impedance

Nominal Characteristic Impedance 52 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.3 dB/100ft
10 MHz	1.1 dB/100ft

50 MHz	2.5 dB/100ft
100 MHz	3.8 dB/100ft
200 MHz	5.6 dB/100ft
400 MHz	8.4 dB/100ft
700 MHz	11.7 dB/100ft
900 MHz	13.7 dB/100ft
1000 MHz	14.5 dB/100ft

Delay

Nominal Delay

1.54 ns/ft

Voltage

Non-UL Voltage Rating 1400 V RMS

Temperature Range

Non-UL Temp Rating:	75°C
Operating Temp Range:	-40°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	23 lbs/1000ft
Max. Pull Tension:	37 lbs
Min Bend Radius/Minor Axis:	2 in

Standards

CPR Euroclass:	Eca
RG Type:	58/U Type

Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes

Flammability, LS0H, Toxicity Testing

IEC Flammability:

IEC 60332-1-2

Plenum/Non-Plenum

Plenum (Y/N):

Part Number

Variants				
Item #	Color	Putup Type	Length	UPC
9201 010500	Black	Reel	500 ft	612825225188
9201 010U500	Black	UnReel	500 ft	612825225225
9201 0101000	Black	Reel	1,000 ft	612825225218
9201 010U1000	Black	UnReel	1,000 ft	612825225195
Footnote:				C -

No

History

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: 9201 010U500 9201 0101000 9201 010500 9201 010U1000