



Product: <u>9892</u> ☑

Transceiver 10BASE5, #20-4pr, FPO, PVC Jkt, CM

Product Description

IEEE 802.3 Ethernet Transceiver 10BASE5, 20 AWG stranded (7x28) tinned copper conductors, Datalene® insulation, 4 twisted pairs, overall polyester isolation tape + a tinned copper braid shield (95% coverage), drain wire, PVC jacket.

Technical Specifications

Product Overview Suitable Applications: IEEE 802.3 Transceiver Cable **Construction Details** Conductor Element No. of Elements Size Stranding Material Pair(s) 4 20 7x28 TC - Tinned Copper Insulation Material Nom. Thickness Nom. Insulation Diameter Color Code Notes PE - Polyethylene (Foam) 0.02 in (0.51 mm) 0.077 in (2.0 mm) Gray & White, Yellow & Orange, Blue & Green, Black & Red HDPE Inner Shield Shield Type Material Coverage Таре Bi-Laminate (Alum+Poly) 100% Outer Shield Shield Type Material Coverage Drainwire Type Braid Tinned Copper (TC) 95% 22 AWG (7x30) TC Outer Jacket Material Nom. Thickness Nom. Diameter PVC - Polyvinyl Chloride 0.035 in (0.89 mm) 0.398 in (10.1 mm) **Electrical Characteristics**

Electricals

Nom. Conductor DCR	Nom. Inner Shield DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Characteristic Impedence	Nom. Velocity of Prop.	Max. Current
11.3 Ohm/1000ft	2.03 Ohm/1000ft (6.66 Ohm/km)	16.7 pF/ft (54.8 pF/m)	29.5 pF/ft (96.8 pF/m)	78 Ohm	78%	2.66 Amps per Conductor at 25°C

Voltage

UL Voltage Rating 30 V (AWM 2919), 300 V (CL2)

Mechanical Characteristics

UL Temperature	Operating	
80°C	-40°C To +80°C	

Bend Radius

3.98 in (101 mm) 3.98 in (101 mm)						
Max. Pull Tension:	175 lbs (79.4 kg)					
Bulk Cable Weight:	93 lbs/1000ft					

Standards and Compliance

Stationary Min. Installation Min.

UL1685 UL Loading, FT4, IEC 60332-1-2
CPR Euroclass: Eca
Article 725, Article 800, CL2, CM
AWM 2919
CM
IEEE 802.3
EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UKCA Mark
China RoHS II (GB/T 26572-2011)
DEC Part No. 17-01320-00
89901

History

Update and Revision:

Revision Number: 0.476 Revision Date: 02-03-2025

Part Numbers

Variants

Item #	Color	UPC	Footnote
9892 0061000	Blue, Light	612825260103	С
9892 006500	Blue, Light	612825260110	С
9892 0065000	Blue, Light	612825260127	С

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

9892 0061000 9892 006500 9892 0065000