



## Product: ACA22-M12 (EEC) right angled ☑

Auto-configuration adapter 512 MB, M12 (USB 2.0), EEC, right angled

## **Product Description**

Auto-configuration adapter 512 MB, right angled with M12 (USB 2.0) connection and extended temperature range, saves two different versions of configuration data and operating software from the connected switch. It enables managed switched to be easily comissioned and quickly replaced.

## **Technical Specifications**

## **Product description**

Туре:	ACA22-M12 EEC
Part Number:	942125002

### **Software**

Diagnostics:	writing to ACA, reading from ACA, writing/reading not OK (display using LEDs on the switch)	
Configuration:	via USB interface of the switch and via SNMP/Web	

### **Ambient conditions**

MTBF:	228 years (MIL-HDBK-217F)
Operating temperature:	-40-+70 °C
Storage/transport temperature:	-40-+85 °C
Relative humidity (non-condensing):	10-95 %

## **Mechanical construction**

Weight:	70 g
Mounting:	plug-in module
Protection class:	IP67

## **Mechanical stability**

IEC 60068-2-6 vibration:	1 g, 8,4 Hz - 200 Hz, 30 cycles
IEC 60068-2-27 shock:	15 g, 11 ms duration, 18 shocks

## **EMC** interference immunity

EN 61000-4-3 electromagnetic field:	10 V/m

## **EMC** emitted immunity

EN 55022:	EN 55022

## **Approvals**

Safety of industrial control equipment:	cUL 508			
Hazardous locations:	ISA 12.12.01 Class 1 Div. 2 ATEX Zone 2			
Shipbuilding:	Germanischer Lloyd			
Transportation:	EN50121-4			

## Scope of delivery and accessories

Scope of delivery:	device, operating manual	

### **Further Instructions**

Product Documentation:	https://www.doc.hirschmann.com
Certificates:	https://www.doc.hirschmann.com/certificates.html

#### Variants

Item #	Туре	
942125002	ACA22-M12 (EEC) right ang	ngled
Update and	d Revision:	Revis

#### © 2022 Belden, Inc

### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Hirschmann:

ACA22-M12 (EEC) RIGHT ANGLED