Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

AX102267 Faceplates and Panels - KeyConnect Decora Adapter 4 Port

989 1771		
		For more Informatio
i i Agé		please call
	1 23%	1-800-Belden1
		AND COMPLY
General Description:		
KeyConnect Decora Adapter	4 Port	
Jsage (Overall)		
Suitable Applications:	- Compatible with a variety of modules that ar 4800,3600, 2400 and 1200.	e suitable for use with Belden IBDN Systems 10GX,
Related Parts:	- Compatible with 10GX, CAT6+ and CAT5E	KeyConnect UTP and Multimedia Modules
Physical Characteristics (Connectiv	vity)	
Capacity		
Max. Capacity:	4 Inserts	
Access		
Front Connection:	Flush	
Dimensions Dimensions:		
Height (mm) Width (mm) Depth (mm) 106.680 37.084 6.604		
Materials		
Materials:		
Description Material Deco Adapter Plastic - UL94V-0		
Color		
Color:	Black	
Weight		
Weight:	0.018 kg	
Included Parts		
Included Parts Included Parts:	0.018 kg installation sheet, screws, blank	
Included Parts Included Parts: Packaging	installation sheet, screws, blank	
Included Parts Included Parts:		
Included Parts Included Parts: Packaging Packaging:	installation sheet, screws, blank Individually packaged in a plastic bag.	
Included Parts Included Parts: Packaging Packaging:	installation sheet, screws, blank Individually packaged in a plastic bag.	
Included Parts Included Parts: Packaging Packaging: Iechanical Characteristics (Connect	installation sheet, screws, blank Individually packaged in a plastic bag.	
Included Parts Included Parts: Packaging Packaging: Aechanical Characteristics (Connec Footprint/Type:	installation sheet, screws, blank Individually packaged in a plastic bag. Individually packaged in a plastic bag.	
Included Parts Included Parts: Packaging Packaging: Mechanical Characteristics (Connec Footprint/Type: Storage Temperature Range:	installation sheet, screws, blank Individually packaged in a plastic bag. Activity) KeyConnect -40°C To +70°C	
Included Parts Included Parts: Packaging Packaging: Aechanical Characteristics (Connect Footprint/Type: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range:	installation sheet, screws, blank Individually packaged in a plastic bag. ctivity) KeyConnect -40°C To +70°C -10°C To +60°C -10°C To +60°C	
Included Parts Included Parts: Packaging Packaging: Aechanical Characteristics (Connect Footprint/Type: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Applicable Specifications and Ager Applicable Standards & Environmental	installation sheet, screws, blank Individually packaged in a plastic bag. Ctivity) KeyConnect -40°C To +70°C -10°C To +60°C -10°C To +60°C -10°C To +60°C Anticipation of the state of the stateo	
Included Parts Included Parts: Packaging Packaging: Mechanical Characteristics (Connect Footprint/Type: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Applicable Specifications and Ager	installation sheet, screws, blank Individually packaged in a plastic bag. ctivity) KeyConnect -40°C To +70°C -10°C To +60°C -10°C To +60°C and a screen scree	
Included Parts Included Parts: Packaging Packaging: Aechanical Characteristics (Connect Footprint/Type: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Applicable Specifications and Ager Applicable Standards & Environmental	installation sheet, screws, blank Individually packaged in a plastic bag. Antivity) KeyConnect -40°C To +70°C -10°C To +60°C -10°C To +60°C Antivity Programs Yes	
Included Parts Included Parts: Packaging Packaging: Aechanical Characteristics (Connect Footprint/Type: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Applicable Specifications and Ager Applicable Standards & Environmental EU Directive 2002/95/EC (RoHS):	installation sheet, screws, blank Individually packaged in a plastic bag. Antivity) KeyConnect -40°C To +70°C -10°C To +60°C -10°C To +60°C Antivity Programs Yes	
Included Parts Included Parts: Packaging Packaging: Aechanical Characteristics (Connect Footprint/Type: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Operating Temperature Range: Applicable Specifications and Ager Applicable Standards & Environmental EU Directive 2002/95/EC (RoHS): EU RoHS Compliance Date (mm/dd/yyyy)	installation sheet, screws, blank Individually packaged in a plastic bag. Activity) KeyConnect -40°C To +70°C -10°C To +60°C -10°C To +60°C -10°C To +60°C -10°C To +60°C Programs Yes): 07/01/2006	
Included Parts Included Parts: Packaging Packaging: Aechanical Characteristics (Connect Footprint/Type: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Operating Temperature Range: Applicable Specifications and Ager Applicable Standards & Environmental EU Directive 2002/95/EC (RoHS): EU RoHS Compliance Date (mm/dd/yyyy) MII Order #39 (China RoHS): Safety Listing:	installation sheet, screws, blank Individually packaged in a plastic bag. Activity) KeyConnect -40°C To +70°C -10°C To +60°C -10°C To +60°C -10°C To +60°C Activity Programs Yes): 07/01/2006 Yes	
Included Parts Included Parts: Packaging Packaging: Mechanical Characteristics (Connect Footprint/Type: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Operating Temperature Range: Applicable Specifications and Ager Applicable Standards & Environmental EU Directive 2002/95/EC (RoHS): EU RoHS Compliance Date (mm/dd/yyyy) MII Order #39 (China RoHS):	installation sheet, screws, blank Individually packaged in a plastic bag. Activity) KeyConnect -40°C To +70°C -10°C To +60°C -10°C To +60°C -10°C To +60°C Activity Programs Yes): 07/01/2006 Yes	
Included Parts Included Parts: Packaging Packaging: Alechanical Characteristics (Connect Footprint/Type: Storage Temperature Range: Installation Temperature Range: Operating Temperature Range: Operating Temperature Range: Applicable Specifications and Ager Applicable Standards & Environmental EU Directive 2002/95/EC (RoHS): EU RoHS Compliance Date (mm/dd/yyyy) MII Order #39 (China RoHS): Safety Listing: Suitability	installation sheet, screws, blank Individually packaged in a plastic bag. ctivity) KeyConnect -40°C To +70°C -10°C To +60°C -10°C To +60°C -10°C To +60°C Programs Yes): 07/01/2006 Yes Bi-national Standard Listed Yes	

Notes: For proper installation refer to installation guide included with the product or visit our web site at http://www.belden.com

Detailed Specifications & Technical Data





AX102267 Faceplates and Panels - KeyConnect Decora Adapter 4 Port

Description	Almond	Elec. White	Black
KeyConnect Decora Adapter 2-Ports	AX104111	AX104112	AX104113
KeyConnect Decora Adapter 4-Ports	AX103927	AX102266	AX102267
KeyConnect Decora Adapter 6-Ports	AX104117	AX104118	AX104119

Itom #	Dutur	Chin Waight	Color	Notoo	Itom Dooo	
item #	Putup	Ship Weight	Color	Notes	Item Desc	

Revision Number: 0 Revision Date: 06-05-2009

© 2017 Belden, Inc All Rights Reserved

All Rights Reserved. Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information and belief at the date of its publication. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided on yearranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: AX102267