Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



AX102660 Faceplates and Panels - KeyConnect Faceplates 1-Port w/ID Windows Single-Gang







For more Information please call

1-800-Belden1



Suitable Applications: S02,040,1200, fibra into avariety of modules that are suitable for use with Beiden IBON Systems 10CX, 4800, 8800, 880, 880, 840, 1200, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800, 1800	Seneral Description:	
Suitable Applications: Related Parts: Suitable Applications: Suitab	KeyConnect Faceplates 1-Port, w/ ID Win	dows, Single Gang, Flush
Related Parts:	Jsage (Overall)	
and Coax Connectors Capacity Max. Capacity: 1-port Access Front Connection: Flush Dimensions Dimensions Dimensions Materials: Description Material Plate Pastic - ULMAY-D Color: Elec. White Weight 0.027 kg Included Parts Included Parts: 6-32 screw, carton label, clear window Packaging Packaging Packaging Packaging Packaging Packaging Packaging: Individually packaged in a plastic bag. Mechanical Characteristics (Connectivity) Connector/Hardware Retention: 88.994 N Storage Temperature Range: 40°C To +70°C Installation Temperature Range: 10°C To +80°C Operating Temperature	Suitable Applications:	
Access Frot Connection: Flush Dimensions: Note Marcials Materials	Related Parts:	
Max. Capacity: 1-port		
Front Connection: Flush Flush		1-port
Dimensions Dimensions: Dimensions: Height (mm) Width (mm) Depth (mm) 114.300 60.850 6.604 Materials: Description Material Plate Plastic - UL-94V-0 Color Color: Elec. White Weight Weight 0.027 kg Included Parts 6.32 screw, carton label, clear window Packaging Packaging: Individually packaged in a plastic bag. Mechanical Characteristics (Connectivity) Connector/Hardware Retention: 88.964 N Storage Temperature Range: 40°C To +70°C Installation Temperature Range: -10°C To +60°C Operating Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Applicable Specifications and Agency Compliance (Overall) Mil Order #39 (China RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006 Mil Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed	Access	
	Front Connection:	Flush
Height (mm) Width (mm) Depth (mm)		
Materials: Description Material Plate Plastic - UL94V-0 Color: Elec. White Weight Weight O.027 kg Included Parts O.027 kg Included Parts: O.32 screw, carton label, clear window Packaging Packaging Individually packaged in a plastic bag. Wechanical Characteristics (Connectivity) Connector/Hardware Retention: 88.964 N Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C Operating Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006 Mill Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed	Height (mm) Width (mm) Depth (mm)	
Description Material Piete Plastic - UL94V-0 Color: Elec. White Weight: 0.027 kg Included Parts Included Parts: 6-32 screw, carton label, clear window Packaging Packaging: Individually packaged in a plastic bag. Mechanical Characteristics (Connectivity) Connector/Hardware Retention: 88.964 N Storage Temperature Range: 40°C To +70°C Installation Temperature Range: -10°C To +60°C Operating Temperature Range: -10°C To +60°C Applicable Spacifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mmidd/yyyy): 07/1/2006 Mill Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed		
Weight: Weight: Weight: 0.027 kg Included Parts Included Parts: 6-32 screw, carton label, clear window Packaging Packaging: Individually packaged in a plastic bag. Mechanical Characteristics (Connectivity) Connector/Hardware Retention: 88.964 N Storage Temperature Range: 40°C To +70°C Installation Temperature Range: -10°C To +60°C Operating Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): Yes EU ROHS Compliance Date (mm/dd/yyyy): 07/01/2006 Mill Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed	Description Material	
Weight Weight: 0.027 kg Included Parts Included Parts: 6-32 screw, carton label, clear window Packaging Packaging: Individually packaged in a plastic bag. Mechanical Characteristics (Connectivity) Connector/Hardware Retention: 88.964 N Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C Operating Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006 MII Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed	Color	
Weight: 0.027 kg Included Parts Included Parts: 6-32 screw, carton label, clear window Packaging Packaging: Individually packaged in a plastic bag. Mechanical Characteristics (Connectivity) Connector/Hardware Retention: 88.964 N Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C Operating Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006 Mill Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed	Color:	Elec. White
Included Parts Included Parts: 6-32 screw, carton label, clear window Packaging Packaging: Individually packaged in a plastic bag. Mechanical Characteristics (Connectivity) Connector/Hardware Retention: 88.964 N Storage Temperature Range: 40°C To +70°C Installation Temperature Range: -10°C To +60°C Operating Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Applicable Specifications and Agency Compliance (Overall) EU Directive 2002/95/EC (RoHS): Yes EU ROHS Compliance Date (mm/dd/yyyy): 07/01/2006 Mill Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed		
Included Parts: 6-32 screw, carton label, clear window Packaging Packaging: Individually packaged in a plastic bag. Mechanical Characteristics (Connectivity) Connector/Hardware Retention: 88.964 N Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C Operating Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Applicable Specifications and Agency Compliance (Overall) EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006 Mill Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed	-	0.027 kg
Packaging: Individually packaged in a plastic bag. Mechanical Characteristics (Connectivity) Connector/Hardware Retention: 88.964 N Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C Operating Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006 Mill Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed		6-32 screw, carton label, clear window
Packaging: Individually packaged in a plastic bag. Mechanical Characteristics (Connectivity) Connector/Hardware Retention: 88.964 N Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C Operating Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006 Mill Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed	Packaging	
Connector/Hardware Retention: Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C Operating Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): O7/01/2006 Mill Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed		Individually packaged in a plastic bag.
Storage Temperature Range: Installation Temperature Range: -10°C To +60°C Operating Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): O7/01/2006 Mill Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed	Mechanical Characteristics (Connectivity)	
Installation Temperature Range: -10°C To +60°C Operating Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006 Mill Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed	Connector/Hardware Retention:	88.964 N
Operating Temperature Range: -10°C To +60°C Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 7//01/2006 MII Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed	Storage Temperature Range:	-40°C To +70°C
Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006 MII Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed	Installation Temperature Range:	-10°C To +60°C
Applicable Standards & Environmental Programs EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): MII Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed	Operating Temperature Range:	-10°C To +60°C
EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006 MII Order #39 (China RoHS): Yes Safety Listing: Bi-national Standard Listed Suitability		e (Overall)
MII Order #39 (China RoHS): Safety Listing: Bi-national Standard Listed Suitability	EU Directive 2002/95/EC (RoHS):	Yes
Safety Listing: Bi-national Standard Listed Suitability	EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006
Suitability	MII Order #39 (China RoHS):	Yes
	Safety Listing:	Bi-national Standard Listed
		Yes

Notes: For proper installation refer to Installation Guide PX103826. Visit our web site at http://www.belden.com

Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



AX102660 Faceplates and Panels - KeyConnect Faceplates 1-Port w/ID Windows Single-Gang

Product Family

Part Numbers:

Item Number	Stainless Steel	Dark Gray	Almond	Black	lvory	Elec. White	Gray
1-Port w/ ID Windows Single-gang	AX104230	-	AX103922	AX104160	AX104565	AX102660	AX107021
2-Port w/ ID Windows Single-gang	AX104231	AX104455	AX103923	AX104161	AX104197	AX102655	AX107022
3-Port w/ ID Windows Single-gang	-	-	AX103924	AX104162	-	AX102661	-
4-Port w/ ID Windows Single-gang	AX104232	AX104464	AX102248	AX104163	AX104198	AX102249	AX107023
6-Port w/ ID Windows Single-gang	AX104233	-	AX102250	AX104164	AX104199	AX102251	AX107024
4-Port w/ ID Windows Double-gang	AX104479	-	-	-	-	-	-
6-Port w/ ID Windows Double-gang	AX104480	AX106594	AX102670	AX104165	AX104566	AX102671	AX107025
12-Port w/ ID Windows Double-gang	AX104234	-	AX102256	AX104166	AX104200	AX102257	-
1-Port Single-gang	AX102006	-	-	-	-	-	-
2-Port Single-gang	AX102007	-	-	-	-	-	-
4-Port Single-gang	AX102009	-	-	-	-	-	-
6-Port Single-gang	AX102010	-	-	-	-	-	-
6-Port Double-gang	AX102012	-	-	-	-	-	-
12-Port Double-gang	AX102013	-	-	-	-	-	-
Wall Mount Phone Plate	AX104126	-	-	-	-	AX102902	-
Single-gang Back Box 1.89 in.	-	-	AX104127	-	-	AX102657	-
Double-gang Back Box 1.89 in.	-	-	AX104130	AX106684	-	AX104131	AX106685

Put Ups and Colors:

Item #	#	Putup	Ship Weight	Color	Notes	Item Desc
AX102	2660	1 EA	0.028 KG			KCONN FACEPLATE 1-P SG WHI

Revision Number: 1 Revision Date: 10-18-2016

© 2017 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

AX102660