

B9B045 Fiber - Distribution Cable - Plenum

For more Information
please call

1-800-Belden1

**General Description:**

FiberExpress Distribution Cable, 6-Fiber, OM1 OFNP, Tight Buffer, Indoor Rated with Orange Jacket, High flexibility for backbone and horizontal applications.

Physical Characteristics (Overall)

| | |
|-----------------------------|-------------------|
| Fiber Type: | 62.5 Micron (OM1) |
| Number of Fibers: | 6 |
| Core Diameter: | 62.5 |
| Clad Diameter: | 125 |
| Primary Coating Diameter: | 250 |
| Secondary Coating Diameter: | 900 |
| Buffer Tube Material: | Thermoplastic |

Inner Jacket

| | |
|-----------------------|-----|
| Inner Jacket Ripcord: | Yes |
|-----------------------|-----|

Outer Jacket**Outer Jacket Material:****Outer Jacket Material**

PVC - Polyvinyl Chloride

| | |
|---------------------|--------|
| Outer Jacket Color: | Orange |
|---------------------|--------|

Strength Member

| | |
|---------------------------|-------------|
| Strength Member Material: | Aramid Yarn |
|---------------------------|-------------|

Overall Cable

| | |
|---------------------------|-----------|
| Overall Nominal Diameter: | 0.170 in. |
|---------------------------|-----------|

Mechanical Characteristics (Overall)

| | |
|---|-----------------|
| Storage Temperature Range: | -40°C To +75°C |
| Installation Temperature Range: | 0°C To +70°C |
| Operating Temperature Range: | 0°C To +70°C |
| Bulk Cable Weight: | 13 lbs/1000 ft. |
| Min. Bend Radius/Minor Axis: | 3 in. |
| Min. Bend Radius for Long Term Application: | 2 in. |
| Max. Load for Installation: | 100 lbs. |
| Max. Load for Long Term Application: | 30 lbs. |

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

| | |
|---------------------------------------|------------|
| NEC/(UL) Specification: | OFNP |
| CEC/C(UL) Specification: | OFNP |
| EU Directive 2011/65/EU (RoHS II): | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 08/01/2008 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |

B9B045 Fiber - Distribution Cable - Plenum

| | |
|-----------------------------|-----|
| MII Order #39 (China RoHS): | Yes |
|-----------------------------|-----|

Flame Test

| | |
|-----------------|--------------|
| UL Flame Test: | UL910 Plenum |
| CSA Flame Test: | FT6 |

Suitability

| | |
|------------------------|-----|
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | No |
| Suitability - Aerial: | No |
| Suitability - Burial: | No |
| Sunlight Resistance: | No |

Plenum/Non-Plenum

| | |
|---------------|-----|
| Plenum (Y/N): | Yes |
|---------------|-----|

Optical Characteristics (Overall)

| | |
|---|------------|
| Maximum Attenuation @ 850nm: | 3.5 dB/km |
| Maximum Attenuation @ 1300nm: | 1.2 dB/km |
| Minimum Bandwidth @ 850nm: | 200 MHz*km |
| Minimum Bandwidth @ 1300nm: | 600 MHz*km |
| Maximum Gigabit Ethernet Length @ 850nm: | 300 meters |
| Maximum Gigabit Ethernet Length @ 1300nm: | 550 meters |

Fiber Coding MLT EMEA:

| Fiber/Tube No. | Color |
|----------------|--------|
| 1 | Blue |
| 2 | Orange |
| 3 | Green |
| 4 | Brown |
| 5 | Slate |
| 6 | White |

Related Documents:

[Distribution Cable.pdf](#) - Distribution Cable technical information.

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|--------|-------|-------------|-------|-------|-----------|
|--------|-------|-------------|-------|-------|-----------|

Revision Number: 2 Revision Date: 08-18-2015

© 2017 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Belden Wire & Cable:](#)

[B9B045](#)