Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



E503003 Cord Sets - DataTuff® Cat 5e IP20 RJ45 Cord Set



For more Information please call

1-800-Belden1



General Description:

3 meter (9.8 ft.), Unshielded with stranded conductors (ref: Belden Bonded-Pair Cable 7924A). Cable Rating NEC: CMR, CMX-Outdoor. CEC: CMR FT4. MSHA.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| EU Directive 2002/95/EC (RoHS): | Yes |
|---------------------------------------|------------|
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2006 |
| MII Order #39 (China RoHS): | EUP 50 |

Notes (Overall)

Notes: For additional information about this product, visit our web site at http://www.belden.com

| able | | | |
|--|---|--|--|
| Description: | 4 pair, 24 AWG Stranded (7x32) Tinned Copper, Polyolefin Insulation, Bonded pairs, Industrial Grade PVC, Oil Res, Sun Res, CMR, CMX-Outdoor, FT4. | | |
| Part Number: | 7924A | | |
| Shielding: | Unshielded | | |
| Electrical Performance: | Category 5e Patch | | |
| Maximum Operating Voltage: | 300 V RMS | | |
| Applicable Standards: ANSI/TIA/EIA-568-C.2, ISO/IEC 11801, UL 1666 Riser | | | |
| • • | · · · · · · · · · · · · · · · · · · · | | |

Connectors

| Connector Type: Cat 5e Sealing: Suitable for IP20 Connector Interface: IEC 60603-7 Shielding: Unshielded Electrical Performance: Cat 5e Maximum Operating Voltage: 300 V RMS | Description: | RJ45 plugs. Suitable for use in IP20 applications | | | |
|--|----------------------------|--|--|--|--|
| Connector Interface: IEC 60603-7 Shielding: Unshielded Electrical Performance: Cat 5e Maximum Operating Voltage: 300 V RMS | Connector Type: | Cat 5e | | | |
| Shielding: Unshielded Electrical Performance: Cat 5e Maximum Operating Voltage: 300 V RMS | Sealing: | Suitable for IP20 | | | |
| Electrical Performance: Cat 5e Maximum Operating Voltage: 300 V RMS | Connector Interface: | IEC 60603-7 | | | |
| Maximum Operating Voltage: 300 V RMS | Shielding: | Unshielded | | | |
| | Electrical Performance: | Cat 5e | | | |
| | Maximum Operating Voltage: | 300 V RMS | | | |
| Applicable Standards: ANSI/TIA/EIA-568-C.2, ISO/IEC 11801, EtherNet/IP Specification | Applicable Standards: | ANSI/TIA/EIA-568-C.2, ISO/IEC 11801, EtherNet/IP Specification | | | |

Assembly

| · · · · · · · · · · · · · · · · · · · | |
|---------------------------------------|----------------|
| Part Number: | E503003 |
| Electrical Performance: | Cat 5e Patch |
| Maximum Operating Voltage: | 300 V RMS |
| Storage Temperature Range: | -40°C To +70°C |
| Installation Temperature Range: | -10°C To +60°C |
| Operating Temperature Range: | -10°C To +60°C |
| | |

Page 1 of 2 01-30-2019

Detailed Specifications & Technical Data





E503003 Cord Sets - DataTuff® Cat 5e IP20 RJ45 Cord Set

Applicable Standards: ANSI/TIA/EIA-568-C.2, ISO/IEC 11801, UL 1863 and CSA-22.2 No. 233

Shielding: Unshielded

Length: 3 meter (9.8 ft.)

Notes: US Patent #'s 5, 606, 151; 5, 734, 126. EtherNet/IP is a trademark of ControlNet International, Ltd. under license by Open DeviceNet Vendor Association, Inc.

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|-----------------|-------|-------------|-------|-------|--------------------------------|
| E503003 002S1 | 1 EA | 1.231 LB | RED | | CORDSET IP20 C5E UTP ST 3M RED |
| E503003 002S1-T | 1 EA | 1.231 LB | | | CORDSET IP20 C5E UTP ST 3M RED |
| E503003 010S1 | 1 EA | 0.610 LB | BLACK | | CORDSET IP20 C5E UTP ST 3M BK |

Revision Number: 0 Revision Date: 12-13-2013

© 2019 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2 01-30-2019

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: E503003 010B36 E503003 010S1