



Product: <u>RPS 260/PoE EEC</u> ☑

48 - 56 V DC rail power supply unit

Product Description

Din-Rail PoE power supply, 260 W output power, 48 V DC output voltage, 100-240 V AC input voltage, operating temperature -25 °C up to +70 °C

Technical Specifications

Product description

Туре:	RPS 260/PoE EEC	
Description:	48 - 56 V DC rail power supply unit	
Part Number:	942200001	
More Interfaces		
Voltage input:	1 x terminal block, 3-pin	
Voltage output:	1 x terminal block, 5-pin	
Power requirements		
Current consumption:	2.32A / 120VAC 1.20A / 230VAC	
Input voltage:	AC 100-240V, DC 110-150V	
Operating Voltage:	AC 100-240V, DC 110-150V	
Output current:	6.0A/48V/ up to 45°C 5.15A/56V/ up to 45°C	
Redundancy functions:	Power supply units can be connected in parallel	
	A A	
Activation Current: Power Output Output voltage:	9 A 48 - 56 V DC (typ. 48 V) externally adjustable	
	9 A 48 - 56 V DC (typ. 48 V) externally adjustable	
Power Output		
Power Output Output voltage:		
Power Output Output voltage: Software	48 - 56 V DC (typ. 48 V) externally adjustable	
Power Output Output voltage: Software Diagnostics:	48 - 56 V DC (typ. 48 V) externally adjustable	
Power Output Output voltage: Software Diagnostics: Ambient conditions	48 - 56 V DC (typ. 48 V) externally adjustable	
Power Output Output voltage: Software Diagnostics: Ambient conditions MTBF:	48 - 56 V DC (typ. 48 V) externally adjustable LED and relay contact 509000 h (230VAC)	
Power Output Output voltage: Software Diagnostics: Ambient conditions MTBF: Operating temperature:	48 - 56 V DC (typ. 48 V) externally adjustable LED and relay contact 509000 h (230VAC) -25-+70 °C	
Power Output Output voltage: Software Diagnostics: Ambient conditions MTBF: Operating temperature: Storage/transport temperature: Relative humidity (non-condensing):	48 - 56 V DC (typ. 48 V) externally adjustable LED and relay contact 509000 h (230VAC) -25-+70 °C -40-+85 °C	
Power Output Output voltage: Software Diagnostics: Ambient conditions MTBF: Operating temperature: Storage/transport temperature:	48 - 56 V DC (typ. 48 V) externally adjustable LED and relay contact 509000 h (230VAC) -25-+70 °C -40-+85 °C	
Power Output Output voltage: Software Diagnostics: Ambient conditions MTBF: Operating temperature: Storage/transport temperature: Relative humidity (non-condensing): Mechanical construction	48 - 56 V DC (typ. 48 V) externally adjustable LED and relay contact 509000 h (230VAC) -25-+70 °C -40-+85 °C 5-95 %	
Power Output Output voltage: Software Diagnostics: Ambient conditions MTBF: Operating temperature: Storage/transport temperature: Relative humidity (non-condensing): Mechanical construction Dimensions (WxHxD):	48 - 56 V DC (typ. 48 V) externally adjustable LED and relay contact 509000 h (230VAC) -25-+70 °C -40-+85 °C 5-95 % 39 mm x 124 mm x 117 mm	

Mechanical stability

IEC 60068-2-6 vibration:	Operating: 2 500Hz 2g
IEC 60068-2-27 shock:	20 g, 11 ms duration

EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD):	± 8 kV contact discharge; ± 15 kV air discharge
EN 61000-4-3 electromagnetic field:	20 V/m (80 MHz 2700 MHz)
EN 61000-4-4 fast transients (burst):	2 kV power lines, 2kV data line
EN 61000-4-5 surge voltage:	power lines: 2 kV (line/earth), 1 kV (line/line)
EN 61000-4-6 Conducted Immunity:	10 V (150 kHz 80 MHz)

EMC emitted immunity

Approvals	
Basis Standard:	CE
Safety of industrial control equipment:	cUL 508
Safety of information technology equipment:	cUL 60950-1
Railway norm:	EN50121-4

EN 55032 Class A

Reliability

Guarantee:	24 months (please refer to the terms of guarantee for detailed information)

Scope of delivery and accessories

_		
Scope	of do	livon

Scope of delivery:	Rail power supply, Description and operating manual
Further Instructions	
Product Documentation:	https://www.doc.hirschmann.com
Certificates:	https://www.doc.hirschmann.com/certificates.html
History	

Update and Revision:

Revision Number: 0.84 Revision Date: 04-17-2024

Variants

Item # Туре 942200001 RPS 260/PoE EEC

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Hirschmann:

RPS 260/POE EEC