Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



XCZ1 Multi-Conductor - Z Cross-Connect Wire

For more Information please call

1-800-Belden1



General Description:

CAT3 (16MHz), 1-Pair, U/UTP-Unshielded, Premise Cross-Connect Cable, 24 AWG solid bare copper conductors, PVC insulation

Usage (Overall)

Suitable Applications: Cross-Connect, Interconnect

Physical Characteristics (Overall)

Conductor

AWG:

Pairs AWG Stranding Conductor Material
1 24 Solid BC - Bare Copper

Total Number of Conductors: 2

Insulation

Insulation Material:

Insulation Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Cabling Color Code Chart:

Color BLUE & WHITE WHITE & BLUE

Overall Nominal Diameter: 0.914 x 1.829 mm

Mechanical Characteristics (Overall)

UL Temperature Rating:	60°C
Bulk Cable Weight:	7.441 Kg/Km
Max. Recommended Pulling Tension:	66.723 N
Min. Bend Radius/Minor Axis:	25.400 mm
Min. Bend/Installation:	25.400 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	UL444
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	08/19/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Page 1 of 2 11-08-2019

Detailed Specifications & Technical Data





XCZ1 Multi-Conductor - Z Cross-Connect Wire

Other Specification:	Meets Category 3 transmission performance requirements as specified by TIA/EIA 568 B-2		
Flame Test			
UL Flame Test: UL1685 UL Loading			
Plenum/Non-Plenum			
Plenum (Y/N):	No		
Reference (Overall)			
Previous Part Number:	22208010, 22208067, 22208068		

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
XCZ1 D87500	500 FT	3.500 LB	BLUE/WHITE & WHITE/BLUE		CAT3 1PR X-CONN REEL
XCZ1 D921000	1,000 FT	4.000 LB	BLUE/RED & RED/BLUE		CAT3 1PR X-CONN REEL
XCZ1 E031000	1,000 FT	4.000 LB	BLUE/YELLOW & YELLOW/BLUE		CAT3 1PR X-CONN REEL
XCZ1 E031000B	305 MT	1.220 LB	BLUE/YELLOW & YELLOW/BLUE		CAT3 1PR X-CONN REEL

Revision Number: 1 Revision Date: 08-14-2013

© 2019 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express,

statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

XCZ1 D87500 XCZ1 D921000 XCZ1 E031000