# **Detailed Specifications & Technical Data**

#### **ENGLISH MEASUREMENT VERSION**



#### A0266828 Modular Connectors - BIX CONNECTOR 25-PAIR

For more Information please call

1-800-Belden1



#### **General Description:**

#### **BIX CONNECTOR 25-PAIR**

## Usage (Overall)

Suitable Applications:	IBDN System 1200, ISO Class E, 100BASE-T	
Related Parts:	Compatible with BIX patch cord, BIX Cross Connect System	

#### **Physical Characteristics (Connectivity)**

#### **Dimensions**

Dimensions:

Height (in.)	Width (in.)	Depth (in.)
0.310	6.630	1.280

#### Materials

#### Materials:

Description	Type	Material
Front Connection	IDC	Copper Allow with Nickel Plating
Rear Connection	IDC	Copper Allow with Nickel Plating
Connector Body		Plastic - UL940V-0

#### Weight

Weight: 0.110 lbs.

### Packaging

Packaging: packaged in carton. Standard pack of 20 units.

## **Mechanical Characteristics (Connectivity)**

#### Termination Interface: **Termination Connection**

**Tool Compatibility:** 

Other Standards

Rear	Gas Tight IDC Connection	200 terminations		
Storage Temperature Range:		-40°C To +70°C		
Installat	ion Temperature Range:		-10°C To +60°C	
Operatir	ng Temperature Range:		-10°C To +60°C	

BIX Connecting Tool (A0270165)

ECC Part 68 Subpart F JEC 60603-7

#### **Applicable Specifications and Agency Compliance (Overall)**

Gas Tight IDC Connection | 200 terminations

#### **Applicable Standards & Environmental Programs**

Other Standards.	Tee Falt 00, Subpart 1, IEE 00003-7	
EU Directive 2002/95/EC (RoHS):	Yes	
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006	
Telecommunications Standards:	Category 5e - TIA 568.C.2	
Third Party Performance Verification:	ETL - Verified Category 5e	
Safety Listing:	ACA, Bi-national Standard Listed	
Guitability		

#### Su

Suitability - Indoor: Yes - Indoor

## **Transmission Characteristics (Connectivity)**

Dielectric Strength:	1,000 V RMS @ 60 Hz for 1 minute	
Current Rating:	1.500 A	
Insulation Resistance:	100 M-Ohm Minimum	
Max. Contact Resistance:	1 m-Ohm	

Page 1 of 2

## **Detailed Specifications & Technical Data**

#### **ENGLISH MEASUREMENT VERSION**



#### A0266828 Modular Connectors - BIX CONNECTOR 25-PAIR

#### Notes (Overall)

Notes: For more information visit our web site at http://www.belden.com

Notes (Cont'd.): Suitable for 22 to 26 Wire Gauge

**Product Family** 

#### **Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
A0266828	1 EA	0.222 LB			BIX DIST.CONNECT 25-PAIR 1A

Revision Number: 0 Revision Date: 03-27-2017

© 2017 Belden, Inc

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: