PLCC2 SMD Top View Package LED SMTL2-GC, GREEN



SMTL2-GC


- **Industry Standard PLCC2 Footprint**
- Low Profile Package
- **High Luminous Intensity**
- Wide Viewing Angle
- **High Power Efficiency**




Bivar SMTL2 LED is offered in an industry standard PLCC2 package with high luminous intensity and wide viewing angles. The miniature package is ideal for small scale applications such as illumination, general indication, and backlighting. Low power consumption and excellent long life reliability are suitable for battery powered equipment. The robust package is ideal for harsh working environments and can be used in clusters for high luminous applications. Wide variety of color and intensity combinations are available to meet any illumination needs. Bivar SMTL2 LED is packaged in standard tape and reels for pick and place assemblies.

Part Number	Material	Emitted Color	Lumen Typ. mcd	Lens Color	Viewing Angle
SMTL2-GC	GaP	Green	40	Water Clear	120°

Outline Dimensions





- Outline Drawings Notes:
 1. All dimensions are in inches [millimeters].
- 2. Standard tolerance: ±0.010" unless otherwise noted.







PLCC2 SMD Top View Package LED SMTL2-GC, GREEN



Absolute Maximum Ratings

 $T_A = 25^{\circ}C$ unless otherwise noted

Power Dissipation	72 mW
Continuous Forward Current	30 mA
Peak Forward Current ¹	100 mA
Reverse Voltage	5 V
Derating Linear From 25°C	0.4 mA/°C
Operating Temperature Range	-40 ~ +85°C
Storage Temperature Range	-40 ~ +100°C
Lead Soldering Temperature (1.6 mm from body) ²	260°C
Electrostatic Discharge (HBM)	2000 V

Electrical Characteristics

 $T_A = 25$ °C & $I_F = 20$ mA unless otherwise noted


Emitting Color	Forward Voltage (V) ¹		Recommend Forward Current (mA)	Reverse Current (µA) V _R =5V	Dominant Wavelength (nm) ²		Luminous Intensity (mcd) ³		Viewing Angle 2 Θ ½ (deg)	
	TYP	MAX	TYP	MAX	MIN	TYP	MAX	MIN	TYP	TYP
Green	1.9	2.4	20	100	564	570	574	20	40	120

Notes: 1. Tolerance of Forward Voltage: ±0.05V.

- 2. Tolerance of Dominant Wavelength: ±0.1nm.
- 3. Tolerance of Luminous Intensity: ±15%.

Directivity Radiation

 $T_A = 25$ °C unless otherwise noted



Bivar reserves the right to make changes at any time without notice

Notes: 1. 10% Duty Cycle, Pulse Width ≤ 0.1 msec.

^{2.} Solder time less than 5 seconds at temperature extreme.

PLCC2 SMD Top View Package LED SMTL2-GC, GREEN



Typical Electrical / Optical Characteristics Curves

 $T_A = 25$ °C unless otherwise noted

Relative Spectrum Emission $I_{rel} = f(I)$, $T_A = 25$ °C , $I_F = 20$ mA V(I) = Standard eye response curve




Fig.1 Relative Luminous Intensity vs. Wavelength

Forward Current $I_F = f(V_F)$ $T_A = 25$ °C




Fig.2 Forward Current vs. Forward Voltage

Relative Luminous Intensity I_V/I_V (20 mA) = f (I_F) $T_A = 25$ °C





Fig.3 Relative Luminous Intensity vs. Forward Current

Ambient Temperature vs. Allowable Forward Current




Ambient Temperature TA (°C)

Fig.4 Forward Current vs. Ambient Temperature

PLCC2 SMD Top View Package LED SMTL2-GC, GREEN




Recommended Soldering Conditions



Tape and Reel Dimensions


Note: 2000 pcs/Reel



- Outline Drawings Notes:
 1. All dimensions are in inches [millimeters].
 2. Standard tolerance: ±0.010" unless otherwise noted.

PLCC2 SMD Top View Package LED SMTL2-GC, GREEN





Outline Drawings Notes:


- 1. All dimensions are in inches [millimeters].
- 2. Standard tolerance unless otherwise noted: X.XXX ± 0.010"

X.X ± 0.1"

Packaging and Labeling Plan

Note: 1 Reel / Bag

Sealed ESD and Moisture Barrier Bag



Part No.	XXXX-XXX-XXX			
Prod. No.	XXXX-XXX-XXX			
PO No.	XXX			
Lot No.	XXXXXXXX			
Q'ty:	X.XXX PCS			
Q.C.	XXX BIN			
Date:	2008.XX.XX			

Internal Quality Control Label

Bivar, Inc.

MSL4

4 Thomas, Irvine, CA 92618-2593 LOT: XXX.XXXXXXXX



Part: XXXX-XXX

Quantity: X,XXX

RoHS Compliant

Bivar Standard Packaging Label

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Califia: SMTL2-GC